Product data sheet Characteristics

QO230C QO Mini CB 30 A 2P 120/240 V 10 kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility





Price*: 67.00 USD



Main

Wichiii		•
Product or component type	Miniature circuit-breaker	
Range of product	QO	
Line Rated Current	30 A	*
System Voltage	120 V AC 120/240 V AC 48 V DC	# # # # # # # # # # # # # # # # # # #
Mounting mode	Plug-in	
Poles description	2P	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	• • • • • • • • • • • • • • • • • • •
Electrical connection	Pressure plate	
Type of packing	Clam packaging	9

Complementary

Breaking capacity	10 kA at: 120/240 V AC 5 kA at: 48 V DC 10 kA at: 120 V AC	setitute for a
Number of spaces required	2	w.
AWG gauge	AWG 14AWG 8 (copper or aluminium)	
Height	3 in	
Depth	2.91 in	
Width	1.5 in	. <u></u>

Environment

LIMIOIIIIEII		5
Product certifications	UL listed	v
	CSA	, Ā
Ambient air temperature for operation	104 °F (40 °C)	<u>i</u>

Ordering and shipping details

Category	01342 - QO 2 POLE CARDED BRKRS.
Discount Schedule	CPQ
GTIN	00047569522185
Nbr. of units in pkg.	3
Package weight(Lbs)	0.589999999999997
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	