Product data sheet Characteristics

Q0124L125PGC

QO LoadCTR, Main Lugs, 125A, 1PH-3W, 24SP, NEMA1, Incl. Gnd.Bar, PON, Comb. CV

Product availability: Stock - Normally stocked in distribution facility



Price*: 572.00 USD



Main

· · · · · · · · · · · · · · · · · · ·		2
Product or component type	Load Center	
Range of product	QO	90
Load center type	Main lugs	‡
Line Rated Current	125 A	
Number of spaces	24	<u>a</u>
Short-circuit current	65 kA	<u>}</u>
Number of circuits	24	
Number of tandem circuit breakers	0	
Phase	1 phase	
		7

Complementary

AWG gauge	AWG 6AWG 2/0 (aluminium/copper)	
NEMA degree of protection	NEMA 1 indoor	. <u>v</u>
Cover type	Combination flush/surface cover	2
Device composition	Grounding bar included (not installed)	
Electrical connection	Lugs	### ####
Wiring configuration	3-wire	
Material	Tin plated copper busbar	
Enclosure material	Welded sheet steel	
Surface finish	Baked enamel grey	
Box number	7	
Product certifications	UL listed	
Height	531 mm	
Width	14.25 in (362 mm)	

Ordering and shipping details

Category	10003 - QO PON 1PH LC,12-60 CKT, ML N1
Discount Schedule	DE3A
GTIN	00785901978374
Nbr. of units in pkg.	1
Package weight(Lbs)	20.1000000000001
Returnability	Υ
Country of origin	US

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov