Product data sheet Characteristics

HOM230CP MINIATURE CIRCUIT BREAKER 120/240V 30A

Product availability: Stock - Normally stocked in distribution facility





Price*: 60.00 USD



Main

1		
Main		
Product or component type	Miniature circuit-breaker	
Range of product	Homeline	
Line Rated Current	30 A	
Product certifications	UL listed	
System Voltage	120/240 V AC	
Mounting mode	Plug-in	
Poles description	2P	
Short-circuit current	10 kA	
Number of spaces required	2	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	
Electrical connection	Clamp terminal for 2 cables	
AWG gauge	AWG 14AWG 8 for 1 cable(s) (aluminium/copper) AWG 14AWG 10 for 2 cable(s) (copper)	
Type of packing	Consumer packaging	
Height	3.13 in	
Width	2 in	
Depth	2.98 in	
Environment		
Ambient air temperature for operation	104 °F (40 °C)	
Ordering and shipping details		
Category	01346 - HOM 2 POL BULK BRKR 15-60A	
Discount Schedule	CPH	
GTIN	00047569062773	
Nbr. of units in pkg.	5	
Av. 42, 2040		

Environment

Ambient six temperature for exerction	404 °F (40 °C)
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01346 - HOM 2 POL BULK BRKR 15-60A
Discount Schedule	СРН
GTIN	00047569062773
Nbr. of units in pkg.	5

Package weight(Lbs)	0.6700000000000004
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

HOM230CP is replaced by:



Homeline Plug-on Circuit Breakers HOM230 MINIATURE CIRCUIT BREAKER 120/240V 30A

Qty 1

Reason for Substitution: End of life | Substitution date: 01 January 2017