Product data sheet Characteristics

HOM220C MINIATURE CIRCUIT BREAKER 120/240V 20A

Product availability: Stock - Normally stocked in distribution facility





Price*: 60.00 USD



Main

The state of the s		
1		
Main		
Product or component type	Miniature circuit-breaker	
Range of product	Homeline	
Line Rated Current	20 A	
Product certifications	UL listed	
System Voltage	120/240 V AC	
Mounting mode	Plug-in	
Poles description	2P	
Short-circuit current	10 kA	
Number of spaces required	2	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	
Electrical connection	Clamp terminal for 2 cables	
AWG gauge	AWG 14AWG 8 for 1 cable(s) (aluminium/copper) AWG 14AWG 10 for 2 cable(s) (copper)	
Type of packing	Clam packaging	
Height	3.13 in	
Width	2 in	
Depth	2.98 in	
Environment		
Ambient air temperature for operation	104 °F (40 °C)	
Ordering and shipping details		
Category	01345 - HOME 2 POLE CARDED BRKRS.	
Discount Schedule	CPH	
GTIN	00047569070990	
Nbr. of units in pkg.	1	
Aug 40, 2049		

Environment

Ambient a	air temperature	for operation	104 °F	(40	°C)
-----------	-----------------	---------------	--------	-----	-----

Ordering and shipping details

Category	01345 - HOME 2 POLE CARDED BRKRS.
Discount Schedule	СРН
GTIN	00047569070990
Nbr. of units in pkg.	1

Package weight(Lbs)	0.71999999999997	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW) Compliant - since 1323 - Schneider Electric declaration of conformity		
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	