Product data sheet Characteristics

HOM4080M200PC HOM INDR 200A MB 40/80CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 1019.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	200 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker (1) 2P 200 A 120/240 V AC main supply ready assembled	

Complementary

Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main breaker	
Line Rated Current	200 A	
Number of spaces	40	
Number of circuits	80	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Circuit breaker (1) 2P 200 A 120/240 V AC main supply ready assembled	
Complementary		
Snort-circuit current	22 kA	
	22 kA 40	
Number of tandem circuit breakers		
Number of tandem circuit breakers Phase	40	
Number of tandem circuit breakers Phase System Voltage	40 1 phase	
Number of tandem circuit breakers Phase System Voltage AWG gauge	40 1 phase 120/240 V AC	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper)	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire Gray baked enamel	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material Enclosure material	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire Gray baked enamel Tin plated aluminium busbar	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material Enclosure material Surface finish	1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire Gray baked enamel Tin plated aluminium busbar Welded sheet steel	
Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material Enclosure material Surface finish	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire Gray baked enamel Tin plated aluminium busbar Welded sheet steel Baked enamel grey	
Short-circuit current Number of tandem circuit breakers Phase System Voltage AWG gauge Wiring configuration Cover finish Material Enclosure material Surface finish Box number Environment	40 1 phase 120/240 V AC AWG 4250 kcmil (aluminium/copper) 3-wire Gray baked enamel Tin plated aluminium busbar Welded sheet steel Baked enamel grey	

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901977575
Nbr. of units in pkg.	1
Package weight(Lbs)	37.67000000000002
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	