

# Product data sheet

## Characteristics

# HOME250SPA

Homeline, spa panel, 50 A, 120/240 V, 1 PH, ML, 2 SP, N3R, encl breaker

Product availability : Stock - Normally stocked in distribution facility



Price\*\* : 473.00 USD



### Main

Product or component type	Spa panel
Marketing Trade Name	Homeline
Load center type	Main lugs
Line Rated Current	50 A
Number of spaces	2
Number of circuits	4
Enclosure Rating	NEMA 3R outdoor
Cover type	Surface cover
Included Options	Circuit breaker 1) 2P 50 A 120/240 V AC ready assembled

### Complementary

Short-circuit current	10 kA
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 8...AWG 6 aluminium/copper
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	1R
Height	9.37 in (238 mm)
Width	4.88 in (124 mm)
Depth	4.02 in (102 mm)

### Environment

Ambient air temperature for operation	23 °F (-5 °C)
---------------------------------------	---------------

Mar 2, 2020

104 °F (40 °C)

Product certifications	UL CSA
------------------------	-----------

### Ordering and shipping details

Category	00185 - MISC. HOM LOAD CENTERS
Discount Schedule	DE3C
GTIN	00785901230540
Returnability	Yes
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------