


SUPER REMOVER FOR GLUE

LIMITED WARRANTY: THE SELLER AND THE MANUFACTURER WILL NOT ACCEPT LIABILITY FOR MORE THAN THE REPLACEMENT OF THIS PRODUCT.

Directions



Interior: Use only in a well-ventilated area.

Exterior: avoid using the Super Remover under direct sunlight. Use the product at a temperature between 10 °C and 25° C in a well-ventilated area. Do not use the product on a rainy day because the Super Remover is water soluble. Do not use on a day with strong wind because the Super Remover is a volatile solvent.

Pour the Super Remover for GLUE directly onto the surface to be stripped. Using a pure bristle paint brush, spread the product so that a layer at least 3 mm thick, i.e., the thickness of two 2\$ coins, covers the surface to be stripped. Dab the angles, moldings and patterns so the product can act in all gaps and corners. Let stand at least 15 minutes. Do not rush this step but do not let the product dry on the surface. Let it work longer if the coating is very resistant or if there are many layers.

Once the surface is ready to be stripped, use a spatula or a scraper to remove residues. Using a stripping pad and a bit of Super Remover for GLUE, remove any coating still remaining. Use a pointed tool or sharpened wooden dowel for angles and patterns.

For wood: Always work along the wood's grain not to damage it. Once the stripping is done, if desired, use methyl hydrate to clean the surface thoroughly.

Tips and tricks

Work section by section and one section at the time to not allow the product to dry.

Under normal storage conditions (around 20°C), the product's consistency is similar to shampoo. To increase its viscosity, for example to facilitate vertical surface stripping,

Sans frais/ Toll free Tel: 1 866 772-2948 Fax: 1 866 427-1040 info@superremover.com

Distributions J. Des Serres



store the closed Super Remover for GLUE container one hour in the refrigerator before applying the product. It will be thicker and thus slide slower along the surface.

Plan to use a rather narrow scraper (around 5 cm in width), because the wider the scraper, the less contact it makes with the surface. Indeed, you will have to work double time to remove the residues left behind by the initial scraping!

Do not use on fiberglass, vinyl, linoleum, rubber, acrylic and plastics.

Consult your municipality's regulations for safe disposal of the product.

Warning

- 1. Always take all necessary precautions in order to avoid contact with eyes and skin. Wear a mask, chemical-resistant neoprene coated gloves and safety glasses. Do not breathe vapors.
- 2. In case of contact with skin, rinse with water to neutralize the product.
- 3. If in eyes, rinse with water for at least 20 minutes.
- 4. If inhaled, move the person to fresh air.
- 5. If swallowed, get immediate medical assistance. Do not induce vomiting.
- 6. Work in a fresh place away from sunshine and in a well-ventilated area.
- 7. Keep away from any heat source, flames or sparks.
- 8. Keep out of reach of children.

Sans frais/ Toll free Tel: 1 866 772-2948 Fax: 1 866 427-1040

info@superremover.com