

PRODUCT DATASHEET

Contractor Series LED PAR Lamps 13W PAR38 5000K FL 45 2PK

SYLVANIA Contractor Series PAR Lamps | PAR Lamps rated up to 11,000 hours life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Beam angle: 45°
- 11,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- No warm-up time, instant-on with full light output and stable color
- Reduces energy consumption up to 88 %
- Lasts 4 times longer than halogen lamps
- 3-year limited warranty



TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED13PAR38850FL4510YVRP2
Abbrev. With Packaging Info.	LED13PAR38850FL4510YVRP2 12/CS 2/SKU
SKU UPC	0046135797361
NAED	79736
Family Brand Name	10YV
General Description	LED PAR38, 13W, 82CRI, 1175 Lumen, 5000K, 11000 life

Electrical data

Nominal Wattage	13.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	90 W
Centerbeam Candlepower (cp)	1,250 cd

Photometrical data

Lumens	1175 lm
Efficacy	90
Color Temperature/CCT	5000 K
Color Rendering Index (CRI)	82
Light color	850

Dimensions & Weight

Overall length	130.00 mm
Diameter	4.76 in
Product weight	0.3 lb

Materials & Colors

Bulb shape	PAR38
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Lifespan

Average Rated Life (hr)	11000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / CSA / FTC / FCC / cULus
-----------------------	--------------------------------

Logistical data

SKU Qty	2
Case Qty	12
Case Length (in)	16.750
Case Width (in)	15.875
Case Depth (in)	5.875
Case Cube (ft)	0.904
Case Weight (lbs)	5.688
SKU UPC	0046135797361
Pallet Qty	504

Safety advice

- Not for use in totally enclosed fixtures.
- Suitable for use in UL rated fixture where protected from the weather.
- Non-dimmable.
- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	Contractor Series LED PAR Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.