



PRODUCT DATASHEET

F T12 15 DSW RP

SYLVANIA T12 Preheat (Starter required) Lamps | Dependable T12 preheat lamps for fixtures requiring starter-based operation



Areas of application

- Residential
- Undercabinet lighting
- Task Lighting

Product features

- Use where existing T12 fixtures utilizing starters are still installed
- Average Rated Life of 9,000 hours (3 hrs. per start)
- Designer and Rare Earth phosphor provide improved lumen maintenance



TECHNICAL DATA

Additional product data

Base type	G12
Mercury content	20.0 mg
Ordering Abbreviation	F15T12/DSW/RP
Abbrev. With Packaging Info.	F15T12DSWRP 6/CS 1/SKU
SKU UPC	0046135215513
NAED	21551
Family Brand Name	Designer Warm White
General Description	15W T12 preheat fluorescent lamp, Designer Warm White rare earth phosphor, 3000K color temperature, 70 CRI

Electrical data

Nominal Wattage	15.00 W
Nominal voltage	47.00 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Lumens	770 lm
Efficacy	51
Color Temperature/CCT	4100 K
Color Rendering Index (CRI)	60
Light color	641
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	556.49 mm
Diameter	1.59 in
Tube diameter	38 mm
Product weight	0.22 lb

Materials & Colors

Bulb shape	T12
------------	-----

Application & Mounting

Starting Method	PREHEAT
-----------------	---------

Lifespan

Service life	4000 h
Average Rated Life (hr)	9000

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	18.750
Case Width (in)	5.813
Case Depth (in)	3.938
Case Cube (ft)	0.248
Case Weight (lbs)	2.276
SKU UPC	0046135215513
Pallet Qty	1,056

Safety advice

- Preheat lamp, starter required.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).
- Contains Mercury – Dispose of according to Local, State or Federal laws

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.