



Acrylic Crack Filler for Asphalt



(70978054 / 1 L)

UPDATE

April 26, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Driveways, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Fills cracks 1.5 cm (½ in) wide or less
- Stops deterioration caused by water and frost
- Easy to apply

DESCRIPTION

Techniseal® Crack Filler is designed for cracks 1.5 cm wide or less. Made of thermoplastic acrylic and silica, it is more durable than ordinary tar-based products. Containing a high percentage of solids, it dries without losing volume. It protects against damage caused by water and freeze-thaw cycles. Easy to apply, it adheres strongly to inner walls of cracks and remains flexible to allow for asphalt movements.

Note: For cracks wider than 1.5 cm, use Techniseal® Patching Compound.

DIRECTIONS

BEFORE YOU BEGIN

- Wear adequate protective clothing. • **ALWAYS TEST** on a small hidden area to ensure that result meets your expectations.

SURFACE PREPARATION

Clean cracks with a water jet; let excess water drain. Fill deep cracks with fine sand up to 2 cm below the surface.

APPLICATION

Shake well before opening the container. Cut nozzle at an angle to the desired diameter. Fill cracks to surface level. Let dry for 24 hours before applying sealant or driving on the surface.

Cleaning of tools: Use mineral spirit.

For a uniform appearance and maximum protection, apply a Techniseal® Protector for Asphalt to the entire surface.

IMPORTANT

Do not apply at a temperature lower than 10°C. Store at a temperature above 15°C.

PACKAGING

Product code	Retail Size	Units per box	Units per pallet
70978054 (142-711)	1 L	6	480

WARNING

KEEP OUT OF REACH OF CHILDREN. FIRST AID TREATMENT If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.