



Instant Leak Sealer



(70978078,70978079,70978077,70978076 / 369 g)

UPDATE

May 9, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Adheres to most material: shingles, sheet metal, aluminum, copper, glass, wood and PVC

PROPERTIES

- Works on gutters, roofs, concrete, heating ducts, PVC, etc.
- Stays flexible and waterproof
- Will not crack or peel
- Seals out rust and corrosion
- Covers up to 1.8 m² (20 sq.ft.)

DESCRIPTION

Techniseal[®] Instant Leak Sealer is a unique spray product that easily and quickly seals cracks. It leaves an abrasion resistant coating that stays flexible, will not crack and is impervious to water. It seals out rust and corrosion. Product can be painted on.

DIRECTIONS

Shake well. Do not apply below 5°C or above 30°C. Apply only to a clean and dry surface. Spray surface with short, even strokes from a distance of 25 to 30 cm (10 to 12"). Multiple coats may be applied. Allow 20 to 30 minutes between coats. For a more uniform finish, use a 2.5 cm (1") paintbrush to spread the product evenly.
Heating ducts: Wait until ducts have cooled down before spraying sealer.

COVERAGE

Covers up to 1.8 m² (20 sq.ft.).

PACKAGING

Colour	Product code	Retail Size	Units per box
Clear	70978078 (140-801)	369 g spray can	12
Black	70978079 (140-811)	369 g spray can	12
White	70978077 (140-821)	369 g spray can	12
Aluminium	70978076 (140-831)	369 g spray can	12

WARNING

CONTAINER MAY EXPLODE IF HEATED. CONTENTS MAY CATCH FIRE. Do not smoke. Do not puncture. Do not burn. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat. **KEEP OUT OF REACH OF CHILDREN. FIRST AID TREATMENT** If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person to fresh air.

SHIPPING

Land

Transported in limited quantity

Sea

UN1950

Aerosols

Class: 2.1

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.