



RoofSkin[™] Elastomeric Sheet Metal Coating

10-Year Warranty

(60102188 ,60102190,60102194,60102192 / 15 L 60102189,60102191,60102195,60102193 / 3.78 L)



UPDATE

April 23, 2016

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com Canada and U.S.A.: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Farm, commercial, industrial and residential structures: barns, silos, churches, warehouses, houses, sheds, cottages, etc.
- Sheet metal or asphalt shingles or membranes sloped or vertical surfaces

PROPERTIES

- Prevents deterioration due to oxidation; extends the life of roofing
- No primer required; adheres to rust
- Allows for a change of roofing colour

DESCRIPTION

Made of 100% acrylic elastomeric resin, RoofSkin[™] Elastomeric Sheet-Metal Coating extends the life while improving the original appearance of your roofing. It modifies or rejuvenates the colour of the roof following partial repairs. Ultra-adherent, it forms a protective coat against the elements and the harsh Canadian climate; it prevents deterioration caused by frost, rain and UV rays. Water-based and free of bitumen, RoofSkin[™] does not release unpleasant fumes, and it is environmentally-friendly.

DIRECTIONS

BEFORE YOU BEGIN

Do not apply to a flat roof or to roofing covered with tar, gravel or a rubber membrane.
If the roof is leaking, make the appropriate repairs.
Do not apply to roofing that is deteriorated in such a way that it needs to be replaced.
Access to roof safely. Use appropriate safety measures during work.
Wear adequate protective clothing and

goggles. • **ALWAYS TEST** product on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure that result meets your expectations (see Warranty).

SURFACE PREPARATION (ESSENTIAL)

- 1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
- 2. Remove lichens, mildew or fungus with Techniseal® Roof Cleaner (140-500).
- 3. Remove loose rust and paint residue with a steel brush or a pressure washer.
- 4. Replace heavily damaged sheet-metal sections.
- 5. Around vents, chimneys, flues and repaired areas, replace tar with Techniseal® Weatherproof Sealant (140-701).
- 6. Punch badly hammered nail heads.
- 7. Prime cracks, nail heads and repaired sections with Techniseal® Weatherproof Sealant (140-701).
- 8. Remove any debris with a leaf blower.

APPLICATION

Application Conditions:

- Roofing must be clean, dry and warm to the touch.
- Preferably apply early in the morning; temperature must be between 10°C and 25°C.
- No rain forecasted for the next 24 hours.
- Use a consistent application method over entire surface.

Required Tools:

- Trimming paintbrush
- Techniseal® Thick-Pile Roller (145-940)
- Airless sprayer for high-viscosity paints (optional)

Do not dilute. Shake well or stir product before and during application. Intermix cans of the same product to ensure colour uniformity.

Trim using a paintbrush. Using the sprayer or the roller, saturate the surface with a first coat of product. Let dry for 18 to 24 hours, then apply a second coat following the same method.

CAUTION

• This product is not intended to seal leaks or to waterproof roofing. • Do not apply to a roof that does not have proper ventilation or insulation. • Application to excessively hot roofing will make coating dry too quickly, which will leave overlap marks. • This product will make the surface more slippery when wet. • Rust stains could be brought to the surface if the application ratio is not followed.

COVERAGE

3.78 L cover up to 14 m² (150 sq. ft.) per coat. / 15 L cover up to 56 m² (600 sq. ft.) per coat. For the warranty to apply, it is mandatory to apply two coats using an approximate application ratio of 1 litre per 2 m² (21 sq. ft.). Coverage will vary according to roof type and condition. It is recommended that a small area be tested to determine the exact amount needed.

STORAGE

Keep from freezing. Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

Colour	Product code	Retail Size	Units per box	Units per pallet
Aluminum	60102189 (140-453)	3.78 L	4	180
	60102188 (140-457)	15 L	—	60
White	60102191 (140-463)	3.78 L	4	180
	60102190 (140-467)	15 L	—	60
Red	60102195 (140-473)	3.78 L	4	180
	60102194 (140-477)	15 L	—	60
Blue	60102193 (140-483)	3.78 L	4	180
	60102192 (140-487)	15 L	_	60

PACKAGING

WARNING

MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN. FIRST AID TREATMENT Contains:** Ethanediol; Zinc oxide. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

Coating Category : Non-Bituminous Roof Coating (VOC Concentration Limit : 250g/L)

SHIPPING

<u>Land</u> NOT REGULATED <u>Sea</u> UN3082 Environmentally hazardous substance, liquid, n.o.s. (Zinc oxide) PG: III Class:9

LIMITED 10-YEAR WARRANTY

Techniseal[®] warranties RoofSkin[™] against manufacturing defects. The warranty will be void if product becomes defective due to freezing. During the first year following purchase, Techniseal[®] will replace the product if it fails to perform within specifications. After this first year, the quantity replaced will drop by 10% for each subsequent year. This warranty is limited to the replacement of the product and does not cover labour costs. This warranty will be void if: product was applied on a defective roof; an insufficient amount of product was applied (see coverage information on label); application was not performed according to directions on the label. User should make sure that product meets his or her needs by carrying out a test on a 0.4 m² (4 sq. ft.) surface, under anticipated conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq. ft.). A proof of purchase will be required for any claim. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages.