



Weatherproof Sealant

(70978066 / 300 ml)

UPDATE

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
 Canada and U.S.A.: dial 1 800 465-7325
 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Adheres to most material: shingles, sheet metal, aluminum, copper, glass, wood and PVC

PROPERTIES

- Seals instantly, even under water, snow and ice
- Adheres to most material
- High Elasticity Formula

DESCRIPTION

Weatherproof Sealant from Techniseal® adheres to almost any surface: asphalt shingles, sheet metal, aluminium, copper, glass, wood and PVC, found on a sloped roof. It is also compatible with gutters and similar structures. Highly recommended before the application of Elastomeric Roof Coating from Techniseal®.
 Not compatible with polysterene foam. Not resistant to solvents.

DIRECTIONS

Ready to use • Do not dilute • Remove all dirt and debris • With a brush or a rubber spatula, apply one thick coat perpendicular to the crack • For cracks wider than 5mm; following the first application and while still fresh, apply fiberglass fabric, then apply a second coat a few days later.

PACKAGING

| Colour | Product code | Retail Size | Units per pallet | Units per box |
|--------|---------------------------|-------------|------------------|---------------|
| Clear | 70978066 (140-701) | 300ml tube | 1200 | 20 |

WARNING

CONTENTS MAY CATCH FIRE. Do not smoke. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. **KEEP OUT OF REACH OF CHILDREN. USE ENTIRE CONTENTS ON OPENING. This container is not child resistant once opened. FIRST AID TREATMENT** If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person to fresh air.

SHIPPING

Land

Exempted under the regulation of the transport of hazardous materials (see section 1.33).

Packaging class III (flash point > 37.8°C)

Sea

UN1133

Adhesives

Class: 3

PG: III

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal® can not guarantee the results. Techniseal warranty is limited to the replacement of product. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.