

Touch 'n Foam

READY-TO-USE FOAM



POLYURETHANE FOAM SEALANTS

• ULC-LISTED • FILLS / SEALS / INSULATES • MINIMIZES ENERGY LOSS • REUSABLE • PAINTABLE / SANDABLE



TRIPLE EXPANDING SEALANT



- 3 times the expansion to fill gaps greater than 2.5 cm
- For larger holes and gaps
- Blocks insects and other pests
- Meets ULC S-102 (ASTM E-84) Class A




FLAME RESISTANT SEALANT



- Approved fire block penetration sealant
- Passes ASTM E-814 (modified), UL-1715, and UL-94 V-0
- Type V residential fire block
- Flame spread 0, smoke developed 5
- Easy-to-identify orange color
- Meets ULC S-102 (ASTM E-84) Class A



MINIMUM EXPANDING SEALANT



- Fills and seals small cracks and gaps
- Water resistant



Exclusive
All-Season Formula
Cures between
-1°-49°C (30°-120°F)



EXTERIOR FILLER-ADHESIVE



- Black foam is UV resistant
- Directs water flow in and around water gardens
- Fish and plant safe
- Superior adhesive for landscaping projects
- Fills knot holes in trees to seal out pests



WINDOW & DOOR SEALANT



- Low pressure formula – won't bow window frames or door jambs
- Bright white foam
- Meets ULC S-102 (ASTM E-84) Class A
- Meets AAMA standards 812-04 for low pressure foams

PRODUCT	PRODUCT NO.	SIZE	CASE PACK	UPC	CARTON CODE	CASE DIMENSIONS
MaxFill	4001112012	340 g (12 oz.)	12	0 75650 00127 1	1 00 75650 00127 8	29,21 x 22,23 x 23,50 cm
MaxFill	4001160316	454 g (16 oz.)	12	0 75650 60316 1	1 00 75650 60316 8	29,21 x 22,23 x 28,56 cm
MaxFill	4001130107	566 g (20 oz.)	12	0 75650 00128 8	1 00 75650 00128 5	28,56 x 22,23 x 30,48 cm
HomeSeal	4001142412	340 g (12 oz.)	12	0 75650 00129 5	1 00 75650 00129 2	29,21 x 22,23 x 23,50 cm
HomeSeal	4001162416	454 g (16 oz.)	12	0 75650 62416 6	1 00 75650 62416 3	29,21 x 22,23 x 23,50 cm
HomeSeal	4001140412	566 g (20 oz.)	12	0 75650 00137 0	1 00 75650 00137 7	29,21 x 22,23 x 23,50 cm
No Warp	4001044010	340 g (12 oz.)	12	0 75650 44010 0	1 00 75650 44010 7	29,21 x 22,23 x 23,50 cm
No Warp	4001164416	454 g (16 oz.)	12	0 75650 64416 4	1 00 75650 64416 1	29,21 x 22,23 x 23,50 cm
FireBreak	4001140016	454 g (16 oz.)	12	0 75650 40016 6	1 00 75650 40016 3	29,21 x 22,23 x 28,56 cm
Landscape	4001140460	454 g (16 oz.)	12	0 75650 40460 7	1 00 75650 40460 4	29,21 x 22,23 x 28,56 cm



READY-TO-USE FOAM

POLYURETHANE FOAM SEALANTS

Property	Home Seal	MaxFill	No Warp	Fire Break	Landscape
Shelf Life	18 months (unopened)	18 months (unopened)	18 months (unopened)	18 months (unopened)	18 months (unopened)
Dry Time/ Tack Free Time	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes	Less than 30 minutes
Fully Cured	Less than 4 hours	Less than 4 hours	Less than 4 hours	Less than 4 hours	Less than 4 hours
Cutttable	Less than 2 hours	Less than 2 hours	Less than 2 hours	Less than 2 hours	Less than 2 hours
ASTM E-814 (modified)	meets	meets	meets	meets	meets
ASTM C-1536 Yield (1 cm bead - 12oz can)	109 meters	121 meters	130 meters	125 meters	125 meters
ULC S-102 Surface Burning Characteristics Fire Test (Flame/Smoke)	20/20	0/5	5/10	0/5	10/5
Underwriters Laboratories (UL/ULC) Classified Caulking & Sealants (R14175)	listed	listed	listed	listed	listed
UL 1715 (Fire Test)	—	—	—	pass	—

INSTALLATION / APPLICATION

For optimal results, first practice dispensing foam onto scrap materials (HomeSeal™ must be held in upside down position). Ensure surface area is dry, clean and free of dust, dirt, grease and other substances that may inhibit adhesion. For best results, apply in temperatures between 16° and 38°C (60° and 100°F), and with 40% or greater relative humidity. Fill gap no more than 1/3 full, allowing room for expansion. Do not overfill. Important: Foam will continue to dispense for a few seconds after releasing the trigger – keep the straw tip moving to reduce the possibility of overfilling.

TECHNICAL DATA

Shelf Life

Eighteen months in unopened container when stored between 16° and 32°C (60°–90°F), in a dry, well ventilated area.

Storage/Reuse

To store unused portion, bend straw back and attach to the knob atop the dispensing trigger. Store can upright below 32°C (90°F). Product can be reused within three weeks if stored properly. To reuse, cut the end off the straw (removing any cured foam), shake well and apply as directed.

KEEP OUT OF REACH OF CHILDREN.

First Aid

If wet foam contacts skin, do not use water to clean it off. Do not attempt to remove cured foam with solvents – cured foam wears off and is not harmful to health.

For more information call 1-800-325-6180 M-F, 8–5 Central Time, or visit our web site at www.touch-n-foam.ca.

Warranty

Convenience Products warrants its Touch 'n Foam products to be free of defects in workmanship and function. Convenience Products is not liable for any incidental, consequential or any other damages or remedies. There are no warranties that extend beyond the description herein, however, certain states have specific laws regarding limitation on incidental or consequential damages, in which case, you may have other legal rights.

Technical Services

Technical assistance, including more detailed information, product literature, test results, assistance with preparing project specifications and application training is available by contacting Convenience Products at 1-800-325-6180.



Convenience Products
866 Horan Drive, Fenton, MO 63026-2416 USA
1-800-325-6180 • www.touch-n-foam.ca

42074-3-091015-TNF