



GUN FOAM



POLYURETHANE FOAM SEALANTS



ALL-PURPOSE POLYURETHANE FOAM SEALANT

- Ideal sealant for gaps & cracks
- Excellent dispensing and control
- Outperforms fiberglass / cellulose
- Class 1 foam / UL-listed
- Bright orange foam simplifies inspections
- Approved Type V residential fireblock sealant
- Meets ASTM E-814, E-84, and UL-1715
- 24 oz. can yields up to the equivalent of 15 tubes of caulk



PRECISION FOAM APPLICATOR

- Metal barrel / trigger / internal parts
- Shockproof hand grip
- Teflon coated adaptor / basket
- Durable



WINDOW & DOOR POLYURETHANE FOAM SEALANT

- Exerts virtually no force on frames or jambs
- Excellent dispensing and control
- Outperforms fiberglass / cellulose
- Class 1 foam / UL-listed
- Bright white / sandable — paintable
- Meets AAMA standards 812-04 for low pressure foams
- 20 oz. can yields up to the equivalent of 13 tubes of caulk



POLYURETHANE FOAM CLEANER

- Removes uncured foam from tools and gun foam applicators
- Attaches to applicator to flush barrel
- Reusable dispensing
- Zero VOC formula



BLACK LANDSCAPING POLYURETHANE FOAM SEALANT

- Excellent for ponds and waterfalls
- Great for securing landscape blocks
- Safe for plants and fish
- UV resistant — won't discolor in sunlight
- Excellent for indoor / outdoor use
- 24 oz. can yields up to the equivalent of 15 tubes of caulk



PRODUCT	PRODUCT NO.	SIZE	CASE PACK	UPC	CARTON CODE	CASE DIMENSIONS (in.)
All-Purpose Gun Foam Sealant	7565002420	24 oz.	12	0 75650 02420 1	1 00 75650 02420 8	11.25 x 8.75 x 12
Window & Door Gun Foam Sealant	7565002010	20 oz.	12	0 75650 02010 4	1 00 75650 02010 1	11.25 x 8.75 x 12
Black Landscaping Gun Foam Sealant	7565002450	24 oz.	12	0 75650 02450 8	1 00 75650 02450 5	11.25 x 8.75 x 12
Polyurethane Foam Cleaner	7565028700	12 oz.	12	0 75650 28700 2	1 00 75650 28700 9	11.50 x 8.75 x 9.25
Precision Foam Applicator	7565028775	—	6	0 75650 28775 0	1 00 75650 28775 7	7 x 13 x 15.25



GUN FOAM

POLYURETHANE FOAM SEALANTS

TYPICAL PROPERTIES

	ALL-PURPOSE	WINDOW & DOOR	LANDSCAPE
Shelf Life	18 months; unopened container	18 months; unopened container	18 months; unopened container
Dry Time/Tack Free Time	Approx. 10 min. @ 50% R.H	Approx. 10 min. @ 50% R.H	Approx. 10 min. @ 50% R.H
Fully Cured	Approx. 1 hour	Approx. 1 hour	Approx. 1 hour
Cuttable	Approx. 30 min.	Approx. 30 min.	Approx. 30 min.
ASTM D-1621 Compressive Strength	11 PSI (0.77 kg/cm ²)	11 PSI (0.77 kg/cm ²)	11 PSI (0.77 kg/cm ²)
ASTM D-1622 Density	1.3-1.8 PCF	1.3-1.8 PCF	1.3-1.8 PCF
ASTM D-1623 Tensile Strength	26 PSI (1.83 kg/cm ²)	26 PSI (1.83 kg/cm ²)	26 PSI (1.83 kg/cm ²)
ASTM E-814 (modified) Fireblocking (Type V)	meets	meets	meets
Applicable Standards ICC-Evaluation Services (ICC-ESR-1926)	approved	approved	approved
ASTM C-518 R-Value	4-5/in (25 mm)	4-5/in (25 mm)	4-5/in (25 mm)
ASTM C-1536 Yield (Linear Feet)	3200 (1/4")	2100 (1/4")	3200 (1/4")
UL 723 Fire Test (Flame/Smoke)	15/25	10/15	5/10
International Building Code	complies	complies	—
International Residential Code	complies	complies	—
California Bureau of Home Furnishings and Insulation	complies	complies	complies
Underwriters Laboratories Classified Caulking & Sealants (R14175)	complies	complies	complies
UL 1715 (Fire Test)	pass*	pass	pass

*UL 1715 test was conducted on Touch 'n Foam Professional All-Purpose Gun Foam and passed without a thermal barrier.

INSTALLATION / APPLICATION

Always refer to local building codes prior to application of Touch 'n Foam sealants. Surface to receive Touch 'n Foam sealants must be dry, clean and free of dust, dirt, grease and other substances that may inhibit proper adhesion. **For best results, apply Touch 'n Foam Gun Foam sealants when surface and ambient temperatures are between 60°–100°F (16°–38°C). Temperature of chemical contents must be between 60°–100°F (16°–38°C) before dispensing. Use all chemical contents within 30 days of initial dispensing.** Always wear proper personal protective equipment, including gloves, clothing and eyewear. Use in well-ventilated area. Use Touch 'n Foam Polyurethane Foam Cleaner to clean wet foam from tools. Please refer to manufacturer's instructions or request a faxed set of instructions from Convenience Products by calling Customer Service at 1-800-325-6180.

TECHNICAL DATA

Shelf Life

Eighteen months (12 months for Low Temp) in unopened container when stored between 60°–90°F (16°–32°C), in a dry, well-ventilated area.

Storage & Disposal

Turn gun's flow control knob to closed position and store can in upright position (with gun still attached). To restart, shake well for 30 seconds, turn flow control knob to open position and dispense foam. Maximum storage: 30 days.

CAN CHANGEOVER: Once started, do not remove gun until can is empty; then purge gun and remove can. Clean gun basket with acetone or polyurethane foam cleaner. Immediately attach fresh can to prevent foam from hardening in gun.

KEEP OUT OF REACH OF CHILDREN.

WARRANTY: If product fails to perform when used as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

TECHNICAL SERVICES: Technical assistance, including more detailed information, product literature, test results, assistance with preparing project specifications and application training is available by contacting 1-888-DAP-TIPS.