

# UDIP

HOSE & TUBING

CATALOG 2017

ULTRA DYNAMIC PRODUCTS



A DIVISION OF  
**ABBOTT** RUBBER  
COMPANY, INC.




# *UDPF*

*ULTRA DYNAMIC PRODUCTS*



A DIVISION OF

**ABBOTT** RUBBER  
COMPANY, INC.

 800-852-1855

[www.udproducts.com](http://www.udproducts.com)

# INDEX

Item.....	Page
T10 Clear Vinyl Tubing .....	2-3
T12 Braided Vinyl Tubing .....	4
T14 Black Vinyl Tubing .....	4
T16 Polyethylene Tubing .....	5
T17 Black Polyethylene Tubing .....	5
T18 Red PVC Air/Spray Hose .....	6
T22 PVC Fuel Hose.....	6
T24 Micro Fuel Tubing.....	7
T28 Vinyl Garden Hose .....	7
T30 Spa Hose.....	8
T32 Pool Vacuum Hose.....	8
T34 Bilge Hose .....	9
T40 Clear PVC Suction Hose .....	9
T36 Economy PVC Discharge Hose .....	10
T38 Reinforced PVC Discharge Hose ....	10
T44 PVC Appliance Drain Hose .....	11
T45 Non Reinforced PVC Drain Hose ....	11
T60 Red Rubber Utility Hose.....	12
T62 Heater Hose .....	12
T64 Latex Tubing.....	13
T68 Vacuum Tubing.....	13
Gasket Material .....	14
Spool and Dispenser Racks .....	15
Appliance Hose .....	16-20



Clear PVC Tubing manufactured with Non-Toxic FDA compounds. Can be used for flexible lines for low pressure air, water, liquids, beverages, chemicals and gases as well as drain lines for air conditioners and dehumidifiers. Excellent resistance to mild acids and chemicals. See through design allows for visual flow. Not for use with Ice Makers or petroleum based products.

- Non-Toxic FDA Grade Compound
- Suitable for use with liquids, chemicals and gases
- Use as flexible drain line
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T10004001	1/8	3/16	100	Boxed	9.5 x 3 x 9.5	1.4	708289450188	30 PSI
T10004002	1/8	1/4	100	Boxed	9.5 x 3 x 9.5	3.1	708289450683	65 PSI
T10004003	.170	1/4	100	Boxed	9.5 x 3 x 9.5	2	708289451185	40 PSI
T10004004	3/16	5/16	100	Boxed	9.5 x 3 x 9.5	3.2	708289451680	55 PSI
T10004005	1/4	3/8	100	Boxed	14 x 4 x 14	3.9	708289452182	55 PSI
T10004006	5/16	7/16	100	Boxed	14 x 4 x 14	5.2	708289452687	50 PSI
T10004007	5/16	1/2	100	Boxed	14 x 4 x 14	7.1	708289453189	55 PSI
T10004008	3/8	1/2	100	Boxed	14 x 4 x 14	5.5	708289453684	45 PSI
T10004009	3/8	9/16	100	Boxed	14 x 4 x 14	7.9	708289454186	50 PSI
T10004010	1/2	5/8	100	Boxed	14 x 4 x 14	6.4	708289454681	30 PSI
T10004011	1/2	3/4	100	Boxed	17 x 5 x 17	13.1	708289455183	45 PSI
T10004013	5/8	7/8	100	Boxed	17 x 5 x 17	15.8	708289456180	40 PSI
T10004014	3/4	1	50	Boxed	17 x 5 x 17	9.4	708289456685	35 PSI
T10004015	1	1-1/4	50	Boxed	18 x 6 x 18	12.7	708289457286	25 PSI
T10004016	1-1/4	1-5/8	50	Boxed	18 x 6 x 18	16.3	708289457880	30 PSI
T10004017	1-1/2	1-7/8	25	Boxed	18 x 6 x 18	14.2	708289458184	30 PSI
T10005001	1/8	3/16	400	Spool	7 x 10	5.6	708289450287	30 PSI
T10005002	1/8	1/4	400	Spool	7 x 10	7.6	708289450782	65 PSI
T10005003	.170	1/4	400	Spool	7 x 10	7.2	708289451284	40 PSI
T10005004	3/16	5/16	300	Spool	7 x 10	9	708289451789	55 PSI
T10005005	1/4	3/8	250	Spool	7 x 10	10.3	708289452281	55 PSI
T10005006	5/16	7/16	200	Spool	7 x 10	9.7	708289452786	50 PSI
T10005007	5/16	1/2	150	Spool	7 x 10	9.2	708289453288	55 PSI
T10005008	3/8	1/2	100	Spool	7 x 10	5.5	708289453783	45 PSI
T10005009	3/8	9/16	100	Spool	7 x 10	8.2	708289454285	50 PSI
T10005010	1/2	5/8	100	Spool	7 x 10	6.9	708289454780	30 PSI
T10005011	1/2	3/4	75	Spool	7 x 10	9.9	708289455282	45 PSI
T10005012	5/8	3/4	100	Spool	7 x 10	8.2	708289455787	25 PSI





- Non-Toxic FDA Grade Compound
- Suitable for use with liquids, chemicals and gases
- Use as flexible drain line
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T10005013	5/8	7/8	100	Spool	11.5 x 10	16.2	708289456289	40 PSI
T10005015	1	1-1/4	50	Spool	7 x 16	13.8	708289457385	25 PSI
T10005016	1-1/4	1-5/8	50	Spool	7 x 21	17.9	708289457989	30 PSI
T10005017	1-1/2	1-7/8	50	Spool	7 x 21	31.7	708289458283	30 PSI
T10006003	.170	1/4	10	Coil	-	0.18	708289451383	40 PSI
T10006005	1/4	3/8	10	Coil	-	0.37	708289452380	55 PSI
T10006008	3/8	1/2	10	Coil	-	0.54	708289453882	45 PSI
T10006010	1/2	5/8	10	Coil	-	0.69	708289454889	30 PSI
T10006011	1/2	3/4	10	Coil	-	1.32	708289455381	45 PSI
T10006013	5/8	7/8	10	Coil	-	1.52	708289456388	40 PSI
T10006014	3/4	1	10	Coil	-	1.88	708289456982	35 PSI
T10007003	.170	1/4	20	Coil	-	0.36	708289451482	40 PSI
T10007004	3/16	5/16	20	Coil	-	0.59	708289451987	55 PSI
T10007005	1/4	3/8	20	Coil	-	0.74	708289452489	55 PSI
T10007006	5/16	7/16	20	Coil	-	0.88	708289452984	50 PSI
T10007008	3/8	1/2	20	Coil	-	1.08	708289453981	45 PSI
T10015005	1/4	3/8	100	Spool	7 x 10	4.2	708289491082	55 PSI
T10015011	1/2	3/4	100	Spool	7 x 10	14.1	708289491181	45 PSI
T10015015	1	1-1/4	100	Spool	7 x 21	29.7	708289457484	25 PSI
T10025001	1/8	3/16	200	Spool	7 x 10	2.6	708289490887	30 PSI
T10055014	3/4	1	50	Spool	11.5 x 10	10.2	708289456784	35 PSI
T10075014	3/4	1	75	Spool	11.5 x 10	15.3	708289456883	35 PSI



## BRAIDED VINYL TUBING

## T12 SERIES



Clear PVC Tubing reinforced with spiral polyester for use in pressure applications. Manufactured with Non-Toxic FDA compounds. Use for flexible lines for air, water, liquids, beverages, and gases as well as drain lines for air conditioners and dehumidifiers where higher pressure or tubing wall stability is required. Excellent resistance to mild acids and chemicals. See through design allows for visual flow. Not for use with Ice Makers or petroleum based products.

- Non-Toxic FDA Grade Compound
- Clear with Polyester Reinforcement
- Suitable for use with liquids, chemicals and gases
- Higher Pressure Ratings
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F



Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T12004001	1/4	1/2	100	Boxed	14 x 4 x 14	8.4	708289458788	250 PSI
T12004002	3/8	5/8	100	Boxed	14 x 4 x 14	11.5	708289459280	225 PSI
T12004003	1/2	3/4	100	Boxed	17 x 5 x 17	14	708289459785	200 PSI
T12004004	5/8	7/8	100	Boxed	17 x 5 x 17	15.8	708289460286	200 PSI
T12004005	3/4	1	50	Boxed	17 x 5 x 17	20	708289460781	150 PSI
T12004006	1	1-3/8	50	Boxed	18 x 6 x 18	23	708289461283	125 PSI
T12004007	1-1/4	1-3/4	50	Boxed	18 x 6 x 18	25.3	708289461788	100 PSI
T12005001	1/4	1/2	250	Spool	11.5 x 10	21	708289458887	250 PSI
T12005002	3/8	5/8	150	Spool	11.5 x 10	17	708289459389	225 PSI
T12005003	1/2	3/4	100	Spool	11.5 x 10	14	708289459884	200 PSI
T12005004	5/8	7/8	75	Spool	11.5 x 10	12	708289460385	200 PSI
T12005005	3/4	1	75	Spool	11.5 x 10	15	708289460880	150 PSI
T12005006	1	1-3/8	50	Spool	7 x 21	17	708289461382	125 PSI
T12005007	1-1/4	1-3/4	50	Spool	7 x 21	29	708289461887	100 PSI
T12005008	1-1/2	2	50	Spool	7 x 21	31.3	708289462280	100 PSI
T12006004	5/8	7/8	10	Coil	-	1.47	708289460484	200 PSI
T12015004	5/8	7/8	100	Spool	11.5 x 10	16	708289491280	200 PSI
T12025007	1-1/4	1-3/4	25	Spool	7 x 21	14	708289491389	100 PSI
T12025008	1-1/2	2	25	Spool	7 x 21	15.6	708289491587	100 PSI
T12055005	3/4	1	50	Spool	11.5 x 10	10	708289491488	150 PSI

## BLACK VINYL TUBING

## T14 SERIES



Black PVC Tubing manufactured with Non-Toxic compounds. Used for low open-end water drain lines. UV and ozone resistant for color stabilization. Not for use with Ice Makers or petroleum based products.

- Non-Toxic PVC Compound
- General Purpose Grade
- Suitable for use with liquids, chemicals and gases
- Use as flexible drain line
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F



Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T14005002	3/8	1/2	100	Spool	7 x 10	6.4	708289463584	45 PSI
T14005003	1/2	5/8	100	Spool	7 x 10	6.9	708289464086	30 PSI
T14005005	3/4	1	100	Spool	11.5 x 10	19.6	708289464581	35 PSI



## T16 SERIES

## POLYETHYLENE TUBING



Natural Non-Toxic FDA Grade Translucent Polyethylene Tubing. Economical and lightweight, used for pneumatic control lines and liquids in industrial applications. Also use for water and water softener lines. Resistant to many solvents, acids, alkalis, and gases. Excellent choice for use with Ice Makers.

- Non-Toxic FDA Grade Compound
- Translucent Milky White Color
- Suitable for use with air and water lines
- Use as pneumatic control line
- For use with compression style fittings
- Temperature Range -40°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T16004001	.170	1/4	100	Boxed	9.5 x 3 x 9.5	2.1	708289465489	140 PSI
T16004002	3/16	5/16	100	Boxed	9.5 x 3 x 9.5	3.3	708289466080	130 PSI
T16004003	1/4	3/8	100	Boxed	14 x 4 x 14	2.9	708289466585	120 PSI
T16004004	3/8	1/2	100	Boxed	14 x 4 x 14	4	708289467087	100 PSI
T16004005	1/2	5/8	100	Boxed	14 x 4 x 14	5.3	708289467582	85 PSI
T16005001	.170	1/4	400	Spool	7 x 10	5.1	708289465588	140 PSI
T16005002	3/16	5/16	300	Spool	7 x 10	7.5	708289466189	130 PSI
T16005003	1/4	3/8	300	Spool	7 x 10	9.1	708289466684	120 PSI
T16005004	3/8	1/2	200	Spool	11.5 x 10	7.2	708289467186	100 PSI
T16005005	1/2	5/8	100	Spool	11.5 x 10	7.5	708289467681	85 PSI
T16007001	.170	1/4	25	Coil	-	0.29	708289465786	140 PSI
T16007003	1/4	3/8	25	Coil	-	0.75	708289466882	120 PSI
T16015003	1/4	3/8	100	Spool	7 x 10	3.1	708289491686	120 PSI
T16025001	.170	1.4	200	Spool	7 x 10	2.6	708289491785	140 PSI



## T17 SERIES

## BLACK POLYETHYLENE TUBING



Opaque Black Non-Toxic Polyethylene Tubing suitable for pneumatic control lines and water lines in industrial applications. Resistant to many solvents, acids, alkalis, and gases.

- Non-Toxic LDPE Compound
- Opaque Black Color
- Suitable for use with air and water lines
- Use as pneumatic control line
- For use with compression style fittings
- Temperature Range -40°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T17005001	.170	1/4	400	Spool	7 x 10	5.1	708289468183	140 PSI



## RED PVC AIR/SPRAY HOSE

## T18 SERIES



Red cover Reinforced Flexible PVC Hose for air, water and spray applications. Contractor grade construction for pressures to 300 PSI. Non-marking abrasion resistant cover.

- Reinforced PVC Compound
- Abrasion resistant cover
- Suitable for air, water, and spray applications
- Contractor grade
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T18004001	1/4	1/2	100	Boxed	12.75 x 5 x 11	4.9	708289468589	300 PSI
T18004002	3/8	5/8	100	Boxed	18 x 6 x 18	9.5	708289468985	300 PSI
T18004003	1/2	3/4	50	Boxed	12.75 x 5 x 11	8	708289469289	300 PSI
T18005001	1/4	1/2	100	Spool	11.5 x 10	5.7	708289468688	300 PSI
T18005002	3/8	5/8	150	Spool	11.5 x 10	13.9	708289469081	300 PSI
T18005003	1/2	3/4	100	Spool	11.5 x 10	15	708289469388	300 PSI
T18025001	1/4	1/2	200	Spool	11.5 x 10	14.6	708289468787	300 PSI



## PVC FUEL HOSE

## T22 SERIES



Black Reinforced PVC Hose for use with petroleum based products. Excellent for lawn and garden equipment fuel lines. Not for use in under-hood applications.

- Reinforced Thermoplastic Compound
- Black Color
- Suitable for use with petroleum based products
- Oil and grease resistant
- Not for under-hood applications
- Temperature Range +15°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T22004001	3/16	3/8	50	Boxed	12.75 x 3 x 11	4.7	708289469982	80 PSI
T22004002	1/4	1/2	50	Boxed	12.75 x 3 x 11	5.3	708289470483	80 PSI
T22004003	5/16	9/16	50	Boxed	12.75 x 3 x 11	6.4	708289470988	80 PSI
T22004004	3/8	5/8	50	Boxed	12.75 x 3 x 11	7.1	708289471480	80 PSI
T22005001	3/16	3/8	150	Spool	7 x 10	14.2	708289470087	80 PSI
T22005002	1/4	1/2	100	Spool	7 x 10	12.1	708289470582	80 PSI
T22005003	5/16	9/16	100	Spool	7 x 10	12.8	708289471084	80 PSI
T22005004	3/8	5/8	50	Spool	7 x 10	7.4	708289471589	80 PSI
T22007002	1/4	1/2	25	Coil	-	2.8	708289470780	80 PSI
T22007003	5/16	9/16	25	Coil	-	3.1	708289471282	80 PSI
T22007004	3/8	5/8	25	Coil	-	3.5	708289471886	80 PSI
T22055001	3/16	3/8	50	Spool	3.5 x 8	4.9	708289491884	80 PSI
T22055002	1/4	1/2	50	Spool	7 x 10	6.4	708289491983	80 PSI
T22055003	5/16	9/16	50	Spool	7 x 10	6.9	708289492089	80 PSI



## T24 SERIES

## MICRO FUEL TUBING



Transparent Thermoplastic Tubing for small diameter gasoline and fuel line applications. Extremely flexible and resistant to weathering, ozone and abrasion. Features a wide temperature range for outdoor applications.

- Thermoplastic Blended Compound
- Translucent Orange Color
- Suitable for small tool fuel applications
- Industrial grade
- Abrasion Resistant
- Temperature Range -40°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T24005001	3/32	3/16	100	Spool	3.5 x 8	1.9	708289471985	125 PSI
T24005002	7/64	1/4	100	Spool	3.5 x 8	2.9	708289472081	125 PSI
T24005003	1/8	3/8	100	Spool	3.5 x 8	2.4	708289472180	125 PSI



## T28 SERIES

## VINYL GARDEN HOSE



Green Reinforced PVC Garden Hose. Flexible and weather resistant use for typical watering and wash down applications. Abrasion resistant cover allows for good service life.

- Reinforced Vinyl Compound
- Weather Resistant
- Suitable for use in water washdown applications
- Abrasion Resistant
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T28005001	5/8	7/8	150	Spool	11.5 x 10	18.4	708289472487	125 PSI



## SPA HOSE

## T30 SERIES



White Non-Toxic PVC Flexible Spa Hose designed for use with PVC Schedule 40 fittings. For spas, jetted hot tubs, and pools. Can also be used for water suction and transfer applications.

- Non-Toxic FDA Compound
- NSF / IAPMO Compliant
- Suitable for use with spas, hot tubs, and swimming pools
- Flexible design
- For use with PVC schedule 40 fittings
- Temperature Range 0°F to +150°F

Part Number	Nominal Size	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T30004002	3/4	1.05	50	Boxed	18 x 6 x 18	11.4	708289501385	100 PSI
T30004003	1	1.31	50	Boxed	18 x 6 x 18	15.5	708289501477	100 PSI
T30004004	1-1/4	1.66	25	Boxed	18 x 6 x 18	10.2	708289501569	80 PSI
T30004005	1-1/2	1.90	20	Boxed	18 x 6 x 18	10.9	708289501651	65 PSI
T30004006	2	2.38	25	Boxed	21 x 12 x 21	16.7	708289501118	65 PSI
T30005001	1/2	.840	100	Spool	7 x 16	16	708289472784	100 PSI
T30005002	3/4	1.05	100	Spool	7 x 16	22.1	708289473088	100 PSI
T30005003	1	1.31	50	Spool	7 x 16	15	708289473385	100 PSI
T30005004	1-1/4	1.66	50	Spool	7 x 21	21	708289473682	80 PSI
T30005005	1-1/2	1.90	50	Spool	7 x 21	23.5	708289473989	65 PSI
T30005006	2	2.38	25	Spool	7 x 21	16	708289474283	65 PSI



## POOL VACUUM HOSE

## T32 SERIES



Blue and Black Pool Vacuum Hose suitable for home swimming pool vacuum systems. Crushproof co-polymer construction is lightweight, floats and is non-marking.

- Flexible UV Resistant Compound
- Blue / Black Color
- Suitable for use with pool vacuums
- Crushproof, Abrasion and Kink Resistant
- End cuffs and connectors available
- Temperature Range 0°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T32004001	1-1/4	1.58	25	Boxed	18 x 6 x 18	3.6	708289500845	N/A
T32004002	1-1/2	1.81	25	Boxed	18 x 6 x 18	4.6	708289500937	N/A
T32005001	1-1/4	1.58	50	Spool	7 x 21	7.2	708289474481	N/A
T32005002	1-1/2	1.81	50	Spool	7 x 21	9.2	708289474580	N/A
T32C00001	1-1/4	-	1	Bag	Cuff	0.3	708289474610	N/A
T32C00002	1-1/2	-	1	Bag	Cuff	0.4	708289474658	N/A



## T34 SERIES

## BILGE HOSE



White Low Density Polyethylene Bilge Hose for marine pump and low pressure discharge applications. Abrasion and kink resistant. Comes with smooth end connections manufactured into the hose every 36 inches for a leak proof connection.

- Low Density Polyethylene Compound
- Milky White Color
- Suitable for marine and low pressure discharge
- Abrasion and kink resistant
- For use with hose barbs and clamps
- Temperature Range 0°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T34005001	3/4	1	50	Spool	7 x 16	6.2	708289474689	N/A
T34005002	1-1/8	1-5/8	50	Spool	7 x 21	8	708289474788	N/A
T34005003	1-1/4	1-3/4	50	Spool	7 x 21	9	708289474887	N/A
T34005004	1-1/2	2	50	Spool	7 x 21	9.3	708289474986	N/A



## T40 SERIES

## CLEAR PVC SUCTION HOSE



Clear Flexible PVC Suction Hose with a white rigid PVC helix for full vacuum service. Use with portable pumps for suction or open end discharge applications in construction, agriculture, marine and mining. See-through design allows for visual flow.

- Flexible PVC Compound
- Clear Body with White Helix
- Suitable for use with centrifugal and trash pumps
- Contractor grade
- Convenient see-through design
- Temperature Range 0°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T40005001	1-1/4	1.50	50	Spool	7 x 21	18.5	708289476782	85 PSI
T40005002	1-1/2	1.85	50	Spool	7 x 21	25.2	708289476980	70 PSI
T40005003	2	2.38	25	Spool	7 x 21	17.9	708289477185	65 PSI



## ECONOMY PVC DISCHARGE HOSE

## T36 SERIES



Blue color Economy PVC Discharge Hose is an extremely lightweight hose for very low pressure open end water discharge applications. Lay-flat construction for easy transport and storage.

- Non-Reinforced PVC Compound
- Blue Color
- Suitable for open end low pressure discharge
- Layflat Design
- Extremely lightweight
- Temperature Range 0°F to +125°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T36005001	1-1/2	1.70	150	Spool	3.5 x 16	12.9	708289475389	25 PSI
T36005002	2	2.20	150	Spool	3.5 x 16	14.5	708289475785	20 PSI



## REINFORCED PVC DISCHARGE HOSE

## T38 SERIES



Blue Reinforced PVC Discharge Hose is designed for water discharge applications using typical centrifugal and trash pumps. Very durable lay-flat design. Can be used for drip irrigation.

- Reinforced PVC Compound
- Blue Color
- Suitable for use with centrifugal and trash pumps
- Durable Layflat Design
- Can be used for drip irrigation
- Temperature Range 0°F to +170°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T38005001	1-1/2	1.85	150	Spool	3.5 x 16	29	708289476188	80 PSI
T38005002	2	2.30	150	Spool	3.5 x 16	37	708289476584	85 PSI



## T44 SERIES

## PVC APPLIANCE DRAIN HOSE



Black PVC Appliance Drain Hose is suitable for use as a flexible dishwasher and washing machine water drain hose. Reinforced with spiral polyester for pressure and stability and is kink resistant.

- Reinforced PVC Compound
- Black Color
- Suitable for use as dishwasher and washing machine drain
- For use with hose barbs and clamps
- Temperature Range +25F to +150F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T44004001	5/8	7/8	50	Boxed	18 x 6 x 18	10.6	708289477987	150 PSI
T44004003	7/8	1-1/8	50	Boxed	18 x 6 x 18	16.5	708289478984	100 PSI
T44025003	7/8	1-1/8	25	Spool	11.5 x 10	9.3	708289479080	100 PSI
T44055001	5/8	7/8	50	Spool	11.5 x 10	10.2	708289478083	150 PSI



## T45 SERIES

## NON REINFORCED PVC DRAIN HOSE



Black Non-Reinforced PVC Drain Hose for dishwasher and washing machine drain applications. Flexible construction allows for bending without kinking.

- Non-Reinforced PVC Compound
- Black Color
- Suitable for use as dishwasher and washing machine drain
- For use with hose barbs and clamps
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T45004005	1	1-1/4	50	Boxed	18 x 6 x 18	13.2	708289500036	25 PSI



## RED RUBBER UTILITY HOSE

## T60 SERIES



Red Utility Hose is a high quality multi-purpose hose for air, water and agricultural spray applications used over a wide temperature range. Reinforced with spiral polyester. Hose is heat, ozone and weather resistant EPDM. Do not use with petroleum based products.

- Polyester Reinforced
- EPDM Rubber
- Heat, ozone and weather resistant
- Suitable for use with air, water and ag spray
- Contractor grade
- Limited oil resistance
- Temperature Range -40°F to +190°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T60004100	3/8	5/8	50	Boxed	12.75 x 5 x 11	8.5	708289500487	200 PSI
T60005001	1/2	3/4	100	Spool	11.5 x 10	21	708289479981	200 PSI
T60005003	3/4	1-1/8	75	Spool	11.5 x 10	26.5	708289480581	200 PSI



## HEATER HOSE

## T62 SERIES



Black Heater Hose that can also be used as a dishwasher and washing machine drain hose. Reinforced with spiral polyester. Very flexible design. Use as a coolant hose in outdoor applications. Not for under-hood applications.

- Reinforced Synthetic Rubber Compound
- Heat, ozone and weather resistant
- Suitable for use as dishwasher and washing machine drain
- Not for under-hood applications
- For use with hose barbs and clamps
- Temperature Range -40°F to +200°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T62004001	1/2	3/4	50	Boxed	12.75 x 5 x 11	9.5	708289481083	105 PSI
T62004002	5/8	7/8	50	Boxed	18 x 6 x 18	11.7	708289481489	80 PSI
T62004003	3/4	1	50	Boxed	18 x 6 x 18	13.4	708289481885	80 PSI
T62005001	1/2	3/4	100	Spool	11.5 x 10	18.6	708289481182	105 PSI
T62005002	5/8	7/8	100	Spool	11.5 x 10	22.9	708289481588	80 PSI
T62005005	1	1-3/8	50	Spool	7 x 16	26	708289496971	80 PSI
T62006002	5/8	7/8	10	Coil	-	2.2	708289481687	80 PSI
T62006003	3/4	1	10	Coil	-	3.1	708289482080	80 PSI
T62025004	7/8	1-1/8	25	Spool	11.5 x 10	10.6	708289496889	80 PSI
T62075003	3/4	1	75	Spool	11.5 x 10	18	708289481939	80 PSI



## T64 SERIES

## LATEX TUBING



Latex Tubing is amber in color. Synthetic compound is very elastic. Use in low pressure applications where extreme flexibility is required. Excellent cold temperature resistance. Do not use with petroleum based products.

- Synthetic Latex Compound
- Amber Color
- Elasticity allows for use in a variety of applications
- Not for pressure applications
- Flexible in low temperatures
- Temperature Range -40°F to +180°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T64005001	1/4	3/8	50	Spool	3.5 x 8	1.6	708289482189	N/A
T64006001	1/4	3/8	10	Coil	-	0.4	708289482288	N/A



## T68 SERIES

## VACUUM TUBING



Black Non-Reinforced Vacuum Tubing. Small diameter thermoplastic compound for a variety of uses. Designed for vacuum applications but can be used for low pressure water lines. Not for underhood applications.

- Non-Reinforced Thermoplastic Compound
- Black Color
- Suitable for use as windshield wiper vacuum tubing
- Weather resistant
- Not for Under Hood Application
- Temperature Range +25°F to +150°F

Part Number	ID	OD	Length	Package Type	Dimensions	Weight	UPC	Pressure @ 70°F
T68004002	1/8	5/16	50	Boxed	9.5 x 3 x 9.5	1.7	708289500128	60 PSI
T68004003	3/16	3/8	50	Boxed	9.5 x 3 x 9.5	1.8	708289500210	50 PSI
T68004004	1/4	7/16	50	Boxed	12.75 x 3 x 11	1.9	708289500302	40 PSI



## BLACK NEOPRENE GASKET MATERIAL

## T80 SERIES



Black moderately oil resistant solid gasket material used for a wide variety of applications including sealing, stripping and vibrating. Medium hardness. Use over a wide temperature range.

- Non-Reinforced Neoprene Rubber Blend Compound
- General Purpose Grade
- Weather resistant material for a variety of applications
- Moderate oil resistance
- Temperature Range -20°F to +180°F

Part Number	Thickness	Width	Length	Package Type	Lenth	Width	Height	UPC
R80005001	1/16	12	33	Spool	10.5	12	10.5	708289484787

## RED RUBBER GASKET MATERIAL

## T82 SERIES



Red general purpose plumber's sheet used for water sealing and other applications where oil resistance is not required. Solid material is medium/high hardness features slight stiffness yet flexible for most applications.

- Non-Reinforced Synthetic Rubber Compound
- General Purpose Grade
- Weather and Abrasion Resistant
- Limited Oil Resistance
- Temperature Range -20°F to +160°F

Part Number	Thickness	Width	Length	Package Type	Lenth	Width	Height	UPC
R82005001	1/16	12	33	Spool	10.5	12	10.5	708289485586
R82005002	1/8	12	18	Spool	10.5	12	10.5	708289485982

## CLOTH-INSERTED GASKET MATERIAL

## T86 SERIES



Black general purpose solid material with added cloth reinforcement embedded in the sheet for increased tear resistance. Limited oil resistant rubber is medium hardness. Use for a variety of applications over a wide temperature range.

- Reinforced Synthetic Rubber Compound
- Black Color
- Weather resistant material for a variety of applications
- Limited Oil Resistance
- Tear Resistant
- Temperature Range -20°F to +170°F

Part Number	Thickness	Width	Length	Package Type	Lenth	Width	UPC
R86005001	1/16	12	33	Spool	0	12	708289487184

## SPOOL AND DISPENSER RACKS

**8 FT  
SPOOL  
RACK**



**3 FT  
DISPENSER  
RACK**



**4 FT  
SPOOL  
RACK**



## PREMIUM RUBBER WASHING MACHINE HOSE



F X M



F X F



F X 90

Highest quality black EPDM rubber washing machine inlet hose assemblies manufactured to original equipment specifications. Can use for hot or cold lines. Quality plated GHT fittings installed each end. Choose from Female x Female, Female x Male or Female x 90° Female assembly.

- Reinforced Premium Rubber Compound
- Use for Hot or Cold Supply Line
- High Burst Strength
- Meets OEM Specifications
- Plated Steel Fittings
- Bagged Hoses Include Washers
- Made in USA
- Bulk: 25/Box

Part Number	Length	Ends	Package	Package Dimensions	Lbs. / Each	UPC
WA6102003	3'	F X F	Bulk	20 x 20 x 6	0.56	708289514439
WA6107003	3'	F X F	Bag	12 x 15	0.60	708289514521
WA6102004	4'	F X F	Bulk	20 x 20 x 6	0.68	708289514613
WA6107004	4'	F X F	Bag	12 x 15	0.72	708289267533
WA6102005	5'	F X F	Bulk	20 x 20 x 6	0.84	708289514705
WA6107005	5'	F X F	Bag	12 x 15	0.88	708289267571
WA6102006	6'	F X F	Bulk	20 x 20 x 6	0.96	708289514798
WA6107006	6'	F X F	Bag	12 x 15	1.00	708289267601
WA6102008	8'	F X F	Bulk	20 x 20 x 6	1.24	708289514880
WA6107008	8'	F X F	Bag	12 x 15	1.28	708289267618
WA6102010	10'	F X F	Bulk	20 x 20 x 6	1.48	708289514972
WA6107010	10'	F X F	Bag	12 x 15	1.52	708289505437
WA6102012	12'	F X F	Bulk	20 x 20 x 6	1.80	708289515061
WA6107012	12'	F X F	Bag	12 x 15	1.84	708289515153
WA6102303	3'	F X M	Bulk	20 x 20 x 6	0.52	708289516778
WA6107303	3'	F X M	Bag	12 x 15	0.56	708289516860
WA6102304	4'	F X M	Bulk	20 x 20 x 6	0.64	708289516952
WA6107304	4'	F X M	Bag	12 x 15	0.68	708289517041
WA6102305	5'	F X M	Bulk	20 x 20 x 6	0.76	708289517133
WA6107305	5'	F X M	Bag	12 x 15	0.80	708289517225
WA6102306	6'	F X M	Bulk	20 x 20 x 6	0.92	708289517317
WA6107306	6'	F X M	Bag	12 x 15	0.96	708289517409
WA6102308	8'	F X M	Bulk	20 x 20 x 6	1.16	708289517492
WA6107308	8'	F X M	Bag	12 x 15	1.20	708289517584
WA6102310	10'	F X M	Bulk	20 x 20 x 6	1.44	708289517676
WA6107310	10'	F X M	Bag	12 x 15	1.48	708289517768
WA6102312	12'	F X M	Bulk	20 x 20 x 6	1.76	708289517850
WA6107312	12'	F X M	Bag	12 x 15	1.80	708289517942
WA6102103	3'	F X 90	Bulk	20 x 20 x 6	0.72	708289515429
WA6107103	3'	F X 90	Bag	12 x 15	0.76	708289515511
WA6102104	4'	F X 90	Bulk	20 x 20 x 6	0.84	708289515603
WA6107104	4'	F X 90	Bag	12 x 15	0.88	708289515696
WA6102105	5'	F X 90	Bulk	20 x 20 x 6	0.96	708289515788
WA6107105	5'	F X 90	Bag	12 x 15	1.00	708289515870
WA6102106	6'	F X 90	Bulk	20 x 20 x 6	1.12	708289515962
WA6107106	6'	F X 90	Bag	12 x 15	1.16	708289295086
WA6102108	8'	F X 90	Bulk	20 x 20 x 6	1.36	708289516051
WA6107108	8	F X 90	Bag	12 x 15	1.40	708289516143
WA6102110	10'	F X 90	Bulk	20 x 20 x 6	1.64	708289516235
WA6107110	10'	F X 90	Bag	12 x 15	1.68	708289516327
WA6102112	12'	F X 90	Bulk	20 x 20 x 6	1.88	708289516419
WA6107112	12	F X 90	Bag	12 x 15	1.92	708289516501



## PREMIUM RUBBER WASHING MACHINE HOSE



Highest quality black EPDM rubber washing machine inlet hose assemblies manufactured to original equipment specifications. Can use for hot or cold lines. Quality plated GHT fittings installed each end. Available in Twin-Pack bagged two hoses in one bag for retail sale. Choose from Red & Blue or Black & Black. Fittings are GHT Female both ends.

- Reinforced Premium Rubber Compound
- Use for Hot or Cold Supply Line
- High Burst Strength
- Meets OEM Specifications
- Plated Steel Fittings
- Bagged Hoses Include Washers
- Made in USA



Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WA6RB7004	4	Twin Pack	12 x 15	1.42	708289620901
WA6RB7005	5	Twin Pack	12 x 15	1.74	708289273688
WA6RB7006	6	Twin Pack	12 x 15	1.98	708289674805
WA6RB7008	8	Twin Pack	12 x 15	2.54	708289513715
WA6RB7010	10	Twin Pack	12 x 15	3.02	708289513807
WA61T7004	4	Twin Pack	12 x 15	1.42	708289620802
WA61T7005	5	Twin Pack	12 x 15	1.74	708289620406
WA61T7006	6	Twin Pack	12 x 15	1.98	708289267496
WA61T7008	8	Twin Pack	12 x 15	2.54	708289267519
WA61T7010	10	Twin Pack	12 x 15	3.02	708289514347

## STEEL BRAID REINFORCED INLET HOSE



Inlet hose featuring a steel braid reinforcement for added protection from hose failure. Cover is color coded for easy identification. Use as hot or cold supply line. Plated GHT Female fittings installed each end.

- Steel Braid Burst-proof Construction
- Use for Hot or Cold Supply Line
- Color Coded for Easy Identification
- Kink Resistant
- Plated Brass Fittings
- Bagged Hoses Include Washers

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WA0702004	4	Bulk	20 x 20 x 6	0.85	708289519748
WA0707004	4	Bag	12 x 15	0.89	708289512008
WA0702005	5	Bulk	20 x 20 x 6	1.00	708289519830
WA0707005	5	Bag	12 x 15	1.04	708289512091
WA0702006	6	Bulk	20 x 20 x 6	1.20	708289519922
WA0707006	6	Bag	12 x 15	1.24	708289512183
WA6707004	4	Bag	20 x 20 x 6	1.75	708289520010
WA6707005	5	Bag	12 x 15	2.05	708289520102
WA6707006	6	Bag	20 x 20 x 6	2.45	708289520195

## "Y" MIXER HOSE



'Y' Mixer hose assembly for washers that have a single supply line. 12" hose length allows for convenient installation. GHT Female fittings installed with a GHT Male between the two hoses.

- Reinforced Premium Rubber Compound
- Use for Hot or Cold Supply Line
- High Burst Strength
- Meets OEM Specifications
- Plated Steel Fittings
- Bagged Hoses Include Washers
- Made in USA

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WA6102901	1	Bulk	20 x 20 x 6	0.48	708289518215
WA6107901	1	Bag	12 x 15	0.52	708289295284

## HOOK DRAIN HOSE



Formed Hook hose used as a washing machine drain hose. Two sizes to choose from for washers using 3/4" to 1-1/4" drain outlets.

- Thermoplastic Construction
- Attaches to 3/4", 7/8" and 1" outlets
- Withstands Chemicals and Detergents
- WD12 attaches to 3/4", 7/8" and 1" outlets
- WD16 attaches to 1", 1-1/8", and 1-1/4" outlets
- Formed Hook End
- Bagged Hoses include Clamp

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WD1202005	5	Bulk	20 x 20 x 6	0.80	708289518307
WD1207005	5	Bag	12 x 15	0.92	708289518390
WD1202006	6	Bulk	20 x 20 x 6	1.00	708289518482
WD1207006	6	Bag	12 x 15	1.30	708289518574
WD1602006	6	Bulk	20 x 20 x 6	1.40	708289518666
WD1607006	6	Bag	18 X 22	1.90	708289267540
WD1602906	6	Bulk	20 x 20 x 6	1.40	708289518758
WD1607906	6	Bag	18 X 22	1.90	708289267588

## CORRUGATED HOOK DRAIN HOSE



Plastic Hook Drain hose featuring a corrugated plastic construction for flexibility and kink resistance. Gray in color.

- Corrugated Plastic Construction
- Kink Resistant and Crushproof
- Attaches to 1", 1-1/8" and 1-1/4" outlets
- Withstands Chemicals and Detergents
- Bagged Hoses include Clamp

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WD5602005	5	Bulk	20 x 20 x 6	0.60	708289520287
WD5607005	5	Bag	12 x 15	0.90	708289520379
WD5602006	6	Bulk	20 x 20 x 6	0.80	708289520461
WD5607006	6	Bag	18 X 22	1.10	708289520553

## RUBBER DISHWASHER DRAIN HOSE



Black rubber hot water drain hose for dishwashers or washing machines. Reinforced for dimensional stability.

- Reinforced Premium Rubber Compound
- Use with Dishwasher and Washing Machines
- Rated for hot water to 190°F
- Made in USA

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WDX500550	50	Bulk	14 x 14 x 4	11.00	708289518932
WDX700550	50	Bulk	21 x 21 x 4	14.00	708289295185

## PLASTIC DISHWASHER DRAIN HOSE



Lightweight and very flexible dishwasher drain hose. Black in color.

- Corrugated Plastic Construction
- Kink Resistant and Crushproof
- Meets OEM Specifications
- Bagged Hoses include Clamp

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WD7802506	6.5	Bulk	20 x 20 x 6	0.50	708289518840
WD7807506	6.5	Bag	12 x 15	0.80	708289505703

## ALUMINUM GOOSENECK



Aluminum Gooseneck for use with 1" hose. Use as a hook for the end of a drain hose to keep hose in place.

- Solid Aluminum Construction
- Attaches to 1" Drain Hose

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WC1602000	-	Bulk	10 x 7 x 10	0.16	708289519205

## UTILITY FILL HOSE



Reinforced rubber hose used as a water fill hose. GHT Female fitting installed one end only.

- Reinforced Premium Rubber Compound
- Plated Steel Fitting
- Bagged Hoses Include Washer
- Made in USA

Part Number	Length	Package	Package Dimensions	Lbs. / Each	UPC
WA6102405	5	Bulk	20 x 20 x 6	0.68	708289519298
WA6107405	5	Bag	12 x 15	0.72	708289505345

***UDP***  
***ULTRA DYNAMIC PRODUCTS***

A DIVISION OF  
**ABBOTT** RUBBER  
COMPANY, INC.

**1700 NICHOLAS BLVD. • ELK GROVE VILLAGE, IL 60007 •**  
**PHONE: 800.852.1855 • [www.udproducts.com](http://www.udproducts.com)**