

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 14-Jan-2014

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier 207, 208, 210

Product Name Oil Base DRYLOK Masonry Waterproofer

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Waterproofing Sealers, Concrete/Masonry

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

United Gilsonite Laboratories
1396 Jefferson Ave.
Dunmore
PA
18509
US
Phone:570-344-1202
Fax:570-969-7634
Email:rbarako@ugl.com
Contact Phone:570-344-1202

Emergency telephone number (800) 424-9300 Chemtrec

2. HAZARDS IDENTIFICATION


Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|------------|
| Acute toxicity - Oral | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 3 |

GHS Label elements, including precautionary statements

Emergency Overview

| | |
|--|------------------------------|
| Signal word | Warning |
| Hazard Statements Harmful if swallowed Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer May cause respiratory irritation. May cause drowsiness or dizziness May be fatal if swallowed and enters airways Flammable liquid and vapor | |
|  | |
| Appearance White | Physical State Liquid |
| Odor Aromatic | |

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)

Skin

If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

42% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No | Weight % | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Portland cement | 65997-15-1 | 10 - 30 | * |
| Quartz | 14808-60-7 | 10 - 30 | * |
| Stoddard solvent | 8052-41-3 | 10 - 30 | * |
| Styrene acrylate copolymer | 25085-34-1 | 5 - 10 | * |
| Limestone | 1317-65-3 | 5 - 10 | * |
| Petroleum naphtha, light aromatic | 64742-95-6 | 1 - 5 | * |
| Mica | 12001-26-2 | 1 - 5 | * |
| 1,2,4 Trimethylbenzene | 95-63-6 | 1 - 5 | * |
| Titanium dioxide | 13463-67-7 | 1 - 5 | * |
| Perlite | 93763-70-3 | 1 - 5 | * |
| 1,3,5-Trimethylbenzene | 108-67-8 | 1 - 5 | * |
| Xylene, mixed isomers | 1330-20-7 | 0.1 - 1 | * |
| Cumene | 98-82-8 | 0.1 - 1 | * |

* The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist, call a physician.

| | |
|-----------------------------------|--|
| Skin Contact | May cause an allergic skin reaction. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician. |
| Inhalation | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen. |
| Ingestion | Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately. Rinse mouth. |
| Protection of First-aiders | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

Most important symptoms and effects, both acute and delayed

| | |
|--|---|
| Most Important Symptoms and Effects | Burning sensation. Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. |
|--|---|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|--|
| Notes to Physician | Treat symptomatically. May cause sensitization of susceptible persons. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances. |
|---------------------------|--|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO₂, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Some may be transported hot.

| | |
|--------------------------|--|
| Uniform Fire Code | Combustible Liquid: II Sensitizer: Liquid Highly Toxic: Liquid |
|--------------------------|--|

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for Cleaning Up Dike far ahead of liquid spill for later disposal. Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wear personal protective equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials. Keep away from heat and sources of ignition. Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------------------------|--|---|--|
| Portland cement 65997-15-1 | TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica | IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| Quartz 14808-60-7 | TWA: 0.025 mg/m ³ respirable fraction | TWA: 0.1 mg/m ³ (vacated) | IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust |
| Stoddard solvent 8052-41-3 | TWA: 100 ppm | TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³ | IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³ |
| Limestone 1317-65-3 | - | TWA: 15 mg/m ³ TWA: 5 mg/m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³ | TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust |
| Mica 12001-26-2 | TWA: 3 mg/m ³ | TWA: 20 mppcf (<1% crystalline silica) 3 mg/m ³ (vacated) | IDLH: 1500 mg/m ³ containing <1% quartz TWA: 3 mg/m ³ respirable dust |
| 1,2,4 Trimethylbenzene 95-63-6 | - | (vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³ | TWA: 25 ppm TWA: 125 mg/m ³ |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Perlite 93763-70-3 | - | (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| 1,3,5-Trimethylbenzene 108-67-8 | - | (vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³ | TWA: 25 ppm TWA: 125 mg/m ³ |
| Xylene, mixed isomers 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | - | |
| Cumene 98-82-8 | TWA: 50 ppm | TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* | IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³ |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters.

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

None required for consumer use. If splashes are likely to occur: Tight sealing safety goggles.

| | |
|---------------------------------|--|
| Skin and Body Protection | Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots. |
| Respiratory Protection | No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. |
| Hygiene Measures | Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

| | | | |
|-----------------------|--------------------------|-----------------------|--------------------------|
| Physical State | Liquid | Odor | Aromatic |
| Appearance | White | Odor Threshold | No information available |
| Color | No information available | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks/ Method</u> |
|---|-------------------|------------------------|
| pH | UNKNOWN | None known |
| Melting/freezing point | No data available | None known |
| Boiling point / boiling range | No data available | None known |
| Flash Point | 40 C / 104 F | None known |
| Evaporation rate | No data available | None known |
| Flammability (solid, gas) | No data available | None known |
| Flammability Limits in Air | | |
| Upper flammability limit | No data available | |
| Lower flammability limit | No data available | |
| Vapor pressure | No data available | None known |
| Vapor density | No data available | None known |
| Specific Gravity | No data available | None known |
| Water Solubility | Insoluble | None known |
| Solubility in other solvents | No data available | None known |
| Partition coefficient: n-octanol/water | No data available | None known |
| Autoignition temperature | No data available | None known |
| Decomposition temperature | No data available | None known |
| Kinematic viscosity | No data available | None known |
| Dynamic viscosity | No data available | None known |
| Explosive Properties | No data available | |
| Oxidizing Properties | No data available | |

Other Information

| | |
|-----------------------------------|-------------------|
| Softening Point | No data available |
| VOC Content (%) | No data available |
| Particle Size | No data available |
| Particle Size Distribution | No data available |

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|----------------------------|---|
| Product Information | Product does not present an acute toxicity hazard based on known or supplied information. |
| Inhalation | Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. |
| Eye Contact | Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. |
| Skin Contact | Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking. |
| Ingestion | Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Harmful if swallowed. (based on components). |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|---------------------|-------------------------|--|
| Quartz 14808-60-7 | = 500 mg/kg (Rat) | - | - |
| Petroleum naphtha, light aromatic 64742-95-6 | - | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h |

| | | | |
|------------------------------------|-----------------------|--------------------------|-----------------------------------|
| 1,2,4-Trimethylbenzene 95-63-6 | = 3400 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 18 g/m ³ (Rat) 4 h |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| 1,3,5-Trimethylbenzene 108-67-8 | - | - | = 24 g/m ³ (Rat) 4 h |
| Xylene, mixed isomers 1330-20-7 | = 4300 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 47635 mg/L (Rat) 4 h |
| Cumene 98-82-8 | = 1400 mg/kg (Rat) | = 12300 µL/kg (Rabbit) | - |

Information on toxicological effects

Symptoms

Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects

There is no data available for this product.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|------------------------------------|-------|----------|-------|------|
| Quartz 14808-60-7 | A2 | Group 1 | Known | X |
| Titanium dioxide 13463-67-7 | | Group 2B | | X |
| Xylene, mixed isomers 1330-20-7 | | Group 3 | | |
| Cumene 98-82-8 | | Group 2B | | |

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. More detailed substance and/or ingredient information may be provided in the other sections of this SDS.

Chronic Toxicity

Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected carcinogen. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Kidney. Lungs. Liver.

Aspiration Hazard

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

867.00 mg/kg

ATEmix (inhalation-gas)

87,000.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

28.41 mg/l

ATEmix (inhalation-vapor)

213.00 ATEmix

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and Degradability

No information available.

Bioaccumulation

| Chemical Name | Log Pow |
|------------------------------------|---------|
| 1,2,4 Trimethylbenzene 95-63-6 | 3.63 |
| Xylene, mixed isomers 1330-20-7 | 3.15 |
| Cumene 98-82-8 | 3.55 |

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of in accordance with local regulations.

US EPA Waste Number D001 U055 U239

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|------------------------------------|------|--------------------------|------------------------|------------------------|
| Xylene, mixed isomers 1330-20-7 | | | | U239 |
| Cumene 98-82-8 | | | | U055 |

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|------------------------------------|----------------------------|
| 1,2,4 Trimethylbenzene 95-63-6 | Toxic |
| Xylene, mixed isomers 1330-20-7 | Toxic Ignitable |
| Cumene 98-82-8 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT
Description CONSUMER COMMODITY, ORM-D, MARINE POLLUTANT
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263, PAINT, 3, III

MEX

UN-No UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263 PAINT, 3, III

ICAO

UN-No UN1263

| | |
|-----------------------------|--|
| Proper Shipping Name | PAINT RELATED MATERIAL |
| Hazard Class | 3 |
| Packing Group | III |
| Description | UN1263, PAINT RELATED MATERIAL, 3, III |

IATA

| | |
|-----------------------------|--|
| UN-No | UN1263 |
| Proper Shipping Name | PAINT RELATED MATERIAL |
| Hazard Class | 3 |
| Packing Group | III |
| Description | UN1263, PAINT RELATED MATERIAL, 3, III |

IMDG/IMO

| | |
|-----------------------------|-------------------------------|
| UN-No | UN1263 |
| Proper Shipping Name | PAINT |
| Hazard Class | 3 |
| Packing Group | III |
| EmS No. | F-E, S-E |
| Description | UN1263, PAINT, 3, III, FP 40C |

RID

| | |
|-----------------------------|----------------------|
| UN-No | UN1263 |
| Proper Shipping Name | PAINT |
| Hazard Class | 3 |
| Packing Group | III |
| Classification Code | F1 |
| Description | UN1263 PAINT, 3, III |

ADR

| | |
|-----------------------------|----------------------|
| UN-No | UN1263 |
| Proper Shipping Name | PAINT |
| Hazard Class | 3 |
| Packing Group | III |
| Classification Code | F1 |
| Description | UN1263 PAINT, 3, III |

ADN

| | |
|-----------------------------|----------------------|
| UN-No | UN1263 |
| Proper Shipping Name | PAINT |
| Hazard Class | 3 |
| Packing Group | III |
| Classification Code | F1 |
| Special Provisions | 163, 640E, 650 |
| Description | UN1263 PAINT, 3, III |
| Hazard Labels | 3 |
| Limited Quantity | 5 L |
| Ventilation | VE01 |

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| | |
|------|--|
| TSCA | Complies |
| DSL | All components are listed either on the DSL or NDSL. |

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS-No | Weight % | SARA 313 - Threshold Values % |
|----------------------------------|---------|----------|-------------------------------|
| 1,2,4 Trimethylbenzene - 95-63-6 | 95-63-6 | 1 - 5 | 1.0 |
| Cumene - 98-82-8 | 98-82-8 | 0.1 - 1 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|-------------------|--------------------------|------------------------------------|--|
| Cumene 98-82-8 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|-------------------------------|---------------------|
| Quartz - 14808-60-7 | Carcinogen |
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Cumene - 98-82-8 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|------------------------------------|------------|---------------|--------------|--------------|----------|
| Portland cement 65997-15-1 | X | X | X | | |
| Quartz 14808-60-7 | X | X | X | | |
| Stoddard solvent 8052-41-3 | X | X | X | | |
| Limestone 1317-65-3 | X | X | X | | |
| Mica 12001-26-2 | X | X | X | | |
| 1,2,4 Trimethylbenzene 95-63-6 | X | X | X | X | X |
| Titanium dioxide 13463-67-7 | X | X | X | | |
| Perlite 93763-70-3 | X | X | X | | |
| 1,3,5-Trimethylbenzene 108-67-8 | X | X | X | | X |

| | | | | | |
|------------------------------------|---|---|---|---|---|
| Xylene, mixed isomers 1330-20-7 | | X | | X | |
| Cumene 98-82-8 | X | X | X | X | X |

International Regulations

Mexico

National occupational exposure limits

| Component | Carcinogen Status | Exposure Limits |
|--|-------------------|---|
| Portland cement 65997-15-1 (10 - 30) | | Mexico: TWA 10 mg/m ³ Mexico: STEL 20 mg/m ³ |
| Quartz 14808-60-7 (10 - 30) | | Mexico: TWA= 0.1 mg/m ³ |
| Stoddard solvent 8052-41-3 (10 - 30) | | Mexico: TWA 100 ppm Mexico: TWA 523 mg/m ³ Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m ³ |
| Limestone 1317-65-3 (5 - 10) | | Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³ |
| Mica 12001-26-2 (1 - 5) | | Mexico: TWA= 3 mg/m ³ |
| 1,2,4 Trimethylbenzene 95-63-6 (1 - 5) | | Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³ |
| Titanium dioxide 13463-67-7 (1 - 5) | | Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³ |
| Perlite 93763-70-3 (1 - 5) | | Mexico: TWA 10 mg/m ³ |
| 1,3,5-Trimethylbenzene 108-67-8 (1 - 5) | | Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³ |
| Xylene, mixed isomers 1330-20-7 (0.1 - 1) | | Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³ |
| Cumene 98-82-8 (0.1 - 1) | | Mexico: TWA 50 ppm Mexico: TWA 245 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 365 mg/m ³ |

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B3 - Combustible liquid

D2A - Very toxic materials



16. OTHER INFORMATION

| | | | | |
|-------------|--------------------------|-----------------------|--------------------------|--|
| NFPA | Health Hazard 2 | Flammability 2 | Instability 0 | Physical and Chemical Hazards - |
| HMIS | Health Hazard 2 * | Flammability 2 | Physical Hazard 0 | Personal Protection X |

Chronic Hazard Star Legend

* = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 14-Jan-2014

Revision Note No information available.

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet