

CLASSIC PATTERNS

FISSURED PANELS

USG Radar™ Basic R2120

TO ORDER SAMPLES, GO TO [USG.COM](https://www.usg.com)

AVAILABLE COLORS*



Flat Black

*Available on Radar R2210 & R2410

FEATURES AND BENEFITS

- Match many existing panels.
- Good sound control for a variety of commercial environments.
- USG Fifth Avenue™ panels feature a directional pattern.
- USG Radar™ panels are nondirectional for even easier installation.







































SUBSTRATE


- Wet-formed mineral fiber


USG Fifth Avenue™


USG Radar™ & USG Radar™ Basic

PRODUCT SPECIFICATIONS

Pattern	Item No.	Edge	Panel Size	Pcs./Carton	Sq. Ft./Carton	Ctns./Pallet	Fire Rating	Sound Control		Technical Information					
								NRC	CAC	LR	R-Value	VOC	Mold, Mildew & Sag Resistance	Recycled Content	USG Commercial Equivalent
USG FIFTH AVENUE™	133	SQ 	2'x2'x5/8"	16	64	20									
	220	SQ 	2'x4'x5/8"	8	64	18		0.55	35	0.81	1.6	Low	—	48-51%	USG Fissured™ Basic 586
	270	SLT 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.81	1.4	Low	—	25%	USG Fissured™ Basic 506
	280	SQ 	2'x4'x5/8"	8	64	20	Class A	0.55	35	0.81	1.4	Low	—	25%	USG Fissured™ Basic 562
	671	SQ 	2'x2'x5/8"	16	64	16		0.55	35	0.81	1.6	Low	—	48-51%	USG Fissured™ Basic 585
USG RADAR™ BASIC	R2110	SQ 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.83	1.4	Low	—	25%	USG Radar™ Basic 2110
	R2115	SQ 	2'x2'x5/8"	16	64	20		0.55	35	0.83	1.6	Low	—	48-51%	USG Radar™ Basic 2115
	R2120	SLT 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.83	1.4	Low	—	25%	USG Radar™ Basic 2120
	2130	FLB 	2'x2'x5/8"	16	64	16	Class A	0.55	33	0.83	1.4	Low	—	25%	USG Radar™ Basic 2130
	R2310	SQ 	2'x4'x5/8"	8	64	20	Class A	0.55	35	0.83	1.4	Low	—	25%	USG Radar™ Basic 2310
	R2315	SQ 	2'x4'x5/8"	8	64	18		0.55	35	0.83	1.6	Low	—	48-51%	USG Radar™ Basic 2315
	R2210¹	SQ 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.84	1.4	Low		25-34%	USG Radar™ 2210
USG RADAR™	R2220	SLT 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.84	1.4	Low		25-34%	USG Radar™ 2220
	R2225	SLT 	2'x2'x5/8"	16	64	16		0.55	35	0.84	1.6	Low		51-59%	USG Radar™ 2225
	2230	FLB 	2'x2'x5/8"	16	64	20	Class A	0.55	33	0.84	1.4	Low		26-34%	USG Radar™ 2230
	R2410¹	SQ 	2'x4'x5/8"	8	64	20	Class A	0.55	35	0.84	1.4	Low		25-34%	USG Radar™ 2410
	R2415	SQ 	2'x4'x5/8"	8	64	18		0.55	35	0.84	1.6	Low		48-51%	USG Radar™ 2415
	R2570²	SF 	12"x12"x5/8"	48	48	18	Class A	0.45	35	0.84	1.4	Low		34-44%	USG Radar™ 2570

 **Low Emissions (VOC)**
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). Certificates of Compliance for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com

 **ClimaPlus™ Warranty Performance**
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

 **High Recycled Content**
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

 **Firecode®**



This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete list of all USG ceiling panels on biopreferred.gov website.



GREENGUARD Gold Certification offers stricter certification criteria, considers safety factors to account for sensitive individuals (such as children and the elderly), and ensures a product is acceptable for use in environments such as schools and healthcare facilities. It is referenced by both The Collaborative for High Performance Schools (CHPS) and the Leadership in Energy and Environmental Design (LEED) Building Rating System.

FOOTNOTES

ASTM E84 surface-burning characteristics
Class A
Flame Spread: 25 or less
Smoke Developed: 50 or less

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Notes
1. Available in Flat Black.
2. USG 2570 has the option to be installed via staple or adhesive.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CLIMAPLUS, FIFTH AVENUE, FIRECODE, FISSURED, RADAR, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

USG Ceiling Solutions