

ELECTRIC WATER HEATERS

Product Type	Model Number	Nominal Capacity Gallons	Rated Storage Volume Gallons	First Hour Delivery (Gallons)	Element Wattage (Standard)	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to top of tank (inches)	Est. Yearly Energy Cost
Hybrid Electric	Heat Pump, 10-Year Limited \	Narranty Tank	/Parts, 1-Yea	r Limited Warra	anty Labor [†]			1		1
Tall	HPHE2K80HD045VUN	80	82	86	4500/4500	21	3.45	26 1/2	69	\$173
Tall	HPHE2K66HD045VUN	66	67	79	4500/4500	21	3.45	26 1/2	61	\$173
Tall	HPHE2K50HD045VUN	50	46	66	4500/4500	21	3.45	22	63	\$113
12-Year Limited	d Warranty Tank/Parts, 1-Yea	ar Limited Wa	rranty Labor	†, Electronic T	hermostat, Toucł	n-Screen Dis	play			
Tall	NEG3J50HD	50	45	67	5500/5500	25	0.93	22	60 1/2	\$419
Short	NEG3J50RD	50	46	66	5500/5500	25	0.92	23	49 3/4	\$424
Tall	NEG3J40HD	40	36	59	5500/5500	25	0.93	20	60 1/4	\$419
Short	NEG3J40RD	40	37	54	5500/5500	25	0.92	20 1/2	50	\$424
9-Year Limited	Warranty Tank/Parts, 1-Year	Limited Warr	anty Labor [†]	Electronic Th	ermostat					
Tall	NEG3H50HD	50	45	62	4500/4500	21	0.93	22	60 1/2	\$419
Short	NEG3H50RD	50	46	62	4500/4500	21	0.92	23	49 3/4	\$424
Tall	NEG3H40HD	40	36	51	4500/4500	21	0.92	20	60 1/4	\$424
Short	NEG3H40RD	40	37	51	4500/4500	21	0.92	20 1/2	50	\$424
6-Year Limited	Warranty Tank/Parts, 1-Year	Limited Warr	anty Labor [†]	Mechanical T	hermostat			1		1
Tall	NEG3F80HD	80	78	80	4500/4500	21	0.93	26	64 1/2	\$647
Tall	NE3F50HD	50	46	62	4500/4500	21	0.92	20 1/2	60 1/2	\$424
Tall	NE3F50HS	50	46	62	4500	21	0.92	20 1/2	60 1/2	\$424
Short	NE3F50RD	50	46	57	4500/4500	21	0.92	23	49 1/4	\$424
Lowboy	NE2F50LD	51	48	51	4500/4500	21	0.92	26 1/2	36	\$424
Tall	NE3F40HD	40	36	53	4500/4500	21	0.92	18	61 1/4	\$424
Tall	NE3F40HS	40	36	53	4500	21	0.92	18	61 1/4	\$424
Short	NE3F40RD	40	37	55	4500/4500	21	0.92	20 1/2	49 3/4	\$424
Lowboy	NE3F40LD	38	35	50	4500/4500	21	0.89	26	33 1/2	\$303
Lowboy	NE3F36LD	36	33	51	4500/4500	21	0.92	24	32	\$424
Table Top	E2F38TD045V	38	35	55	4500/4500	21	0.90	24 x 25	36	\$433
Tall	NE3F30HD	30	47	48	4500/4500	21	0.89	19	46 1/2	\$302
Tall	NE3F30HS	30	27	48	4500	21	0.89	19	46 1/2	\$302
Lowboy	NE3F30LD	28	26	44	4500/4500	21	0.90	24	31 1/4	\$299
Lowboy	NE3F20LS	19.9	19	N/A	4500	21	N/A	20	30	N/A
Compact Electr	ic, 6-Year Limited Warranty Ta	ank/Parts, 1-Ye	ear Limited V	Varranty Labor	t					
Compact	E61-19L-045DV	19	18	N/A	4500/4500	21	N/A	16	31 1/4	N/A
Compact	E61-19L-030D	19	18	N/A	3000/3000	14	N/A	16	31 1/4	N/A
Compact	E61-20U-015SV*∆	19	17	N/A	1500	7	N/A	18	25	N/A
Compact	E61-20U-045SV△	19	17	N/A	4500	21	N/A	18	25	N/A
Compact	E61-12U-015SV*∆	12	12	N/A	1500	7	N/A	16	22 3/4	N/A
Compact	E61-06U-017SV*	6	6	N/A	1650	8	N/A	14 1/4	15 1/4	N/A
6-Year Limited	Warranty Tank/Parts, 1-Year	Limited Warr	anty Labor [†]	Mechanical T	hermostat, Shipp	ed with Fact	ory Insulatio	n Blanket		1
Lowboy	NE2F50LBD	48	44	60	4500/4500	21	0.93	26 1/2	34	\$419
Lowboy	NE3F40LBD	38	35	47	4500/4500	21	0.93	23	32	\$289
Lowboy	NE3F30LBD	28	26	46	4500/4500	21	0.92	20	30	\$292
MH Lowboy	MHNE3F30LD**	28	26	47	4500/4500	21	0.90	22	30	\$299
Point-of-Use, 6	-Year Limited Warranty Tank	/Parts, 1-Yea	r Limited Wa	rranty Labor [†]				·		
Point-of-Use	6 2 EOMS K [‡]	2.5	2.6	N/A	1440	7	N/A	11 3/4 X 10 3/8	14 1/2	N/A
Point-of-Use	6 4 EOMS K [‡]	4	3.8	N/A	1440	7	N/A	11 3/4 X 10 3/8	19 1/4	N/A
Point-of-Use	6 6 EOMS K [‡]	6	5.9	N/A	1440	7	N/A	13 3/4 X 12 1/2	20	N/A
Mobile Home, 6	-Year Limited Warranty Tan	k/Parts, 1-Yea	r Limited Wa	arranty Labor ⁺	·	· 	, 	· 		·
MH - Short	MHNE3F40RD**	40	36	54	4500/4500	21	0.95	22	50	\$410
MH - Short	MHNE3F40RS**	40	36	54	4500	21	0.95	22	50	\$410
MH - Tall	MHNE3F30HD**	30	27	50	4500/4500	21	0.90	19	46 3/4	\$299
MH - Tall	MHNE3F30HS**	30	27	50	3000	14	0.90	19	46 3/4	\$299

ENERGY STAR® Qualified Models

Standard voltage for all models is 240 VAC single phase power. **Side water connections. ^Top inlet/outlet water connections; may be field converted to side inlet/outlet. *Point-of-Use are Reliance® brand products.

Energy Factor ratings shown for Hybrid Electric Heat Pump units are based on operation in the Hybrid mode. Recovery Ratings shown for Hybrid Electric Heat Pump units are based on back up heating element performance.

For models shipped with an insulation blanket, see the "Shipped with Factory Insulation Blanket" section of the table above.

U.S. Craftmaster[®] Water Heaters reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.



GAS WATER HEATERS

Available in Natural Gas or Propane (LP)

Product Type	Model Number	Nominal Capacity Gallons	Rated Storage Volume Gallons	First Hour Delivery (Gallons)	Natural Gas‡ BTU Input	Recovery 90° Rise - Gallons/Hour	Uniform Energy Factor	Diameter (inches)	Height to Vent Connection (inches)	Est. Yearly Energy Cost
12-Year Limited Warr	anty Tank/Parts, 1-Year Li	mited Warran	ty Labor⁺, S	tandard Ven	t (Not for Mobile H	lome Use)				
Tall	NG2J5040TR*	50	48	84	40,000	43	0.62	22	61	\$298
Tall	NG2J4040TR	40	38	67	40,000	42	0.62	20	62	\$220
9-Year Limited Warra	nty Tank/Parts, 1-Year Lin	nited Warrant	y Labor†, Ele	ectronic The	rmostat			1	,	
Tall	NG1H5040TR	50	48	81	40,000	43	0.62	21	61	\$298
Tall	NG2H4040TR*	40	38	67	40,000	42	0.55	20	62	\$220
Short	NG2H4040SR	40	38	67	40,000	41	0.59	22	52 1/2	\$205
6-Year Limited Warra	nty Tank/Parts, 1-Year Lin	nited Warrant	y Labor⁺, Me	echanical Th	ermostat					
Tall	NG1F5040TR*	50	48	76	40,000	43	0.65	21	60 3/4	\$284
Tall	NG2F5060T	50	49	83	60,000	65	0.62	22	65 1/2	\$298
Tall	NG2F4040TR*	40	38	67	40,000	42	0.55	20	62	\$220
Short	NG2F4040SR*	40	38	83	40,000	41	0.62	22	52 1/2	\$298
Tall	NG2F4035TR*	40	38	65	35,500	38	0.59	20	61 3/4	\$205
Tall	NG2F3032TR*	30	29	62	32,000	31	0.60	18	60 1/2	\$201
Short	NG2F3032SR*	30	29	55	32,000	32	0.60	20	50 1/4	\$201
	nty Tank/Parts, 1-Year Lin	nited Warrant		• •	actory Insulation I	1			1	
Tall with Blanket	NG1F3032TBR*	30	29	62	32,000	32	0.60	16	60 1/2	\$201
Short with Blanket	NG1F3032SBR*	30	29	65	32,000	32	0.60	18	50 1/4	\$201
Short with Blanket	NG1F4040SB*	40	38		40,000	43				
Tall with Blanket	NG1F4040TB*	40	38	78	40,000	43	0.65	18	62	\$284
	nty Tank/Parts, 1-Year Lin			1						
Tall	NG2C4035TR	40	38	65	35,500	38	0.59	20	61 3/4	\$205
•	/ent, 6-Year Limited Warra			1					50	
Direct Vent	DVG62-50T40-NOV #	50	48	77	40,000	44	0.66	22	59	\$280
Direct Vent	DVG62-40S38-NOV #	40	39	64	38,000	42	0.60	22	50	\$201
	mited Warranty Tank/Part				1	, I	0.00		70 5 (0	4070
Power Vent	PVG62-75T76-NV**	75	72	116	76,000	84	0.69	26	70 5/8	\$270
Power Vent	PVG6250T50NVS**	50	48	97	50,000	56	0.72	22	68 1/8	\$259
Power Vent	PVG6240T50NVS**	40	38	87	50,000	56	0.70	20	68 1/2	\$266
	-Year Limited Warranty Ta			-		-				
Power Direct Vent	PDVG62-75T76-NV	75	72	129	76,000	84	0.68	26	70 5/8	\$275
Power Direct Vent	PDVG62-50T62-NV**	50	48	118	62,000	69	0.73	22	69	\$257
Power Direct Vent	PDVG62-50T45-NV**	50	48	81	45,000	50	0.72	22	67 1/2	\$262
Power Direct Vent	PDVG62-40S40-NV**	40	38	74	40,000	45	0.68	22	58 1/4	\$182
	rd-Vent w/ Convertible Co		-	-	1		1	1		
Mobile Home	MHG62 40T35R	40	38	59	35,500	36	0.58	20	61 3/4	\$208
Mobile Home	MHG62 30T35R	30	29	63	35,500	36	0.61	18	61 1/2	\$198
	Vent w/ Convertible Contro			1						
Mobile Home	MHDV-62-40T32	40	38	57	32,000	33	0.59	20	58 3/4	\$205
Mobile Home	MHDV-62-30T30	30	29	60	30,000	31	0.61	18	58	\$198
Mobile Home	MHDV-62-50T40	50	47	67	40,000	43	0.56	22	57	\$216
	mited Warranty Tank/Part				1					
Large Capacity	G62-100T77-4NOV**	100	95	170	75,100	81	0.58	27 3/4	68 1/2	\$318
Large Capacity	G2F7575T4NOV ⁺⁺	74	71	125	75,100	81	0.60	26 1/2	61	\$308

ENERGY STAR[®] Qualified Models

* For propane model change the "N" to "L". ** For Propane model change "N" to "P". ++For Propane model change "NOV" to "PV".

+For complete information consult written warranty.

‡ Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and Recovery by up to 3 gallons on propane models.
‡‡ Atmospheric Direct Vent models DVG62-50T40-NOV and DVG62-40S38-NOV are not available in propane. 40 gallon model requires 67" minimum and 50 gallon model requires 76" minimum vertical clearance for factory provided/required coaxial vent kit. These coaxial vent kits terminate horizontally through a side wall only.

For models shipped with an insulation blanket, see the "Shipped with Factory Insulation Blanket" section of the table above.

Power Vent model PVG62-75T76-NV and Power Direct Vent models PDVG62-75T76-NV and PDVG6250T62NV are factory equipped with side loop water connections for combination domestic hot water and hydronic heating applications where local codes permit.

U.S. Craftmaster® Water Heaters reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.