



## White Lithium Grease Biobased Lubricating Grease

Part No: 10307, 10308, 10309, 10310, 10311

### DESCRIPTION

White Lithium Grease is a premium quality biobased, biodegradable multipurpose grease formulated from USA-grown vegetable oils and a lithium-based thickener.

### APPLICATIONS

- ▶ Recommended for most chassis and general purpose lubrication
- ▶ Prevents rust and corrosion
- ▶ Designed for protection between all metal to metal contact areas
- ▶ Recommended for farm and plant machinery
- ▶ Recommended for environmentally sensitive areas near waterways
- ▶ Replaces and freely mixes with petroleum based grease

### BENEFITS

- ▶ White color helps differentiate new grease from old grease
- ▶ Contains extreme pressure additives to minimize friction and wear
- ▶ Superior lubricity reduces heat and lessens energy consumption
- ▶ Higher flash point than petroleum based greases for increased safety
- ▶ Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- ▶ USDA BioPreferred™ listed and approved
- ▶ Manufactured from renewable USA-grown crop based oils

### PERFORMANCE LEVELS

- ▶ Meets NLGI "LB" classification for chassis lubricant
- ▶ Operating temperature range -40°F (-40°C) to +287°F (+141°C)

### TYPICAL PROPERTIES

Property	Method	Value
Appearance	visual	White to Off-White
NLGI Grade	2	
Cone Penetration, worked 60X	ASTM D-217	265-295
Four Ball Wear Scar (mm)	ASTM D-2266	0.54
Four Ball Weld Load (kg)	ASTM D-2596	250
Four Ball Load Wear Index (kg)	ASTM D-2596	51
Timken OK Load (lbs.)	ASTM D-2509	25
Drop Point °C (°F)	ASTM D-2265	197 (387)
Oil Separation	ASTM D-1742	<5%
Base Oil Viscosity at 40°C (cSt)	ASTM D-445	51
Base Oil Viscosity at 100°C (cSt)	ASTM D-445	10.5
Base Oil Viscosity Index	ASTM D-2270	202
Base Oil Flash Point °C (°F)	ASTM D-92	326 (619)
Base Oil Biodegradability	OECD	Pass
Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

### PACKAGING

8-oz Squeeze Tube	35-lb Plastic Pail
14-oz Cartridge	120-lb Metal Drum
	400-lb Metal Drum

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.