

SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

### 29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

### **Product identifier**

Trade name

SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	
1-800-TEAMVAL (1-800-832-6825)	Product Information
, ,	1-800-TEAMVAL (1-800-832-6825)

### **SECTION 2. HAZARDS IDENTIFICATION**

### **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	25.234
Mineral Oil		Asp. Tox. 1; H304	5.871



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

# SECTION 4. FIRST AID MEASURES

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	:	No hazards which require special first aid measures.

# **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local
	circumstances and the surrounding environment.



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
V//955	

	Water spray Foam Carbon dioxide (CO2) Dry chemical	
Specific hazards during firefighting	Do not allow run-off from fire fighting to enter drains or wat courses.	ter
Hazardous combustion products	carbon dioxide and carbon monoxide Hydrocarbons nitrogen oxides (NOx)	
Specific extinguishing methods		
	Product is compatible with standard fire-fighting agents.	
Further information	Standard procedure for chemical fires.	
Special protective equipment for firefighters	In the event of fire, wear self-contained breathing apparatu	JS.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.	ł
Environmental precautions	: Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
Other information	: Comply with all applicable federal, state, and local regulations	

# SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>For personal protection see section 8.</li> </ul>
Materials to avoid	: No materials to be especially mentioned.



 SAFETY DATA SHEET
 Revision Date: 01/08/2018

 Print Date: 12/7/2019
 SDS Number: R0252918

 SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil
 Version: 1.4

 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV955

Page: 4

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
Distillates (Petroleum),	64742-54-7	TWA	5 mg/m3	OSHA Z-1
Hydrotreated Heavy Paraffinic			Mist	
•		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	

#### Hazardous components without workplace control parameters

Components	CAS-No.
Mineral Oil	
Engineering measures	: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Personal protective equipment Respiratory protection :	No personal respiratory protective equipment normally required.
Eye protection :	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection :	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures :	General industrial hygiene practice.



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
<sup>™</sup> Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: liquid	
Colour	: amber	
Odour	: mild	
Odour Threshold	: No data available	
рН	: No data available	
Melting point/freezing point	: No data available	
Boiling point/boiling range	: 626 °F / 330 °C (1,013.333333 hPa)	
Flash point	Calculated Phase Transition Liquid/G : > 390 °F / 199 °C Method: Cleveland open cup	as
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Upper explosion limit	: 6 %(V) Calculated Explosive Limit	
Lower explosion limit	: 1 %(V) Calculated Explosive Limit	
Vapour pressure	: 1.33333333 hPa (20 °C) Calculated Vapor Pressure	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.8473 g/cm3	
Solubility(ies) Water solubility	: No data available	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Thermal decomposition	: No data available	
Viscosity Viscosity, dynamic	: No data available	



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various	Version: 1.4
countries	
VV955	

Viscosity, kinematic : 63.17 mm2/s (40 °C)

Oxidizing properties : No data available

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

# SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion				
Acute toxicity					
Not classified based on availal	ble information.				
Components:					
Distillates (Petroleum), Hydrot	reated Heavy Paraffinic:				
Acute oral toxicity	: LD50 (Rat): > 15 g/kg				
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg				
Skin corrosion/irritation					
Not classified based on availal	ble information.				
Components:					
Distillates (Petroleum), Hydrotreated Heavy Paraffinic:					
Result: Slight, transient irritation	on -				
0					

### Serious eye damage/eye irritation Not classified based on available information. Product:



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV955	Version: 1.4

Remarks: Unlikely to cause eye irritation or injury.

### Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Product: No aspiration toxicity classification

#### Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

Mineral Oil: May be fatal if swallowed and enters airways.

# Further information

<u>Product:</u> Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
<sup>™</sup> Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

### **SECTION 12. ECOLOGICAL INFORMATION**

Ec	oto	oxi	city		
<u>Pr</u>	odu	uct	:		
_				-	

Persistence and degradabilit <u>Components:</u> No data available Bioaccumulative potential	у	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Components: Distillates (Petroleum), Hydrotre Toxicity to fish		ted Heavy Paraffinic <b>:</b> LL50 (Fish): > 100 mg/l Exposure time: 96 h
Chronic aquatic toxicity	:	Not classified based on available information.
Ecotoxicology Assessment Acute aquatic toxicity	:	Not classified based on available information.

No data available	
Bioaccumulative potential	
Components:	
No data available	
Mobility in soil	
Components:	
No data available	
Other adverse effects	
No data available	
Product:	
Additional ecological	: No data available
information	

### **Components:**

# SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and federal regulations.



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
<sup>™</sup> Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

Contaminated packaging

: Empty remaining contents.

### **SECTION 14. TRANSPORT INFORMATION**

### International transport regulations

#### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

### U.S. DOT - ROAD

Not dangerous goods	

### CFR\_RAIL\_C

Not dangerous goods

### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

### TDG\_ROAD\_C

Not dangerous goods

### TDG\_RAIL\_C

Not dangerous goods

### TDG\_INWT\_C

Not dangerous goods

# INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

# INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

# INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
<sup>™</sup> Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	

#### MX\_DG

Not dangerous goods

#### \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

CERCLA Reportable Quantity	y					
Components		CAS-No.	Component RQ	Calculated product RQ		
			(lbs)	(lbs)		
TOLUENE		108-88-3	1000	*		
*: Calculated RQ exceeds reasonably attainable upper limit.						
SARA 304 Extremely Hazardous Substances Reportable Quantity						
This material does not contain any components with a section 304 EHS RQ.						
SARA 311/312 Hazards	:	No SARA Hazards				
SARA 313				emical components with		
				threshold (De Minimis) Title III, Section 313.		
California Prop 65		This product does n	ot contain any che	emicals known to the		
	State of California to cause cancer, birth defects, or other					
		reproductive harm.		4 a v! a a .		
The components of this product are reported in the following inventories:         DSL       : All components of this product are on the Canadian DSL						
DOL	•					
AICS	:	Not in compliance with the inventory				
		-				
ENCS		Contact your sales representative for additional information.				
KECI	·	: On the inventory, or in compliance with the inventory				
	•					
IECSC	:	q (quantity restricted)				
PICCS	:	: Not in compliance with the inventory				
TSCA	:	: On TSCA Inventory				



SAFETY DATA SHEET	Revision Date: 01/08/2018
	Print Date: 12/7/2019
	SDS Number: R0252918
SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil	Version: 1.4
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV955	


#### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

### **SECTION 16. OTHER INFORMATION**

### Further information

Revision Date: 01/08/2018



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

#### Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Version: 1.4



Revision Date: 01/08/2018

Print Date: 12/7/2019 SDS Number: R0252918

SynPower™ Full Synthetic Advanced SAE 5W-30 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV955

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

SAFETY DATA SHEET

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

**PPE : Personal Protective Equipment** 

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System