

	Page: 1
SAFETY DATA SHEET	Revision Date: 01/09/2019
	Print Date: 8/13/2020
	SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Stroke Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822384	Version: 2.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Multi-Purpose 2-Stroke Motor Oil

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Combustible liquid.
Causes skin irritation.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Wash skin thoroughly after handling.
Wear protective gloves/ eye protection/ face protection.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 822384

Response:

IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant
 foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal
 plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=30.00 - < 40.00
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315	>=20.00 - < 30.00
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	Not a hazardous substance or mixture.	>=20.00 - < 30.00
Naphtha (petroleum), heavy aromatic	64742-94-5	Asp. Tox. 1; H304	>=1.50 - < 5.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical
 advice.
 If symptoms persist, call a physician.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
™ Trademark, Valvoline or its subsidiaries, registered in various countries
822384

- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
Causes skin irritation.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
nitrogen oxides (NO_x)
Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

Further information : Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
 Use personal protective equipment.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.
 Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 No smoking.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 822384

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES, SOLVENT- REFINED HEAVY PARAFFINIC	64741-88-4	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

into eyes.

- Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Discard gloves that show tears, pinholes, or signs of wear.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : < -38 °F / < -39 °C
- Boiling point/boiling range : > 356 °F / 180 °C
 (1013 hPa)
- Flash point : 196 °F / 91 °C
- Evaporation rate : 0.1
 butyl acetate=1
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Static-accumulating flammable liquid.
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : 6.0 %(V)
- Lower explosion limit / Lower flammability limit : 1.0 %(V)
- Vapour pressure : 0.2 mmHg (68 °F / 20 °C)

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822384

Relative vapour density : No data available

Relative density : No data available

Density : Average 0.8550 g/cm³ (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 36.8 mm²/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

Naphtha (petroleum), heavy aromatic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m³
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
 Result : No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment : Irritating to skin.
 Result : Irritating to skin.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species : Rabbit
 Result : No skin irritation

Naphtha (petroleum), heavy aromatic:

Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
 Result : No eye irritation

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species : Rabbit
 Result : Slight, transient irritation

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

Respiratory or skin sensitisation
Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type : Buehler Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Test Type : Buehler Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.
 Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Genotoxicity in vitro : Test Type: Ames test
 Result: negative

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Genotoxicity in vitro : Test Type: Ames test
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

No aspiration toxicity classification

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

No aspiration toxicity classification

Naphtha (petroleum), heavy aromatic:

May be fatal if swallowed and enters airways.

Further information
Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >=

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384

toxicity) 1,000 mg/l
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: semi-static test
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Persistence and degradability
Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable
 Biodegradation: 58.6 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B
 Remarks: Information given is based on data obtained from similar substances.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822384

No data available

Bioaccumulative potential**Components:**

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available
information

Components:**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822384

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

	Page: 15
SAFETY DATA SHEET	Revision Date: 01/09/2019
	Print Date: 8/13/2020
	SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Stroke Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822384	Version: 2.3

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/09/2019

NFPA:	HMIS III:
--------------	------------------

SAFETY DATA SHEET


Revision Date: 01/09/2019

Print Date: 8/13/2020

SDS Number: R0172415

Version: 2.3

Valvoline™ Multi-Purpose 2-Stroke Motor Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822384



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

Full text of H-Statements

H227 Combustible liquid.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

	Page: 17
SAFETY DATA SHEET	Revision Date: 01/09/2019
	Print Date: 8/13/2020
	SDS Number: R0172415
Valvoline™ Multi-Purpose 2-Stroke Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822384	Version: 2.3

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System