



Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Date of Revision: 09/19/2019 Revision: 02

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **SEF 50:1 2 Cycle**

1.2 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.3 Recommended Use: Small Engine Fuel

1.4 **RESTRICTIONS on USE** THIS PRODUCT IS FOR SMALL 2 CYCLE GASOLINE ENGINE USE ONLY!

1.5 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

1.6 See Section 16.3 for CHEMTREC in Country Emergency Number

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Hazard Categories

Highly Flammable liquid/vapor	Category 2
Specific Target Organs toxicity single exposure	Category 3
Specific Target Organs repeated exposure	Category 2
Eye Irritation	Category 2A
Skin Irritation	Category 2
Acute Toxicity Oral	Category 4
Acute Toxicity Inhalation	Category 4
Mutagenicity	Category 1B
Carcinogen	Category 1B
Reproductive Toxicity	Category 2
Aspiration Hazard	Category 1
Toxic to Aquatic Life Long Lasting Effects	Category 2

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

2.2 Signal Word: **Danger**



2.3 Pictograms:

Flame Health Hazard Irritant Aquatic Hazard

2.4 Hazard Statements

PHYSICAL HAZARDS:

H224: Extremely flammable liquid and vapor.

HEALTH HAZARDS:

H302: harmful if swallowed.

H304: May be fatal if swallowed and enter the airway.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361: Suspected of damaging fertility or the unborn child.

H373: May causes damage to organs through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

READ SDS BEFORE USE.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames- No smoking.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe mist.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P273: Avoid release to the environment.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

P280: Wear protective gloves, clothing, and eye protection.

RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: USA Immediately call the National POISON CENTER at **800-222-1222**. **OUTSIDE USA** Immediately call poison center or doctor. **DO NOT** induce vomiting.

P303+P361+P353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED. Remove to fresh air and keep comfortable for breathing.

P305+P351: IF IN EYES: Rinse cautiously with water for at least 15 minutes.

P308+P313: If exposed or concerned, get medical attention.

P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse
P313+P332+P337: If skin or eye irritation persists get medical attention.

H314: Get medical attention if you feel unwell.

P370: In case of fire use foam, carbon dioxide, dry chemicals to extinguish fire.

P391: Collect spillage.

STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	GHS Classification
Blend	Blend	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	97-98%	None
Proprietary	Proprietary	Synthetic 2 Cycle Oil	2 - 3%	Asp. Tox. 1 H304

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

3.2 Hydrocarbon Blend

Chemical Names	CAS#	EC#	GHS Classification
1,1,2-Trimethylethane	78-78-4	201-142-8	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Aquatic Chronic 2 H411
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Repr. 2 H361, STOT RE 2 Central nervous sys H373
Alkylate Full Range	64741-64-6	265-066-7	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central Nervous Sys. Inhalation H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411
Hydrotreated light distillate	64742-47-8	265-149-8	Asp. Tox. 1 H304

3.3 Trade Secret Provision and Chemical Concentration Disclosure: Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and apply to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Extreme overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following exposure may be more related to the time between the exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists, and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with the material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container in a cool, dry, and well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20 - 300 ppm TWA	20- 300 ppm TWA
Synthetic 2 Cycle Oil	5 mg/m3 TWA	5 mg/m3 TWA

8.2.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse.
Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

8.6 Protective Clothing Pictograms



SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Blue

Odor: Aromatic Hydrocarbon Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1,): 0.725

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble

Melting point/freezing point: Not Available

Flash Point: -31.9°F (-35.5°C) close cup

Boiling Point / Range: 97.7 – 402.1°F
(36.5 – 205.6°C)

Lower Explosive Limits (vol % in air): 1%

Upper Explosive Limits (vol % in air): 8%

Viscosity: <20.5mm²/s @104°F 40°C

Auto ignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 1666 mg/kg

ATE (Dermal): 2500 mg/kg

ATE (Inhalation vapor/mist): 5.9 mg/l mist

11.1.1 OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause Harmful Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Harmful Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause Harmful Inhalation Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and/or Eye Contact.

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that components of this product may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause genetic defects.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause serious eye irritation.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Data Base shows that components of this product may cause damage to the central nervous system (CNS).

11.11 Specific Target Organ Toxicity (Repeated Exposure): Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

11.12 Signs and Symptoms: Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Not classifiable as a human carcinogen	Not classifiable as a human carcinogen	Not listed	Not listed
Synthetic 2 Cycle Oil	None shown	None shown	None shown	None shown

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	It is expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		
Synthetic 2 Cycle Oil	Under Section 311 of the Clean Water Act and the Oil Pollution Control Act of 1990, this material is considered to be toxic to aquatic organisms.		

Toxicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause long-term toxicity to aquatic life.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marking: MARINE POLLUTANT Alkylate Full Range when shipping ground greater than 119 gallons' single container or any quantity by water

14.2 IMDG Transport Information



ID No.: UN 1203

Shipping Name: GASOLINE

Hazard Class: 3

Packing Group: II

Flash Point: (-35.5°C c.c.)

EmS Number: F-E, S-E

Label: Flammable


Placard: Flammable

Marking: Marine Pollutant Alkylate Full Range


14.3 UN Dangerous Goods Transport Information

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System




ID No.: UN1203
Shipping Name: Gasoline
Hazard Class: 3
Packing Group: II
Label: Flammable
Placard: Flammable
Marking: Marine Pollutant Alkylate Full Range



Use marking when shipping as a consumer commodity ground in the US

14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over
1.0L (0.3 gallons) net capacity each.
Outer Package not over 30kg (66lbs) each



Use marking when shipping as a limited quantity by vessel.

14.5 IMDG Transport Limited Quantity

Inner packaging not over
1.0L (0.3 gallons) net capacity each.
Outer Package not over 30kg (66lbs) each

ID No.: UN 1203

Shipping Name: GASOLINE LTD.QTY.

Hazard Class: 3

Packing Group: II

Flash Point: (-35.5° C c.c.)

EmS Number: F-E, S-E

NOTE: Because the MARINE POLLUTANT Alkylate Full Range in the inner packaging of the combination packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required.

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

Toxic Release Inventory (TRI): This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
108-88-3	Phenylmethane	18%

This information must be included in all SDSs that are copied and distributed for this material.

CERCLA Hazardous Substances and corresponding RQs: Phenylmethane 1000lbs

SARA Community Right-to-Know Program: All components of this blend.

Clean Water Act: Synthetic 2 Cycle Oil

Clean Air Act: 1,1,2-Trimethylethane

OSHA: All ingredients are regulated by 28 CFR 1910.1200.

State Regulations California prop. 65



WARNING-Cancer and Reproductive Harm - www.P65Warnings.ca.gov."

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 International Regulations:

Australian Inventory of Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements

National Existing Chemical Inventory in Taiwan: All components of this product are on Inventory or are exempt from Inventory requirements

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements

SEF 50:1 2 Cycle


Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller onLine, European Chemical Agency Data Base and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC in-country emergency dial numbers:

 In-Country Dial Numbers	Local # Provided in Country	Toll Free in Country*	Greeting Language
AMERICAS			
CHEMTREC Argentina (Buenos Aires)	+(54)-1159839431		Latin American Spanish
CHEMTREC Brazil (Rio De Janeiro)	+(55)-2139581449		Portuguese
CHEMTREC Cayman Islands	+(1)-345-749-8392		English
CHEMTREC Chile (Santiago)	+(56)-225814934		Latin American Spanish
CHEMTREC Colombia *		01800-710-2151	Latin American Spanish
CHEMTREC Costa Rica*	+(506)-40003869		Latin American Spanish
CHEMTREC Mexico*		01-800-681-9531	Latin American Spanish
CHEMTREC Panama	+(507)-8322475		Latin American Spanish
CHEMTREC Peru (Lima)	+(51)-17071295		Latin American Spanish
CHEMTREC Trinidad and Tobago*	+(1)-868-224-5716		English

SEF 50:1 2 Cycle

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

16.3 CHEMTREC in-country emergency dial numbers continued:

MIDDLE EAST			
CHEMTREC Bahrain (Bahrain)	+ (973)-16199372		Arabic
CHEMTREC Israel (Tel Aviv)	+ (972)-37630639		Hebrew
CHEMTREC Saudi Arabia*	+ (966)-8111095861		Arabic and English
CHEMTREC Kuwait National	+965-22274681		Arabic and English
SUB SAHARAN AFRICA			
CHEMTREC South Africa*		0-800-983-611	English
EAST ASIA			
CHEMTREC Hong Kong (Hong Kong)*		800-968-793	Cantonese
CHEMTREC Japan (Tokyo)	+ (81)-345209637		Japanese
CHEMTREC South Korea*		00-308-13-2549	Korean
CHEMTREC South Korea	+ (82) 070-7686-0086		Korean
CHEMTREC Taiwan*		00801-14-8954	Mandarin
SOUTHEAST ASIA			
CHEMTREC Indonesia*		001-803-017-9114	Indonesian
CHEMTREC Malaysia *		1-800-815-308	Malay
CHEMTREC Malaysia (Kuala Lumpur)	+ (60)-327884561		Malay
CHEMTREC Philippines *		1-800-1-116-1020	Tagalog
CHEMTREC Philippines (Manila)	+ (63) 2-395-3308		Tagalog
CHEMTREC Singapore*		800-101-2201	English and Mandarin
CHEMTREC Singapore	+ (65)-31581349		English and Mandarin
CHEMTREC Thailand *		001-800-13-203-9987	Thai
CHEMTREC Vietnam (Hanoi)*	+ (84)-444581938		Vietnamese
SOUTH ASIA			
CHEMTREC Bangladesh††	N/A	N/A	Bengali
CHEMTREC India *		000-800-100-7141	Hindi
AUSTRALIA & OCEANIA			
CHEMTREC Australia (Sydney)	+ (61)-290372994		English
CHEMTREC New Zealand (Auckland)*	+ (64)-98010034		English
*Phone numbers for countries marked with an asterisk must be dialed within the country			
*Phone numbers for countries marked with an asterisk must be dialed within the country.			
†† Phone numbers marked with a double dagger have a DID and greeting ONLY supplied by CHEMTREC			

16.4 SDS Preparation Date 01/23/2016

SDS Previous Issue Date: None

SDS Revision Date: 01/22/2019 Sections 2,3,8,11,12,14,15,16

SDS Revision Date: 09/19/2019 Sections 2,3,8,11, 15,16

Prepared by SJC Compliance Education, Inc
 16516 El Camino Real Suite 417
 Houston, TX 77062
VP@sicedu.org

