



## *Safety Data Sheet*

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System

Date of Revision: 01/25/2019

Revision: 01

### Section 1 - Chemical Product and Company Identification

1.1 Product Name: **Fix It Fuel**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Small Engine Fuel

1.5 **RESTRICTIONS on USE** THIS PRODUCT IS FOR SMALL 4 CYCLE ENGINE USE ONLY!

1.6 Emergency Response Number: CHEMTREC 800-424-9300

International Emergency Telephone Number: +1-703-527-3887

1.7 See Section 16.3 for CHEMTREC in Country Emergency Numbers

### Section 2 - Hazards Identification

#### 2.1 GHS HAZARD

##### Hazard Classes

##### Hazard Categories

Flammable liquid/vapor

Category 2

Specific Target Organs single exposure

Category 3

Specific Target Organs repeated exposure

Category 2

Eye Irritation

Category 2A

Skin Irritation

Category 2

Acute Toxicity (Oral)

Category 4

Acute Toxicity (Dermal)

Category 4

Mutagenicity

Category 1B

Carcinogen

Category 1B

Reproductive Toxicity

Category 2

Aspiration Hazard

Category 1

Toxic to Aquatic Life Long Lasting Effects

Category 2

2.2 Signal Word: **Danger**

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System



Flame

Health Hazard

Irritant

Aquatic Hazard

### 2.3 Pictograms:

### 2.4 Hazard Statements

#### PHYSICAL HAZARDS:

H224: Highly flammable liquid and vapor

#### HEALTH HAZARDS:

H302: Harmful if swallowed

H304: May be fatal if swallowed and enter the airway

H312: Harmful in contact with skin

H315: Causes skin irritation

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

H340: May cause genetic defects

H350: May cause cancer

H361: Suspected of damaging fertility or the unborn child

H373: May cause damage to organs through prolonged or repeated exposure

#### ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long lasting effects

#### PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children

P201: Obtain special instructions before use.

READ SDS BEFORE USE

P202: Do not handle until all safety precautions have been read and understood

P210: Keep away from sparks and open flames- No smoking

P240: Ground or bond container and receiving equipment

P241: Use explosion-proof equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P260: Do not breathe vapors

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P271: Use only outdoors or in well ventilated area

P273: Avoid release to the environment

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

**P280:** Wear protective gloves, clothing and eye protection

### RESPONSE STATEMENTS:

**P303+P361+P353:** IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water  
**P304+P340:** IF INHALED. Remove to fresh air and keep comfortable for breathing  
**P305+P351:** IF IN EYES rinse cautiously with water for at least 15 minutes  
**P308+P313:** If exposed or concerned get medical attention  
**P362+P364:** IF ON CLOTHING, take off contaminated clothing and wash it before reuse  
**P313+P332+P337:** If skin or eye irritation persists get medical attention  
**H314:** Get medical attention if you feel unwell  
**P370:** In case of fire use foam, carbon dioxide, dry chemical to extinguish fire

### STORAGE STATEMENTS:

**P403+P405+P235:** Store in a well-ventilated place, store locked up and keep cool

### DISPOSAL STATEMENTS:

**P501:** Dispose of content and/or container in accordance with local, regional, national or international regulations

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Repeated exposure may cause skin dryness or cracking

## Section 3 - Composition / Information on Ingredients

### 3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	80-88%	None
111-76-2	203-905-0	3-Oxa-1-heptanol	10-15%	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox. 4 H332
73398-61-5	277-452-2	Glycerides, mixed decanoyl and octanoyl	2-5%	Eye Irrit 2 H319

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### 3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification
1,1,2-Trimethylethane	78-78-4	201-142-8	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Aquatic Chronic 2 H411
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Repr. 2 H361, STOT RE 2 Central nervous sys H373
Alkylate Full Range	64741-64-6	265-066-7	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central Nervous Sys. Inhalation H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411
Hydrotreated light distillate	64742-47-8	265-149-8	Asp. Tox. 1 H304

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** In accordance with OSHA and GHS Regulations we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and are applicable to the hazards as identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

**4.5 After first aid, get appropriate paramedic, or community medical support.** The severity of outcome following ingestion may be more related to the time between ingestion and treatment, rather than the amount ingested. Therefore, there is a need for rapid treatment of any ingestion exposure.

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose the specific chemical percentages.

### Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire

**5.2 Hazardous Combustion Products:** Avoid fumes of burning product.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam

**5.4 Fire Fighting Equipment/Instructions:** Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

### Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

### Section 7 - Handling and Storage

**7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin or clothing. Keep container tightly closed. Avoid inhalation.

**7.2 Storage Requirements:** Store in a tightly closed container in a cool, dry and well-ventilated area.



## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### Section 8 - Exposure Controls / Personal Protection

#### 8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20-300ppm TWA	20-300ppm TWA
3-Oxa-1-heptanol	20ppm TWA	50ppm TWA
Glycerides, mixed decanoyl and octanoyl	Not Established	Not Established

#### 8.2

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.**

**OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation are preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

#### 8.5 Personal protective equipment

##### 8.5.1 Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

##### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Viton is a Registered Trademark of The DuPont Company

##### 8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

##### 8.5.4 Skin and body protection

Impervious-clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### 8.6 Protective Clothing Pictograms



Splash Goggles

Gloves

Protective Apron

Vapor Respirator

## Section 9 - Physical and Chemical Properties

### 9.1

**Physical State:** Liquid

**Appearance:** Various

**Odor:** Aromatic Hydrocarbon Odor

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** 3.9

**Specific Gravity (H<sub>2</sub>O=1,):** 0.75

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not Applicable.

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**Water Solubility:** Insoluble

**Melting point/freezing point:** Not Available

**Flash Point:** -40°F (-40°C) close cup

**Boiling Point:** 96°F (35.5°C)

**Lower Explosive Limits (vol % in air):** 1%

**Upper Explosive Limits (vol % in air):** 8%

**Viscosity:** Not Available

**Auto ignition Temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** None

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents

**10.4 Hazardous Decomposition Products:** Combustion produces carbon monoxide and carbon dioxide

**10.5 Conditions to Avoid:** Avoid heat, sparks open flames and other ignition sources

## Section 11- Toxicological Information

11.1 Product Name	Results	Species	Dose	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Oral LD50	Rat	>300mg/kg <2000 mg/kg	None Listed
3-Oxa-1-heptanol	Dermal LD50	Rabbit	1066 mg/kg	None Listed
Glycerides, mixed decanoyl and octanoyl	Oral LD50	Rat	5000 mg/kg	None Listed

**11.11.1** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause Oral Toxicity.

**11.11.2** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to be Inhalation Toxicity.

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

**11.11.3** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to Dermal Toxicity.

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin and/or Eye Contact

**11.3 Aspiration Hazard:** European Chemical Agency Data Base shows that components of this product may be fatal if swallowed and enters airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause serious eye irritation.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause damage to fertility or the unborn child.

**11.8 Skin Sensitisation** OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause skin sensitivity.

**11.9 Respiratory Sensitisation** OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Data Base shows that components of this product may cause damage to the central nervous system (CNS).

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains material which may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Not classifiable as a human carcinogen	Not classifiable as a human carcinogen	Not listed	Not listed
3-Oxa-1-heptanol	Not classifiable as a human carcinogen	Confirmed animal with unknown relevance to humans	Not listed	Not listed
Glycerides, mixed decanoyl and octanoyl	Not listed	Not listed	Not listed	Not listed



## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### Section 12 - Ecological Information

#### 12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		
3-Oxa-1-heptanol	LC50 1490 mg/l	Fish	96 hours
3-Oxa-1-heptanol	EC50 835 mg/l	Daphnia	24 hours
Glycerides, mixed decanoyl and octanoyl	LC50 >100mg/l	Fish	96 hours

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

### Section 13 - Disposal Considerations

**13.1 Disposal:** DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

### Section 14 - Transport Information

#### 14.1 US Transport Information



#### DOT Transport Information

ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Marking: MARINE POLLUTANT Marine Pollutant Alkylate Full Range shipping ground greater than 119 gallons single container or any quantity by water

Label: Flammable

Placard: Flammable

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### 14.2 IMDG Transport Information



ID No.: UN 1203

Shipping Name: GASOLINE

Hazard Class: 3

Packing Group: II

Flash Point ((-40°C c.c.)

EmS Number: F-E, S-E

Marking: MARINE POLLUTANT

MARINE POLLUTANT Name: Alkylate Full Range

Label: Flammable

Placard: Flammable

### 14.3 UN Dangerous Goods Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3


Packing Group: II

MARINE POLLUTANT Name: Alkylate Full Range

Marking: MARINE POLLUTANT The marine pollutant mark is only applicable for packages containing more than 5 liter for liquids

Label: Flammable

Placard: Flammable



Use marking when shipping as a consumer commodity ground in the US

### 14.4 DOT Transport Limited Quantity/Consumer Commodity


Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System



Use marking when shipping as a limited quantity by vessel.

### 14.8 IMDG Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

ID No.: UN 1203

Shipping Name: GASOLINE LTD.QTY.

Hazard Class: 3

Packing Group: II

Flash Point: (-40° C c.c.)

EmS Number: F-E, S-E

**NOTE:** Because the MARINE POLLUTANT Naphtha (petroleum), full-range alkylate in the inner packaging of the combination packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required

## Section 15 - Regulatory Information

### 15.1 US Regulations

**US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

**US TRI Reporting SARA 313:** Phenylmethane

**CERCLA Hazardous Substances and corresponding RQs:** Phenylmethane 1000lbs

**SARA Community Right-to-Know Program:** All components of this blend

**Clean Water Act:** Synthetic 2 Cycle Oil

**Clean Air Act:** 1,1,2-Trimethylethane

**OSHA:** All ingredients are regulated by 1910.1200

#### State Regulations

California prop. 65



**WARNING** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### 15.2 International Regulations:

**Australian Inventory of Chemical Substance:** All components of this product are on the Inventory or are exempt from Inventory requirements.

**National Existing Chemical Inventory in Taiwan:** All components of this product are on Inventory or are exempt from Inventory requirements.

**Philippine Inventory of Chemicals and Chemical Substances** All components of this product are on the Inventory or are exempt from Inventory requirements .

**China Existing Chemical Inventory:** All components of this product are on the Inventory or are exempt from Inventory requirements.

## Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

**16.2 References:** CHEMpendium data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base and MSDS and SDS of chemicals in this mixture.

### 16.3 CHEMTREC in country emergency dial numbers:

<b>CHEMTREC</b> In-Country Dial Numbers	Local # Provided in Country	Toll Free in Country*	Greeting Language
<b>AMERICAS</b>			
CHEMTREC Argentina (Buenos Aires)	+(54)-1159839431		Latin American Spanish
CHEMTREC Brazil (Rio De Janeiro)	+(55)-2139581449		Portuguese
CHEMTREC Cayman Islands	+(1)-345-749-8392		English
CHEMTREC Chile (Santiago)	+(56)-225814934		Latin American Spanish
CHEMTREC Colombia *		01800-710-2151	Latin American Spanish
CHEMTREC Costa Rica*	+(506)-40003869		Latin American Spanish
CHEMTREC Mexico*		01-800-681-9531	Latin American Spanish
CHEMTREC Panama	+(507)-8322475		Latin American Spanish
CHEMTREC Peru (Lima)	+(51)-17071295		Latin American Spanish
CHEMTREC Trinidad and Tobago*	+(1)-868-224-5716		English

## Fix It Fuel

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Conforms to The United Nations Regulation Globally Harmonized System

### 16.3 CHEMTREC in country emergency dial numbers continued:

MIDDLE EAST			
CHEMTREC Bahrain (Bahrain)	+(973)-16199372		Arabic
CHEMTREC Israel (Tel Aviv)	+(972)-37630639		Hebrew
CHEMTREC Saudi Arabia*	+(966)-8111095861		Arabic and English
CHEMTREC Kuwait National	+965-22274681		Arabic and English
SUB SAHARAN AFRICA			
CHEMTREC South Africa*		0-800-983-611	English
EAST ASIA			
CHEMTREC Hong Kong (Hong Kong)*		800-968-793	Cantonese
CHEMTREC Japan (Tokyo)	+(81)-345209637		Japanese
CHEMTREC South Korea*		00-308-13-2549	Korean
CHEMTREC South Korea	+(82) 070-7686-0086		Korean
CHEMTREC Taiwan*		00801-14-8954	Mandarin
SOUTHEAST ASIA			
CHEMTREC Indonesia*		001-803-017-9114	Indonesian
CHEMTREC Malaysia *		1-800-815-308	Malay
CHEMTREC Malaysia (Kuala Lumpur)	+(60)-327884561		Malay
CHEMTREC Philippines *		1-800-1-116-1020	Tagalog
CHEMTREC Philippines (Manila)	+(63) 2-395-3308		Tagalog
CHEMTREC Singapore*		800-101-2201	English and Mandarin
CHEMTREC Singapore	+(65)-31581349		English and Mandarin
CHEMTREC Thailand *		001-800-13-203-9987	Thai
CHEMTREC Vietnam (Hanoi)*	+(84)-444581938		Vietnamese
SOUTH ASIA			
CHEMTREC Bangladesh††	N/A	N/A	Bengali
CHEMTREC India *		000-800-100-7141	Hindi
AUSTRALIA & OCEANIA			
CHEMTREC Australia (Sydney)	+(61)-290372994		English
CHEMTREC New Zealand (Auckland)*	+(64)-98010034		English
*Phone numbers for countries marked with an asterisk must be dialed within the country			
*Phone numbers for countries marked with an asterisk must be dialed within the country.			
†† Phone numbers marked with a double dagger have a DID and greeting ONLY supplied by CHEMTREC			

### 16.4 SDS Preparation Date 01/23/2016

SDS Previous issue Date: None

SDS Revision Date: 01/24/2019 Revisions: 2,3,8,11,12,14,15,16

Prepared by SJC Compliance Education, Inc

16516 El Camino Real Suite 417

Houston, TX 77062

[VP@sjcedu.org](mailto:VP@sjcedu.org)

**SMALL  
ENGINE  
FUELS**