



## *Safety Data Sheet*

Conforms to 29 OSHA CFR 1910.1200 and aligns to the United Nations Globally Harmonized System  
Date of Revision: 11/02/2020 Revision: 03

### Section 1 - Chemical Product and Company Identification

1.1 Product Name: **SEF 50:1 2 Cycle Fuel**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Small Engine Fuel

1.5 **RESTRICTIONS on USE** **THIS PRODUCT IS FOR SMALL 2 CYCLE GASOLINE ENGINE USE ONLY!**

1.6 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

1.7 See Section 16.3 for CHEMTREC in Country Emergency Number

### Section 2 - Hazards Identification

#### 2.1 **GHS HAZARD**

##### Hazard Classes

##### Hazard Categories

**Highly Flammable liquid/vapor**

**Category 2**

**Specific Target Organs toxicity single exposure**

**Category 3**

**Specific Target Organs repeated exposure**

**Category 2**

**Acute Toxicity Inhalation**

**Category 4**

**Eye Irritation**

**Category 2A**

**Skin Irritation**

**Category 2**

**Mutagenicity**

**Category 1B**

**Carcinogen**

**Category 1B**

**Reproductive Toxicity**

**Category 2**

**Aspiration Hazard**

**Category 1**

**Toxic to Aquatic Life Long-Lasting Effects**

**Category 2**

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 2.2 Signal Word: **Danger**



Flame      Health Hazard      Irritant      Aquatic Hazard

### 2.3 Pictograms:

### 2.4 Hazard Statements

#### PHYSICAL HAZARDS:

H225: Highly flammable liquid and vapor

#### HEALTH HAZARDS:

H304: May be fatal if swallowed and enter the airway.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if Inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361: Suspected of damaging fertility or the unborn child.

H373: May causes damage to organs through prolonged or repeated exposure.

#### ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

#### PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

**READ SDS BEFORE USE.**

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames- No smoking.

P233: Keep the container tightly closed.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

P280: Wear protective gloves, clothing, and eye protection.

### RESPONSE STATEMENTS:

P301 +310+ P331: IF SWALLOWED: Immediately call a poison center or doctor. DO NOT induce vomiting.

P303+P361+P353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED. Remove to fresh air and keep comfortable for breathing.

P305+P351: IF IN EYES. Rinse cautiously with water for at least 15 minutes.

P308+P313: If exposed or concerned, get medical attention.

P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse  
P313+P332+P337: If skin or eye irritation persists, get medical attention.

H314: Get medical attention if you feel unwell

P370+P378: In case of fire, use foam, carbon dioxide, dry chemical to extinguish the fire.

### STORAGE STATEMENTS:

P403 +P235: Store in a well-ventilated place and keep cool.

P405: Store lockup.

### DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national, or international regulations.

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Repeated exposure may cause skin dryness or cracking

## Section 3 - Composition / Information on Ingredients

### 3.1

| CAS# | EC# | Chemical Names                                           | Percent | Classification   |
|------|-----|----------------------------------------------------------|---------|------------------|
| N/A  | N/A | Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20 | 97-98%  | None             |
| N/A  | N/A | Synthetic 2 Cycle Oil                                    | 2 - 3%  | Asp. Tox. 1 H304 |

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 3.2 Blend

| Chemical Names                | CAS#       | EC#       | Classification                                                                                                                                                                   |
|-------------------------------|------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1,1,2-Trimethylethane         | 78-78-4    | 201-142-8 | Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Aquatic Chronic 2 H411                                |
| Phenylmethane                 | 108-88-3   | 203-625-9 | Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Repr. 2 H361, STOT RE 2 Central nervous sys H373      |
| Alkylate Full Range           | 64741-64-6 | 265-066-7 | Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central Nervous Sys. Inhalation H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411 |
| Hydrotreated light distillate | 64742-47-8 | 265-149-8 | Asp. Tox. 1 H304                                                                                                                                                                 |

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Following OSHA and GHS Regulations, we have withheld specific percentages of the mixture's chemicals. The chemical concentrations have been disclosed as a blend and applicable to the hazards identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**4.5 After first aid, get appropriate paramedic or community medical support.** The severity of the outcome following exposure may be related to the time between the exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, following OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity

### Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

### Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

### Section 7 - Handling and Storage

**7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep container tightly closed. Avoid inhalation.

**7.2 Storage Requirements:** Store in a tightly closed container in a cool, dry, and well-ventilated area.

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 8 - Exposure Controls / Personal Protection

#### 8.1

| Chemical Names                | ACGIH- TLV          | OSHA - PEL          |
|-------------------------------|---------------------|---------------------|
| Alkylate Full Range           | No TLV established  | No PEL established  |
| 2-Methylbutane                | 1000 ppm TWA        | None shown          |
| Phenylethane                  | 20 ppm TWA          | 20 ppm TWA          |
| Hydrotreated light distillate | 5 mg/m <sup>3</sup> | 5 mg/m <sup>3</sup> |
| Synthetic 2 Cycle Oil         | 5 mg/m <sup>3</sup> | 5 mg/m <sup>3</sup> |

#### 8.2.

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.**

**OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

#### 8.5 Personal protective equipment

##### 8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

##### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Viton is a Registered Trademark of The DuPont Company

##### 8.5.3 Eye protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

##### 8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

## Section 9 - Physical and Chemical Properties

### 9.1

**Physical State:** Liquid

**Appearance:** Blue

**Odor:** Aromatic Hydrocarbon Odor

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** >1

**Specific Gravity (H<sub>2</sub>O=1):** 0.73

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not applicable.

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**Water Solubility:** Insoluble

**Melting point/freezing point:** Not Available

**Flash Point:** -31.9°F (-35.5°C) close cup

**Boiling Point / Range:** 97.7 – 402.1°F  
(36.5 – 205.6°C)

**Lower Explosive Limits (vol % in air):** 1%

**Upper Explosive Limits (vol % in air):** 8%

**Viscosity:** ≤20.5mm<sup>2</sup>/s 104°F, 40°C

**Auto ignition Temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** None

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents.

**10.4 Hazardous Decomposition Products:** Combustion produces carbon monoxide and carbon dioxide.

**10.5 Conditions to Avoid:** Avoid heat, sparks, open flames, and other ignition sources.

## Section 11- Toxicological Information

### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 2824 mg/kg

ATE (Dermal): 2439 mg/kg

ATE (Inhalation vapor/mist): 6.67 mg/l mist

**11.1.1** OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Oral Toxicity.

**11.1.2** OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Dermal Toxicity.

**11.1.3** OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Inhalation Toxicity.

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

**11.3 Aspiration Hazard:** European Chemical Agency Database shows that this product's components may be fatal if swallowed and enters airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause serious eye irritation.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components damage fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Database shows that this product's components may damage the central nervous system (CNS).

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains material which may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components can cause cancer.

## Section 12 - Ecological Information

### 12.1

| Product Name                  | Results                                                                                                                          | Species | Exposure |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------|---------|----------|
| Alkylate Full Range           | NOEC 0.1 mg/l                                                                                                                    | Algae   | 72 hours |
| 2-Methylbutane                | LC50 3.1 mg/l                                                                                                                    | Fish    | 96 hours |
| Phenylethane                  | LC50 7.63 mg/l                                                                                                                   | Fish    | 96 hours |
| Hydrotreated light distillate | LC50 2.9 mg/l                                                                                                                    | Fish    | 96 hours |
| Synthetic 2 Cycle Oil         | Under Section 311 of the Clean Water Act and the Oil Pollution Control Act of 1990, this material is toxic to aquatic organisms. |         |          |

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water



## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

### Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

### Section 14 - Transport Information

#### 14.1 DOT Transport Information



**ID No.:** UN 1203

**Shipping Name:** Gasoline

**Hazard Class:** 3

**Packing Group:** II

**Label:** Flammable

**Placard:** Flammable

**Marking:** MARINE POLLUTANT Alkylate Full Range when shipping ground greater than 119 gallons' single container or any quantity by water

#### 14.2 IMDG Transport Information



**ID No.:** UN 1203

**Shipping Name:** GASOLINE

**Hazard Class:** 3

**Packing Group:** II

**Flash Point:** (-35.5°C c.c.)

**EmS Number:** F-E, S-E

**Label:** Flammable


**Placard:** Flammable

**Marking:** Marine Pollutant Alkylate Full Range


## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 14.3 UN Dangerous Goods Transport Information




**ID No.:** ID No.: UN1203  
**Shipping Name:** Gasoline  
**Hazard Class:** 3  
**Packing Group:** II  
**Label:** Flammable  
**Placard:** Flammable  
**Marking:** Marine Pollutant Alkylate Full Range



Use marking when shipping as a consumer commodity ground in the US

### 14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over  
1.0L (0.3 gallons) net capacity each.  
Outer Package not over 30kg (66lbs) each



Use marking when shipping as a limited quantity by vessel.

### 14.5 IMDG Transport Limited Quantity

Inner packaging not over  
1.0L (0.3 gallons) net capacity each.  
Outer Package not over 30kg (66lbs) each

**ID No.:** UN 1203

**Shipping Name:** GASOLINE LTD.QTY.

**Hazard Class:** 3

**Packing Group:** II

**Flash Point:** (-35.5° C c.c.)

**EmS Number:** F-E, S-E

**NOTE:** Because the MARINE POLLUTANT Naphtha (petroleum), full-range alkylate in the combination packaging's inner packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required.

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 15 - Regulatory Information

#### 15.1 US Regulations

**US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

| CAS Number | Chemical Name | Chemical percentage by weight not exceeding |
|------------|---------------|---------------------------------------------|
| 108-88-3   | Phenylmethane | 18%                                         |
| 110-54-3   | n-Hexane      | At demines% limits                          |
| 100-41-4   | Ethylbenzene  | At demines% limits                          |

This information must be included in all SDSs that are copied and distributed for this material.

**CERCLA Hazardous Substances and corresponding RQs:** Phenylmethane 1000lbs, Ethylbenzene 1000 pounds, n-Hexane 5000 pounds.

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None

**Clean Air Act:** 2-Methylbutane

**OSHA:** All ingredients are regulated by 29 CFR 1910.1200,

**California prop. 65**



**WARNING** This product can expose you to chemicals including Ethylbenzene CAS # 100-41-4 and Phenylmethane CAS # 188-88-3, and n-Hexane CAS # 110-54-3, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

#### 15.2 International Regulations:

**Australian Inventory of Chemical Substances:** All components of this product are on the Inventory or are exempt from Inventory requirements

**National Existing Chemical Inventory in Taiwan:** All components of this product are on Inventory or are exempt from Inventory requirements

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

**Philippine Inventory of Chemicals and Chemical Substances** All components of this product are on the Inventory or are exempt from Inventory requirements

**China Existing Chemical Inventory:** All components of this product are on the Inventory or are exempt from Inventory requirements

### Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

**16.2 References:** CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller onLine, European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

#### 16.3 CHEMTREC in-country emergency dial numbers:

| County              | Greeting Language      | City             | Local number     | Toll-Free number |
|---------------------|------------------------|------------------|------------------|------------------|
| Argentina           | Latin American Spanish | Buenos Aires     | 54-1159839431    |                  |
| Brazil              | Portuguese             | Rio De Janeiro   | 55-2139581449    |                  |
| Brazil              | Portuguese             | Sao Paulo        | 55-1143491359    |                  |
| Brazil - Toll-Free  | Portuguese             |                  | 0800 892 0479    | 0800 892 0479    |
| Cayman Islands      | English                | Local (National) | 345-749-8392     |                  |
| Chile               | Latin American Spanish | Santiago         | 56 2 2581 4934   |                  |
| Colombia            | Latin American Spanish |                  | 01800-710-2151   | 01800-710-2151   |
| Costa Rica          | Latin American Spanish |                  | 506-40003869     |                  |
| Dominican Republic  | Latin American Spanish | Santo Domingo    | 1 (829) 956-7588 |                  |
| El Salvador         | Latin American Spanish | San Salvador     | 503 2136 7633    |                  |
| Grenada             | English                | St George        | 1 (473) 230-0165 |                  |
| Guinea              | French                 |                  | 224 660 71 03 00 |                  |
| Mexico              | Latin American Spanish |                  | 01-800-681-9531  | 01-800-681-9531  |
| Panama              | Latin American Spanish |                  | 507-8322475      |                  |
| Peru                | Latin American Spanish | Lima             | 51-17071295      |                  |
| Trinidad and Tobago | English                | National Number  | 1-868-224-5716   |                  |

## SEF 50:1 2 Cycle Fuel

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

### 16.3 CHEMTREC in-country emergency dial numbers continued:

| County       | Greeting Language       | City         | Local number                         | Toll-Free number               |
|--------------|-------------------------|--------------|--------------------------------------|--------------------------------|
| India        | Hindi, Bengali, English |              | 000-800-100-7141                     | 000-800-100-7141               |
| Indonesia    | Indonesian              |              | 001-803-017-9114                     | 001-803-017-9114               |
| Israel       | Hebrew                  | Tel Aviv     | 972-37630639                         |                                |
| Japan        | Japanese                | Tokyo        | 81-345209637                         |                                |
| Malaysia     | Malay                   | Kuala Lumpur | 60-392125794                         | 1-800-815-308                  |
| Philippines  | Tagalog                 | Manila       | +63 2 8395 3308 and 1-800-1-116-1020 | 1-800-1-116-1020               |
| Russia       | Russian                 |              | 8-800-100-6346                       | 8-800-100-6346                 |
| Saudi Arabia | Arabic and English      |              | 966-8111095861                       |                                |
| Singapore    | English and Mandarin    |              | 65-31581349                          | 800-101-2201                   |
| South Korea  | Korean                  |              |                                      | 003-0813-2549 and 080-822-1374 |
| Taiwan       | Mandarin                | Taipei       | 886-2-7741-4207                      | 00801-14-8954                  |
| Thailand     | Thai                    |              | 001-800-13-203-9987                  | 001-800-13-203-9987            |
| India        | Hindi, Bengali, English |              | 000-800-100-7141                     | 000-800-100-7141               |

| County      | Greeting Language | City     | Local number | Toll-Free number |
|-------------|-------------------|----------|--------------|------------------|
| Australia   | English           | Sydney   | 61-290372994 |                  |
| New Zealand | English           | Auckland | 64-98010034  |                  |

| County       | Greeting Language | City | Local number  | Toll-Free number |
|--------------|-------------------|------|---------------|------------------|
| South Africa | English           | None | 0-800—983-611 | 0-800—983-611    |

### 16.4 SDS Preparation Date 01/23/2016

**SDS Previous Issue Date:** None

**SDS Revision Date:** 05/16/2017 Sections 2,3,4,5,8,9,11,14

**SDS Revision Date:** 01/22/2019 Sections 2,3,8,11,12,14,15,16

**SDS Revision Date:** 11/02/2020 Sections 1,2,8,9,11,12,13,15,16

Prepared by SJC Compliance Education, Inc

1319 Varese Dr.

Pearland TX. 77581

[steve@sjcedu.org](mailto:steve@sjcedu.org)

