



Safety Data Sheet

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System
Date of Revision: 12/24/2021 Revision: 02

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **SEF 2 Cycle 40:1**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Small Engine Fuel

1.5 **RESTRICTIONS on USE THIS PRODUCT IS FOR SMALL 2 CYCLE GASOLINE ENGINE USE ONLY!**

1.6 Emergency Response Number: **CHEMTREC 800-424-9300**

Local/International Emergency Telephone Number: **+1-703-527-3887**

1.7 See Section 16.3 for CHEMTREC in Country Emergency Number

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Hazard Categories

Flammable liquid

Category 1

Specific Target Organs toxicity single exposure

Category 3

Specific Target Organs repeated exposure

Category 2

Skin Irritation

Category 2

Acute Toxicity Oral

Category 4

Acute Toxicity Inhalation

Category 4

Mutagenicity

Category 1B

Carcinogen

Category 1B

Reproductive Toxicity

Category 2

Aspiration Hazard

Category 1

Toxic to Aquatic Life Long Lasting Effects

Category 2

GHS Classification Scale (1= severe hazard; 4= slight hazard)

2.2 Signal Word: **Danger**

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System



Flame Health Hazard Irritant Aquatic Hazard Keep away from children

2.4 Hazard Statements

PHYSICAL HAZARDS:

H224: Extremely flammable liquid and vapor.

HEALTH HAZARDS:

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enter the airway.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P203: Obtain special instructions before use, READ SDS BEFORE USE.

P210: Keep away from sparks and open flames- No smoking.

P233: Keep container tightly closed.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe mist.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye protection.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: USA
Immediately call the National POISON CENTER
at **800-222-1222**. DO NOT induce vomiting.

P303+P361+P353: IF ON SKIN, Take off
immediately all contaminated clothing. Rinse
skin with water.

P304+P340: IF INHALED. Remove to fresh air
and keep comfortable for breathing.

P305+P351: IF IN EYES: Rinse cautiously with
water for at least 15 minutes.

P308+P313: If exposed or concerned, get
medical attention.

P313+P332: If skin irritation persists, get
medical attention.

H314: Get medical attention if you feel unwell.

P362+P364: IF ON CLOTHING, take off
contaminated clothing and wash it before reuse

P370: In case of fire, use foam, carbon dioxide,
dry chemicals to extinguish the fire.

P391: Collect spillage.

STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place.
Keep cool.

P405: Store locked up.

DISPOSAL STATEMENTS:

P501: Dispose of content and container per
local, regional, national, or international
regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may
cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
64741-64-6	265-066-7	Naphtha (petroleum), full range alkylate	30-60	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

78-78-4	201-142-8	Isopentane	10-30	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411
108-88-3	203-625-9	Toluene	10-30	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE H336, Repr. 2 H361, STOT RE 2 H373
Prosperity	Prosperity	Synthetic 2 cycle oil	1-5	Asp. Tox. 1 H304

3.3 Trade Secret Provision and Chemical Concentration Disclosure: Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range and applied to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic or community medical support. The severity of outcome following exposure may be more related to the time between the exposure and treatment than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations, as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep the container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container in a cool, dry, and well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Naphtha (petroleum), full-range alkylate	No TLV established	No PEL established
Isopentane	1000 ppm TWA	None shown
Toluene	20 ppm TWA	200 ppm TWA
Synthetic 2 cycle oil	5 mg/3 TWA	5 mg/3 TWA

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

8.2.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder them before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows that air-purifying respirators are appropriate, use a full-face respirator with a multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Red

Odor: Aromatic Hydrocarbon Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1,): 0.7225

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble

Melting point/freezing point: Not Available

Flash Point: -31.9°F (-35.5°C) close cup

Boiling Point / Range: 91.8-376°F
(33.2- 191.1°C)

Lower Explosive Limits (vol % in air): 1%

Upper Explosive Limits (vol % in air): 8%

Viscosity: <20.5mm²/s @104°F 40°C

Auto ignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 1666 mg/kg

ATE (Dermal): 2500 mg/kg

ATE (Inhalation vapor/mist): 5.9 mg/l mist

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Database show that no components of this product cause Harmful Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

11.3 Aspiration Hazard: European Chemical Agency Database shows that components of this product may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause genetic defects.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Database shows that no components of this product cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database shows that no components of this product cause serious eye irritation. However, can irritate your eyes.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Database shows that components of this product may cause damage to the central nervous system (CNS).

11.11 Specific Target Organ Toxicity (Repeated Exposure): Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

11.12 Signs and Symptoms: Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause cancer.

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Naphtha (petroleum), full range alkylate	LC50 3.1 mg/l	Fish	96 hours
Naphtha (petroleum), full range alkylate	EL50 4.5 mg/l	Daphnia	48 hours
Naphtha (petroleum), full range alkylate	EL50 45 mg/l	Algae	96 hours
Isopentane	LC50 34.5 mg/l	Fish	96 hours
Isopentane	EC50 59.4 mg/l	Daphnia	48 hours
Isopentane	EC50 10.7 mg/l	Algae	96 hours
Toluene	LC50 7.63 mg/l	Fish	96 hours
Toluene	EC50 6 mg/l	Daphnia	48 hours
Synthetic 2 cycle oil	Under Section 311 of the Clean Water Act and the Oil Pollution Control Act of 1990, this material is toxic to aquatic organisms.		

Toxicity: OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water.

12.3 Persistence/degradability: Inconclusive technical data.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

12.4 Bioaccumulation: Inconclusive technical data.


12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marking: MARINE POLLUTANT Alkylate Full Range when shipping ground greater than 119 gallons' s
ingle container or any quantity by water

Special Provision: 177 Gasoline, or ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) must be assigned to Packing Group II regardless of variations in volatility.

14.2 IMDG Transport Information



ID No.: UN 1203

Shipping Name: GASOLINE

Hazard Class: 3

Packing Group: II

Flash Point: (-35.5°C c.c.)

EmS Number: F-E, S-E

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant Naphtha (petroleum), full-range alkylate

Special Provision: 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

14.3 UN Dangerous Goods Transport Information



ID No.: ID No.: UN1203

Shipping Name: Gasoline

Hazard Class: 3


Packing Group: II

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant Naphtha (petroleum), full-range alkylate

Special Provision: 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.




14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each



14.5 IMDG Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

ID No.: UN 1203

Shipping Name: GASOLINE LTD.QTY.

Hazard Class: 3

Packing Group: II

Flash Point: (-35.5° C c.c.)

EmS Number: F-E, S-E

NOTE: Because the MARINE POLLUTANT Naphtha (petroleum), full-range alkylate in the inner packaging of the combination packaging is a net quantity of 5 L or less. The MARINE POLLUTANT marking is not required.

Special Provision: 243 Gasoline, motor spirit, and petrol, for use in internal combustion engines (e.g., in automobiles, stationary engines, and other engines) shall be assigned to entry regardless of variations in volatility.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

Toxic Release Inventory (TRI): This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
108-88-3	Toluene	20%
110-54-3	n-Hexane	At demines% limits
100-41-4	Ethylbenzene	At demines% limits

This information must be included in all SDSs copied and distributed for this material.

CERCLA Hazardous Substances and corresponding RQs: Toluene 1000lbs. n-Hexane 5000 lbs. Ethylbenzene 1000 lbs.

SARA Community Right-to-Know Program: All components of this blend.

Clean Water Act: None.

OSHA: All ingredients are regulated by 29 CFR 1910.1200.

State Regulations

State Regulations

California prop. 65



WARNING This product can expose you to chemicals including Ethylbenzene CAS # 100-41-4 and Toluene CAS # 188-88-3, and n-Hexane CAS # 110-54-3, which are known to the State of California to cause cancer and birth defects, or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and assume the risk of their use.

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

16.2 References: CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC in-country emergency dial numbers:

County	Greeting Language	City	Local number	Toll-Free number
Argentina	Latin American Spanish	Buenos Aires	54-1159839431	
Brazil	Portuguese	Rio De Janeiro	55-2139581449	
Brazil	Portuguese	Sao Paulo	55-1143491359	
Brazil - Toll-Free	Portuguese		0800 892 0479	0800 892 0479
Cayman Islands	English	Local (National)	345-749-8392	
Chile	Latin American Spanish	Santiago	56 2 2581 4934	
Colombia	Latin American Spanish		01800-710-2151	01800-710-2151
Costa Rica	Latin American Spanish		506-40003869	
Dominican Republic	Latin American Spanish	Santo Domingo	1 (829) 956-7588	
El Salvador	Latin American Spanish	San Salvador	503 2136 7633	
Grenada	English	St George	1 (473) 230-0165	
Guinea	French		224 660 71 03 00	
Mexico	Latin American Spanish		01-800-681-9531	01-800-681-9531
Panama	Latin American Spanish		507-8322475	
Peru	Latin American Spanish	Lima	51-17071295	
Trinidad and Tobago	English	National Number	1-868-224-5716	

India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141
-------	-------------------------	--	------------------	------------------

SEF 2 Cycle 40:1

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Indonesia	Indonesian		001-803-017-9114	001-803-017-9114
Israel	Hebrew	Tel Aviv	972-37630639	
Japan	Japanese	Tokyo	81-345209637	
Malaysia	Malay	Kuala Lumpur	60-392125794	1-800-815-308
Philippines	Tagalog	Manila	+63 2 8395 3308 and 1-800-1-116-1020	1-800-1-116-1020
Russia	Russian		8-800-100-6346	8-800-100-6346
Saudi Arabia	Arabic and English		966-8111095861	
Singapore	English and Mandarin		65-31581349	800-101-2201
South Korea	Korean			003-0813-2549 and 080-822-1374
Taiwan	Mandarin	Taipei	886-2-7741-4207	00801-14-8954
Thailand	Thai		001-800-13-203- 9987	001-800-13-203- 9987
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141

Australia	English	Sydney	61-290372994	
New Zealand	English	Auckland	64-98010034	

South Africa	English	None	0-800—983-611	0-800—983-611
--------------	---------	------	---------------	---------------

16.4 SDS Preparation Date 01/23/2016

SDS Previous Issue Date: None

SDS Revision Date: 01/22/2019 Sections 2,3,8,11,12,14,15,16

SDS Revision Date: 12/24/2021 Sections 2,3,8,9,11,12,13,14,15,16

Prepared by SJC Compliance Education, Inc
1319 Varese Dr.
Pearland, TX. 77581
steve@sjcedu.org

END OF SAFETY DATA SHEET