



Metal Building Siding and Roof Finish



Product Description

Valspar Metal Building Roof & Siding Finish restores old, weathered metal siding and roofs to a beautiful appearance and protects against rust. This premium water reducible acrylic formula dries quickly to a long lasting, durable, fade and chalk resistant semi-gloss finish. Cleans up easily with soap and water. Ideal for sloped metal roofs and vertical metal siding on sheds, outbuildings, barns and pole buildings. Use as is for a "Direct to Metal" (DTM) product or use with Valspar Rusty Metal Primer over corroded metals.

Features

- Resists rust & corrosion
- Excellent adhesion
- Fade and chalk resistant
- Water clean-up
- 100% acrylic semi-gloss for maximum durability
- Dries quickly

Recommended Uses

- Metal roof surfaces
- Vertical metal siding
- Steel and galvanized raised ridge surfaces
- Wood siding surfaces

Colors and Part Numbers

	Part Number
Brite White	4260 (Gallon & 5 Gallon)
Classic Green	4261 (Gallon & 5 Gallon)
Classic Red	4262 (Gallon & 5 Gallon)
Classic Brown	4263 (Gallon Only)
Light Stone	4264 (Gallon & 5 Gallon)
Ash Gray	4265 (Gallon & 5 Gallon)

Typical Properties (27-4260 Series)

Vehicle Type: Acrylic Resin

Sheen: 25–40 Units @ 60° angle

Solids by Volume: 30%

Solids by Weight: 43%

Weight per Gallon: 10.1 lbs./gal.

VOC: Less than 150 g/L

Viscosity: 94–100 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 30-60 minute(s)

Recoat: 24 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 7 day(s)

Surface Coverage:

300 sq. ft./gal.

At: 4.0 mil Wet, 1.2 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallons – 4 per carton
5 Gallon Pails

Surface Preparation

Read the Lead Warning in Cautions section. **General:** Paint must be applied to clean, sound surfaces. Inspect roof and siding seams for leaks and make repairs with appropriate paintable patching material. Clean the surface thoroughly, removing all dirt, dust, chalk, rust, grease, wax and mildew and allow to dry. For large areas, cleaning is most effective with a power washer. Brush off loose rust and spot prime with Valspar Rusty Metal Primer. Prime bare wood surfaces with a high quality oil or latex exterior primer. **Previously Painted Surfaces:** Scrape off loose and peeling paint, sand, then spot prime. Thoroughly remove all chalk by vigorous washing with a non-residue (TSP) cleaner, then rinse surface well. Surfaces with many layers of old, brittle paint may require a complete removal of all the previous coats prior to repainting. This is best done with a power washer.

Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Make sure surface is clean, dry and sound. Prepare surface according to “Surface Preparation” instructions. Use a paint paddle to stir paint up from the bottom of the can. To ensure uniform color, intermix all containers of the same color. Do not apply to wet surfaces or in direct, hot sun, when rain is imminent or late in the day when dew may affect the paint cure. Apply paint with an airless sprayer. Work quickly as paint dries fast on roofing surfaces. Premium quality polyester brushes and rollers may be used for small or difficult to spray areas. Apply two coats to all surfaces, allowing to dry overnight between coats. When applying to raised ridge or other directional surfaces, spray the second coat from the opposite side of the first to ensure complete coverage. Thin only for spray application with up to 8 oz. water per gallon of paint. Clean up with warm, soapy water.

Cautions (27-4260 Series)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean up. Follow respirator manufacturer’s direction for respirator use. **AVOID CONTACT WITH EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the state of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Contains crystalline silica which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 150 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

1191 Wheeling Rd, Wheeling, IL 60090 800-845-9061
www.valspar.com

12/09

PDS 27-4260