



Porch and Floor Oil Gloss Enamel



Product Description

Valspar Interior/Exterior Oil Porch & Floor Enamel is a high gloss coating that resists scuffing and abrasion. Super tough, polyurethane modified formula is ideal for use on floors, trim or doors. Indoors or out, the weather resistant formula gives years of long lasting beauty and protection.

Features

- Use on wood, concrete, floors, primed metal, steps, railings and porches
- Weather resistant
- For interior and exterior use

Recommended Uses

- Concrete
- Wood
- Porches
- Basement floors
- Stairs
- Breezeways
- Primed metal
- Indoor and outdoor floors

Colors and Part Numbers

	Part Number
White	1000 (Quart & Gallon)
Clear Base	1005 (Quart & Gallon)
Dark Brown	1015 (Gallon Only)
Dark Green	1021 (Gallon Only)
Light Gray	1033 (Gallon Only)
Dark Gray	1034 (Gallon Only)
Tile Red	1089 (Gallon Only)

Typical Properties (27-1000 Series)

Vehicle Type: Urethane-Alkyd Resin

Sheen: 80+ Units @ 60° angle

Solids by Volume: 51%

Solids by Weight: 67%

Weight per Gallon: 9.5 lbs./gal.

VOC: Less than 380 g/L

Viscosity: 73–85 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 8 hour(s)

Recoat: 24 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 2 day(s)

Surface Coverage:

500 sq. ft./gal.

At: 4.0 mil Wet, 2.0 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quarts – 4 per carton
Gallons – 2 per carton

Surface Preparation

Read the Lead Warning in Cautions section. The surface must be clean, dry and free of all loose, peeling or cracking paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute), scouring powder, wax remover or diluted ammonia. Wire brush or scrape chipped or peeling paint. Rough or repaired wood surfaces should be sanded smooth. Prime bare, new wood with an enamel undercoater. All rust must be removed from metal prior to painting. Prime all iron and steel with a rust inhibiting metal primer. Remove gloss from previously painted surfaces with gloss remover or by sanding. For new concrete, allow it to cure at least 60 days before painting. Then acid etch with muriatic acid (see etching instructions and read all cautions on etching packages). Unpainted or smoothly worn concrete should also be etched. For newly etched concrete surfaces or badly worn spots on wood, apply 2 coats of Oil Floor Enamel – a thin first coat and the second coat at the normal rate. **Etching Instructions:** New, unpainted or smooth worn concrete must be etched with a muriatic acid solution for proper penetration and adhesion. Before preparing acid solution, READ ALL CAUTIONS AND WARNINGS on acid packaging. Wear appropriate protective clothing, goggles and rubber gloves when handling acid. Mix 1 quart of muriatic acid with 1 gallon of water. Flush floor with acid solution. DO NOT BREATHE VAPORS and make certain there is good ventilation. After 30 minutes, or when acid solution stops bubbling, rinse with water while scrubbing floor with stiff broom to remove all powdery residue. Allow to dry.

Application and Cleanup

Stir paint thoroughly before and during use. If using more than one can of the same color, intermix to maintain color consistency. To increase traction on stairs and other areas where accidental slips may occur, add one cup of clean, dry sand when applying the finishing coat. Stir frequently during application to avoid settling. Use a premium quality roller, polyester brush, pad applicator or airless sprayer (do not use sand if spraying!). Apply liberally over the full length of the surface to avoid lap marks. If applied by airless sprayer, back-roll to ensure proper penetration. Finish with long even strokes in one direction. **Care and Washing Instructions:** Do not allow water to pond or puddle on newly painted surfaces. Always use a mild detergent and soft sponge when cleaning the surface. Stubborn stains may require the use of an ammoniated household cleaner. Do not use cleaners containing abrasives or abrasive scouring pads to clean the surface. Do not thin. Clean tools with mineral spirits.

Cautions (27-1000 Series)

WARNING: CONTAINS PETROLEUM DISTILLATE. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. USE ONLY WITH ADEQUATE VENTILATION. Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating or inhaling the vapors may be harmful or fatal.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 380 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.