

GENERAL DESCRIPTION

Valspar® Etching Stain is a decorative concrete finish that gives a marble-like look to interior and exterior concrete. Valspar Etching Stain transforms concrete surfaces to the warm earth tones historically associated with rich, old world floor design. Must be top coated with Valspar® Etching Stain Sealer.

PRODUCT FEATURES

- Marbled Effect – Enhances concrete patios, driveways and living spaces
- Permanent color
- Lasting Color – Resists peeling and fading
- Saves Time – Etches and stains concrete in one easy step

RECOMMENDED USES

- Basements
- Patios
- Walkways
- Porches
- Driveways

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Gallon – 4 per carton

COMPOSITION

Base and Fill Levels

(oz./gal.)

| | |
|-------------|-----|
| Tan | 128 |
| Coffee | 128 |
| Cayenne Red | 128 |

APPLICATION AND CLEANUP

IMPORTANT! SEE CAUTIONS ON LABEL AND TDS. Carefully read and follow all label instructions before use. Be Safe! Use proper protective equipment. Wear rubber boots, rubber gloves and eye protection at all times when using this product. Do not place stain in metal containers. Grease and oil spots should be treated with a good-quality degreaser. Dampen the surface with water; remove any puddles or standing water. Apply with a low-pressure sprayer, mop or brush. For greater color depth or variations, apply multiple colors or coats while stain is still wet. Allow stain to stand 4 hours or until completely dry. Remove residue by washing with a solution of 4 oz. of baking soda for every 1 gallon of water. Scrub thoroughly with a stiff bristle brush. Remove wash water with wet-vacuum or mop. Allow surface to completely dry and top coat with Valspar® Etching Stain Sealer. Clean tools and materials with a solution of 1 pound of baking soda to 2 gallons of water. Rinse all tools, material and personal protection with water before storing.

PRODUCT SPECIFICATIONS

Flashpoint: N/A

VOC (g/L): Less than 100 g/L

Volume Solids: 6.91 ±2%

Weight Solids: 17.38 ±2%

Weight Per Gallon: 9.39± .2 lbs./gal.

Practical Coverage: Covers approximately 300–400 sq. ft. per gallon (27–37 m² per 3.78 L) depending on surface porosity. Do not thin.

Dry Time @ 77 °F and 50% Relative Humidity

Dries to the touch in 4 hours. For best results wait 24 hours before washing off etching residue.

Application Temperature: 50–90 °F (10–32 °C)

REGULATORY COMPLIANCE

Current as of: 1/25/2017

| | |
|---------------|-----|
| SCAQMD | Yes |
| CARB 2000 SCM | Yes |
| CARB 2007 SCM | Yes |
| OTC/LADCO | Yes |
| US National | Yes |

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



Valspar® Etching Stain

No. 82070 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Concrete suitable for staining must be free of dirt, oil, grease, concrete-curing compounds, sealers, paint and any material that interferes with the ability for water to soak into the surface. Test for water absorption. Concrete will not accept stain if water beads or does not soak into the surface.

Newly poured concrete:

Must be at least 28 days old and fully cured. Protect all areas not to be stained with water-resistant masking tape. Protect plants and landscaping from direct runoff. A general cleaning of the surface should be done with TSP (or substitute) and water, scrubbing with a stiff deck brush. Do not use muriatic acid or acid cleaners.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

CAUTIONS

DANGER! MAY BE HARMFUL OR FATAL IF INHALED. CAUSES EYE AND SKIN BURNS. MAY BE FATAL IF SWALLOWED.

DANGER! CORROSIVE. CONTAINS UREA HYDROCHLORIDE AND HYDROGEN CHLORIDE. KEEP OUT OF THE REACH OF CHILDREN. Causes eye burns. Risk of serious damage to eyes. Causes skin burns. Causes digestive tract burns. May be fatal if swallowed. Corrosive to respiratory tract. Use only with adequate ventilation. Do not breathe spray or mist. If applied indoors, wear appropriate (NIOSH approved), properly fitted respirator effective for chlorine gas during application. Avoid contact with the eyes, skin and clothing. Protective equipment MUST be worn during application, including acid resistant rubber gloves, goggles, boots, dust mask and other appropriate clothing. Wash thoroughly after handling. Wash clothing, shoes and protective equipment after use. Do not reuse shoes that may have absorbed stain. Close container after each use. DO NOT TAKE INTERNALLY. Do not mix with bleach, other chemicals, detergents or cleaners. First Aid: Eye And Skin Contact: Flush thoroughly with water for at least 15 minutes. Remove contaminated clothing. If irritation persists, get medical attention.* If Swallowed: DO NOT INDUCE VOMITING. Give large quantities of water or milk. Get medical attention immediately.* If Inhaled: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.*

COR SPL 1.3

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631
877.825.7727
valsparpaint.com
Revised: 1/25/17
Version: 82070B