

GENERAL DESCRIPTION

Valspar Color Flakes enhance the appearance of the surface and mask any slight imperfections in the concrete on your newly painted surface. The color combinations are carefully chosen to complement paint colors for a polished and eye-catching look.

PRODUCT FEATURES

- Color Flake Shaker easily distributes flakes
- Creates a professional, custom look

RECOMMENDED USES

- Garage floors
- Interior concrete floors

STORAGE AND DISPOSAL

Unused flakes and their container may be thrown away. Do not reuse container.

COMPOSITION

Package
Fill

Color flakes 10 oz

PRODUCT SPECIFICATIONS

Flashpoint: NA

VOC (g/L): NA

Practical Coverage:

250 sq. ft. in a standard pattern

125 sq. ft. in a heavy pattern.

**Dry Time @ 77 °F and 50% Relative Humidity
To Touch:** NA

APPLICATION

Specially designed for Valspar® floor coatings

It is important to spread the Color Flakes evenly over the entire surface. Apply only to wet coating. To ensure you can reach each area with the flake shaker, paint no more than a 2' x 6' size area, then stop and apply Color Flakes. Shake bottle lightly and allow flakes to fall naturally. Repeat these steps until you have finished the entire floor.

LIMITED WARRANTY

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

CAUTIONS

KEEP OUT OF THE REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

1191 Wheeling Road, Wheeling, IL 60090
888.313.5569
www.valsparpaint.com
Revised: Sept 2012