

### GENERAL DESCRIPTION

Valspar Etching Stain Sealer seals and enhances the color and design of concrete stained with Valspar Etching Stains. This sealer is formulated to protect your etching stain surfaces against sun, weather and household chemicals. Resists gasoline, oil and de-icing salts.

### PRODUCT FEATURES

- Enhances etching stain color
- Protects from sun, water and household-chemical damage
- Apply one coat for a hand rubbed sheen, multiple coats for a high gloss finish
- Soap and water clean up

### RECOMMENDED USES

- Use over Valspar Etching Stains

### PACKAGING

**Packaging:**  
Gallon – 4 per carton

### THINNING

Do not thin.

### CLEANUP

Clean up with warm, soapy water.

### STORAGE AND DISPOSAL

Do not freeze! Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

### COMPOSITION

|        | Package Fill | Tint Fill | Tint Strength |
|--------|--------------|-----------|---------------|
|        | (oz./gal.)   |           |               |
| Gallon | 128          |           |               |

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic Emulsion

**Viscosity:** 12 – 16 sec #4 Ford cup

**Gloss:** 50 - 60 Units @ 60° angle

**Flashpoint:** 205 F

**VOC (g/L):** Less than 100 g/L

**Volume Solids:** 25%

**Weight Solids:** 27%

**Weight Per Gallon:** 8.4 lbs./gal.

**Practical Coverage:**

200 – 400 sq. ft. /gal. depending on surface porosity

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 - 2 hour

**Recoat:** 2 hours

**Full Cure:** Dries hard overnight

**Application Temperature –** 50-90 °F

### SURFACE PREPARATION

Surface preparation: All surfaces must be clean, dry and free of all loose, peeling paint or contaminants.

**For topcoating Valspar Etching Stain:**

Remove all residue and clean per Etching Stain label instructions. Allow the floor to dry completely, at least 24 hours.

### APPLICATION

Apply with a roller, brush or low-pressure garden sprayer. If the first coat sinks in rapidly, apply a second coat after 2 hours. Allow to soak for 10–15 minutes — or until pores are completely sealed. Wipe off excess from the surface before the sealer dries. Clean up with warm, soapy water. Do not apply to wet or damp surfaces, or areas prone to ponding water.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

### CAUTIONS

CAUTION Contains Tributyl Citrate and Dipropylene Glycol Butoxy Ether..

**KEEP OUT OF THE REACH OF CHILDREN.**

May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.\* \*Call poison control center, hospital emergency room or physician immediately.

CL1.3

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than 100 g/L VOC**

Revised: Sept 2012