

GENERAL DESCRIPTION

Valspar Natural Look Waterproofer forms a long lasting, waterproofing seal on concrete, brick, masonry, aggregate, natural stone and pavers. This sealer is formulated to protect against the sun's UV rays, water, gasoline and de-icing salts. This protective sealer allows the natural look of the surface to come through.

PRODUCT FEATURES

- Waterproofs
- Protects from sun, water and household-chemical damage
- Soap and water clean up
- Does not change natural appearance

RECOMMENDED USES

- Concrete
- Brick, Slate, Flagstone and Pavers
- Exterior Masonry and Mortar
- **Do not use below grade**

PACKAGING

Packaging:

Gallon – 4 per carton
5 gallon pail

THINNING

Do not thin.

CLEANUP

Clean up with warm, soapy water.

STORAGE AND DISPOSAL

Do not freeze! Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

COMPOSITION

	Package Fill	Tint Fill (oz./gal.)	Tint Strength
Gallon	128		
5 gallon	640		

PRODUCT SPECIFICATIONS

Vehicle Type: Silicone Emulsion

Recommended Film Thickness:

NA Does not form a surface film

Viscosity: 8 – 12 sec #4 Ford cup

Gloss: Flat

Flashpoint: NA

VOC (g/L): Less than 100 g/L

Volume Solids: 6 %

Weight Solids: 6 %

Weight Per Gallon: 8.3 lbs. /gal.

Practical Coverage:

75 - 150 sq. ft. /gal. depending on surface porosity.

Dry Time @ 77 °F and 50% Relative Humidity

To The Touch: 1 hour

Application Temperature – 50-90 °F

SURFACE PREPARATION

General: All surfaces must be clean, dry and free of all loose, peeling paint or contaminants.

Bare Concrete: Allow 60 days minimum for new concrete to cure before sealing.

Previously Painted/Stained Concrete: Clean with an all-purpose cleaner (TSP or substitute). Previously sealed surfaces must be porous and able to accept additional sealer. **Test surface porosity before sealing: Avoid using this product on nonporous, sealed surfaces.** To test, place a few drops of water on the surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

APPLICATION

Use a roller or low-pressure garden type sprayer. While the first coat is still wet, apply a second coat to maximize protection. Allow 5-10 minutes for final penetration, then use a clean, dry cloth to wipe off all excess which did not soak into the surface. **Do not pond or puddle this product.**

Periodic maintenance: Reapply when water begins to penetrate the surface again.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

CAUTIONS

CAUTION

KEEP OUT OF THE REACH OF CHILDREN.

May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.*
*Call poison control center, hospital emergency room or physician immediately.

CL1.3

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 100 g/L VOC

1191 Wheeling Road, Wheeling, IL 60090
888.313.5569
www.valsparpaint.com
Revised: Sept 2012