



# Valspar Door & Trim Enamel Classic Enamel Oil/Alkyd

## No. 83061 Series

### GENERAL DESCRIPTION

Valspar® Door And Trim Enamel Classic Enamel is a traditional long oil alkyd formula developed specifically for door and trim application.

### PRODUCT FEATURES

- Superior flow and leveling – dries to a smooth, glass like finish
- Excellent durability
- Excellent block resistance minimizing sticking of painted doors and windows.
- Specially formulated to resist yellowing as coating ages
- Easy spray, brush and roll application

### RECOMMENDED USES

- Interior primed or previously painted wood trim, cabinets and doors
- Ideal for giving custom wood work a rich, elegant look
- Can be used on interior metal doors
- Millwork in residential new construction
- Can be used on a variety of other surfaces

### REGULATORY COMPLIANCE

Current as of: 12/23/2015  
US National

### PRODUCTS AVAILABLE

#### SEMI-GLOSS

Pastel Base (83061)

Clear Base (83064)

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Alkyd

**Flashpoint:** 100°F

**VOC:** <380g/L or <3.16 lbs./gal.

**Volume Solids:** 52%±2%

**Weight Solids:** 71%±2%

**Weight Per Gallon:** 10.96 lbs./gal. ± .2 lbs.

**60° Gloss (Initial):** 45-55 Units

**60° Gloss (After 30 Day Cure):** 30-40 Units

*Above specifications are rounded and based on Semi-Gloss Pastel Base (Specifications will vary by color and base.)*

**Practical Coverage:** Covers up to 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.

**Drying Time\*\*:**

77 °F (25°C) and 50% RH

Surface Dry: 6-8 Hours

Recoat: 24 hours

**Application Temperature:** 50 – 90 °F (10 – 32 °C)

*Dry time will vary by film thickness, temperature and humidity*

**Tinting (Universal Colorants)**

**Pastel Base:** Up to 2 Ounces/gallon

**Clear Base:** Up to 12 Ounces/gallon

### APPLICATION

**Apply at 3.5 mil WFT; 1.8 mil DFT Minimum**

**Airless:**

Fluid pressure: 2000psi

Filter Size: 60 mesh

Tip size: .011-.015"

**Brush:** Natural Bristle

**Roller Cover:** 3/8" or higher Soft Woven

### SYSTEM RECOMMENDATIONS

**Drywall/Plaster/Wood**

1 Coat Valspar Interior Latex Primer

1-2 Coats Door & Trim Latex Plus

**Bare Steel/Galvanized Metal**

1 Coat Valspar Bonding Primer

1-2 Coats Door & Trim Latex Plus

**Masonry**

1 Coat Valspar Alkali Resistant Primer

1-2 Coats Door & Trim Latex Plus

**Previously Painted Surfaces**

1-2 Coats Door & Trim Latex Plus



# Valspar Door & Trim Enamel Classic Enamel Oil/Alkyd

## No. 83061 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Remove rust, oil, grease, mildew salt and dirt from surface. Remove all dust or other loose material off the surface. Verify area is dry and free of all dust and loose material.

**Previously Painted Surfaces:** Follow *General* prep section. Glossy surfaces should be dulled. If substrate is showing prime with appropriate Valspar primer.

**Steel:** Solvent clean all surfaces per SSPC-SP1, SSPC-SP 2, Hand Tool Cleaning is the MINIMUM prep required. SSPC-SP 6/NACE NO. 3, Commercial Blast Cleaning is PREFERRED.

**Galvanized:** All new galvanized metal must be allowed to weather for a minimum of six months before coating. SSPC-SP 1 Solvent Cleaning is the MINIMUM prep required. SSPC-SP 16, Brush-off Blast Cleaning of Non-Ferrous Metals is PREFERRED.

**Concrete/Masonry:** All new concrete surfaces must be allowed to weather a minimum of 30 days prior to coating. Make sure all release agents are removed from surface prior to coating. SSPC-SP 13/NACE No. 6, Surface Preparation of Concrete is required

**Aluminum:** SSPC-1 surface prep recommended.

**Drywall:** Fill cracks, pits and voids with patching compound, let cure and sand smooth. Remove all sanding dust. Spot prime new or bare surfaces before applying the finish coat.

**Wood:** Surface must be in sound condition and free from all dirt, oils and other contaminants. Solvent cleaner or other detergent might be required. Remove any loose wood by sanding as required.

### CLEAN UP

Clean spills and equipment with mineral spirits.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

#### **Packaging:**

- Gallon (83061) – 4 per carton
- Gallon (83064) – 2 per carton
- 5 gallon pails

### STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with an HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CAUTION

WARNING! Contains Petroleum Distillates and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** NOTICE: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Do not induce vomiting. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately. For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product. UCS 6.1

### **EMERGENCY MEDICAL TELEPHONE:**

**1-888-345-5732**

8725 W. Higgins Rd.  
Chicago, IL 60631  
877.825.7727  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 12/23/15  
Version: 83061A