SAFETY DATA SHEET

81021

Section 1. Identification

| Product name | : Garage Floor Coating Kit Tan |
|----------------------------------|---|
| Product code | : 81021 |
| Other means of identification | : Not available. |
| Product type | : Liquid. |
| Relevant identified use | es of the substance or mixture and uses advised against |
| | |

Paint or paint related material.

| Manufacturer | : Valspar 101 W. Prospect Avenue Cleveland, OH 44115 |
|--|--|
| Emergency telephone number of the company | : (800) 424-9300 |
| Product Information Telephone Number | : Not available. |
| Regulatory Information Telephone Number | : (216) 566-2902 |
| Transportation Emergency Telephone Number | : (800) 424-9300 |

Section 2. Hazards identification

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|---|
| Classification of the substance or mixture | SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2 |
| | Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 34.3% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 34.3% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 39. 6% |
| GHS label elements | |
| Hazard pictograms | |
| Signal word | : Danger |
| Hazard statements | : Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Suspected of causing cancer. |
| Precautionary statements | |
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |

| Date of issu | e/Date of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version : 4.02 | 1/13 |
|--------------|-------------------------|--------------|------------------------|--------------|----------------|------|
| 81021 | Garage Floor Coa Tan | ating Kit | | | SHW-85-NA-GHS- | US |

Section 2. Hazards identification

| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. |
|-------------------------------------|---|
| Response | : IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. |
| Storage | : Store locked up. |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. |
| | This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|---|-------------|------------|
| Titanium Dioxide | ≤10 | 13463-67-7 |
| Phenolic Resin | ≤6.3 | - |
| Diethylaminopropylamine | ≤10 | 104-78-9 |
| Titanium Dioxide, Rutile | ≤3 | 1317-80-2 |
| Alkyl Phenolic Ether | ≤1.2 | - |
| Alkoxylated Alcohol | ≤1.2 | - |
| Isotridecylalcohol, ethoxylated, sulfated | ≤1.2 | - |
| 4-Nonylphenol | ≤0.3 | 84852-15-3 |
| Modified Aliphatic Amine | ≤0.3 | - |
| Isophorone Diamine | ≤0.3 | 2855-13-2 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| Description of necessary first aid measures | | | | | |
|---|---|--|--|--|--|
| Eye contact | : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. | | | | |
| Inhalation | : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | | | | |
| Skin contact | : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. | | | | |
| Ingestion | : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. | | | | |

Most important symptoms/effects, acute and delayed

| Causes serious eye damage. |
|--|
| No known significant effects or critical hazards. |
| Causes severe burns. May cause an allergic skin reaction. |
| No known significant effects or critical hazards. |
| <u>ns</u> |
| Adverse symptoms may include the following: pain watering redness |
| Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations |
| |

| Date of issue/Date | of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version | : 4.02 | 3/13 |
|--------------------|-------------------------------|--------------|------------------------|--------------|----------|-----------|------|
| 81021 | Garage Floor Coating K Tan | Kit | | | SHW-85-I | NA-GHS-US | |

Section 4. First aid measures

| Ingestion | : Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations |
|----------------------------|---|
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| | - |
|--|---|
| Extinguishing media | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protect | ive equipment and emergency procedures |
|--------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |

| Version : 4.02 | 4/13 |
|------------------|------------------|
| SHW-85-NA-GHS-US | |
| | SHW-85-NA-GHS-US |

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | Exposure limits |
|---|--|
| Titanium Dioxide | ACGIH TLV (United States, 3/2017). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 6/2016). TWA: 15 mg/m ³ 8 hours. Form: Total dust |
| Phenolic Resin Diethylaminopropylamine Titanium Dioxide, Rutile Alkyl Phenolic Ether Alkoxylated Alcohol Isotridecylalcohol, ethoxylated, sulfated | None. None. None. None. None. None. |
| Date of issue/Date of revision : 10/30/2018 Date of prev 81021 Garage Floor Coating Kit Tan | ious issue : 10/17/2018 Version : 4.02 5/13 SHW-85-NA-GHS-US |

Section 8. Exposure controls/personal protection

4-Nonylphenol Modified Aliphatic Amine 3-aminomethyl-3,5,5-trimethylcyclohexylamine None. None. None.

Occupational exposure limits (Canada)

| Ingredient name | Exposure limits |
|---------------------------------------|-----------------|
| None. | |
| Occupational exposure limits (Mexico) | |

| Ingredient name | Exposure limits |
|-----------------|-----------------|
| None. | |

| Appropriate engineering controls | If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
|----------------------------------|---|
| Environmental exposure controls | ¹ This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | Emissions from ventilation or work process equipment should be checked to ensure |

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
|------------------------|--|
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

| Date of issue/Date | e of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version : 4.02 | 6/13 |
|--------------------|-----------------------------|--------------|------------------------|--------------|-----------------|------|
| 81021 | Garage Floor Coating Tan | Kit | | | SHW-85-NA-GHS-U | S |

Section 9. Physical and chemical properties

| : Liquid. |
|---|
| : Not available. |
| : Not available. |
| : Not available. |
| : 9 |
| : Not available. |
| : 100°C (212°F) |
| : Closed cup: 94°C (201.2°F) [Pensky-Martens Closed Cup] |
| : 0.09 (butyl acetate = 1) |
| : Not available. |
| : Not available. |
| : 2.3 kPa (17.5 mm Hg) [at 20°C] |
| : 1 [Air = 1] |
| : 1.23 |
| : Not available. |
| : Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt) |
| : Not applicable. |
| |
| : 4.289 kJ/g |
| |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

| Acute toxicity | |
|-------------------------|--------|
| Product/ingredient name | Result |
| | |

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|------------------------|---------|-------------------------|----------|
| Diethylaminopropylamine 4-Nonylphenol | LD50 Oral LD50 Oral | | 550 mg/kg 1300 mg/kg | - |

Irritation/Corrosion

| Date of issue/Date | of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version : 4.02 | 7/13 |
|--------------------|-------------------------------|---|------------------------|--------------|------------------|------|
| 81021 | Garage Floor Coating I Tan | <it< td=""><td></td><td></td><td>SHW-85-NA-GHS-US</td><td></td></it<> | | | SHW-85-NA-GHS-US | |

| Section 11. Toxicological information | | | | | |
|---------------------------------------|------------------------|---------|-------|--|-------------|
| Product/ingredient name | Result | Species | Score | Exposure | Observation |
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |
| 4-Nonylphenol | Eyes - Severe irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 500 milligrams | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|--|------|----------|-----|
| Titanium Dioxide Titanium Dioxide, Rutile | - | 2B 2B | |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

| Eye contact | : | Causes serious eye damage. | | |
|--------------|---|---|--|--|
| Inhalation | : | No known significant effects or critical hazards. | | |
| Skin contact | : | Causes severe burns. May cause an allergic skin reaction. | | |
| Ingestion | ÷ | No known significant effects or critical hazards. | | |

| Symptoms related to the pl | hysical, chemical and toxicological characteristics |
|----------------------------|---|
| Eye contact | : Adverse symptoms may include the following: pain watering redness |
| Inhalation | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |

| Date of issue/L | Date of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version : 4.02 | 8/13 |
|--------------------------------|------------------|--------------|------------------------|--------------|------------------|------|
| 81021 Garage Floor Coating Kit | | | | | SHW-85-NA-GHS-US | |
| | Tan | | | | | |

| Skin contact | | Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations |
|--------------------------------|------|--|
| Ingestion | : | Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations |
| Delayed and immediate eff | fect | s and also chronic effects from short and long term exposure |
| Short term exposure | | |
| Potential immediate effects | : | Not available. |
| Potential delayed effects | 1 | Not available. |
| Long term exposure | | |
| Potential immediate effects | : | Not available. |
| Potential delayed effects | : | Not available. |
| Potential chronic health ef | fec | <u>ts</u> |
| Not available. | | |
| General | : | Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : | Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : | No known significant effects or critical hazards. |
| Teratogenicity | : | Suspected of damaging the unborn child. |
| Developmental effects | : | No known significant effects or critical hazards. |
| Fertility effects | : | Suspected of damaging fertility. |
| | | |

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|----------------|-------------------------------|
| Oral Dermal | 6875.7 mg/kg 13751.5 mg/kg |
| Dermal | 13751.5 mg/kg |

Section 12. Ecological information

| <u>Toxicity</u> | | | | |
|---------------------------------------|--|--|--|--|
| Product/ingredient name | Result | Species | Exposure | |
| Titanium Dioxide 4-Nonylphenol | Acute LC50 >1000000 μg/l Marine water Acute EC50 0.03 mg/l Marine water Acute EC50 0.027 mg/l Marine water Acute EC50 137 μg/l Marine water | Fish - Fundulus heteroclitus Algae - Skeletonema costatum Algae - Skeletonema costatum Crustaceans - Eohaustorius | 96 hours 72 hours 96 hours 48 hours | |
| | Acute LC50 17 µg/l Marine water | estuarius - Adult Fish - Pleuronectes americanus - Larvae | 96 hours | |
| | Chronic EC10 0.012 mg/l Marine water Chronic NOEC 5 µg/l Fresh water | Algae - Skeletonema costatum Crustaceans - Gammarus fossarum - Adult | 96 hours 21 days | |
| | Chronic NOEC 7.4 µg/l Fresh water | Fish - Pimephales promelas - Embryo | 33 days | |
| Date of issue/Date of revision | : 10/30/2018 Date of previous issue | :10/17/2018 Version :4 | .02 9/13 | |
| 81021 Garage Floor Coating Kit SHW-85 | | | | |

| Section 12. Ecological information | | | | | | | |
|--|----------------------------------|-------------------------|----------|--|--|--|--|
| 3-aminomethyl-3,5, 5-trimethylcyclohexylamine | Acute EC50 17.4 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours | | | | |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| 4-Nonylphenol | - | 740 | high |

Mobility in soil

| Soil/water partition | : Not available. |
|----------------------|------------------|
| coefficient (Koc) | |

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Tan

| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|---|--|-----------------------|--------------------------|---|---|
| UN number | Not regulated. | Not regulated. | Not regulated. | UN3082 | UN3082 |
| UN proper shipping name | - | - | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-Nonylphenol) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-Nonylphenol). Marine pollutant (4-Nonylphenol) |
| Transport hazard class(es) | - | - | - | 9 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1) | 9 |
| Date of issue/Date of rev 81021 Gara | rision : 10/30/2 ge Floor Coating Kit | 018 Date of previous | issue : 10/17/20 | | |

| Packing group Environmental hazards Additional information | No. - | No. - | No. | Yes. | Yes. | |
|--|----------------|--|--|--|---|--|
| | - | - | - | | | |
| | | | | This product is not regulated as good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the genera provisions of 5.0 2.4.1, 5.0.2.6.1. and 5.0.2.8. | dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1 0. 1, 4.1.1.2 and 4.1. | |
| Special precaution | ns for user | consider container s mode of transport (s suitably for that mod prior to shipment, an responsibility of the unloading dangerou | sizes. The presence sea, air, etc.), does de of transport. All p nd compliance with person offering the s goods must be tra | rovided for informationa of a shipping description not indicate that the pro- packaging must be revie the applicable regulation product for transport. P ained on all of the risks of f emergency situations. | on for a particular duct is packaged wed for suitability ns is the sole eople loading and deriving from the | |
| Fransport in bulk a to Annex II of MAR the IBC Code | | : Not available. | | | | |
| | | Proper shipping nar | me : Not ava | ailable. | | |
| | | Ship type : Not available. | | | | |
| | | Pollution category | : Not ava | ailable. | | |
| Section 15. | Regula | tory information | on | | | |
| J.S. Federal regula | tions | : TSCA 5(a)2 propose | • | | nethylisothiazolinone | |
| | | TSCA 5(a)2 final significant new use rules: 4-Nonylphenol This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. | | | | |
| <u>SARA 313</u> | | | | | | |
| SARA 313 (40 CFF | R 372.45) s | upplier notification can be | e found on the Envi | ronmental Data Sheet. | | |
| California Prop. WARNING: Thi reproductive har | s product c | ontains chemicals knowr | to the State of Cal | ifornia to cause cancer a | and birth defects or oth | |
| International regu | <u>lations</u> | | | | | |
| International list | S | Japan inventory (| ry (AICS): Not dete IECSC): Not detern (ENCS): Not determ (ISHL): Not determi | nined. nined. ned. | | |
| | | Korea inventory (Malaysia Inventor New Zealand Inve Philippines inven Taiwan Chemical | tory (PICCS): Not of Substances Inver ry: Not determined. | Not determined. I s (NZIoC) : Not determi | | |

Section 15. Regulatory information

Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| Classification | Justification |
|---|--------------------|
| SKIN CORROSION/IRRITATION - Category 1B | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 | Calculation method |
| SKIN SENSITIZATION - Category 1 | Calculation method |
| CARCINOGENICITY - Category 2 | Calculation method |
| TOXIC TO REPRODUCTION (Fertility) - Category 2 | Calculation method |
| TOXIC TO REPRODUCTION (Unborn child) - Category 2 | Calculation method |

| <u>History</u> | |
|--------------------------------|---|
| Date of printing | : 10/30/2018 |
| Date of issue/Date of revision | : 10/30/2018 |
| Date of previous issue | : 10/17/2018 |
| Version | : 4.02 |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations |
| Matter to seales | |

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs

| | | 12/13 |
|---|-----------|-------|
| 81021 Garage Floor Coating Kit SHW-85-NA Tan | IA-GHS-US | |

Section 16. Other information

obtained from any other source.

| Date of issue/Date | of revision | : 10/30/2018 | Date of previous issue | : 10/17/2018 | Version : 4.02 | 13/13 |
|--------------------------------|-------------|--------------|------------------------|------------------|----------------|-------|
| 81021 Garage Floor Coating Kit | | | | SHW-85-NA-GHS-US | | |
| | Tan | | | | | |