

GENERAL DESCRIPTION

Natural Look Waterproofer forms a long-lasting, waterproofing seal on concrete, brick, masonry, natural stone and pavers. The penetrating formula protects against the sun's powerful rays, damaging weather, water, gasoline and de-icing salts.

PRODUCT FEATURES

- Clear, waterproofing sealer for brick, pavers, driveways, sidewalks and patios
- Protects from sun, water and household-chemical damage
- Resists gasoline, oil and de-icing salts
- Maintains the beauty of concrete without changing its appearance

RECOMMENDED USES

Use on interior and exterior aggregate, concrete, masonry, mortar and flagstone. Do not use below grade.

COMPOSITION

	Base and Fill Levels (oz./gal.)
Clear	128

REGULATORY COMPLIANCE

Current as of: 3/10/2017	
SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. All surfaces must be clean, dry and free of all loose, peeling paint or contaminants.

Bare concrete:

New concrete, masonry surfaces and mortar should be cured 60 days.

Previously sealed surfaces:

Clean with an all-purpose cleaner (TSP or substitute). Previously sealed surfaces must be porous and able to accept additional sealer.

Test surface porosity before sealing:

Avoid using this product on nonporous, sealed surfaces. To test, place a few drops of water on the surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION AND CLEANUP

Use a roller or low-pressure, garden-type sprayer. While the first coat is still wet, apply a second coat to maximize protection. Allow 5–10 minutes for final penetration, then use a clean, dry cloth to wipe off all excess that did not soak into the surface. **Do not pond or puddle this product.** Clean up with warm, soapy water.

Periodic maintenance: Since sealers do not last forever, reapply when water begins to penetrate the surface again.

STORAGE AND DISPOSAL

Do not freeze! Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

PRODUCT SPECIFICATIONS

Vehicle Type: Silicone emulsion

Viscosity: 8–13 Ford Cup

Flashpoint: N/A

VOC (g/L): less than 100 g/L

VOC (lbs./gal.): 0.46

Volume Solids: 30%

Weight Solids: 30%

Weight Per Gallon: 8.33 lbs./gal.

Practical Coverage: Covers approximately 75–150 sq. ft. (7–14 m²) per gallon, depending upon surface porosity. Do not thin.

Recommended Film Thickness:

14.2 mil Wet 4.3 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To the Touch: 1 hour

Application Temperature: 50–90 °F (10–32 °C)

CAUTIONS

CAUTION. KEEP OUT OF THE REACH OF CHILDREN. May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.*

CL 1.3

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 3/10/17

Version: 82092B