# **SAFETY DATA SHEET**

17003

# Section 1. Identification

Product name	: Expressions® Interior Paint & Primer Flat Tint Base
Product code	: 17003
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of the	ne substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone	. (800) 424-9300

Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	: SKIN CORROSION/IRRITATION - Category 2
substance or mixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A
GHS label elements	
Hazard pictograms	
Circual word	
Signal word	: Danger
Hazard statements	: Causes skin irritation.
	Causes serious eye irritation. May cause cancer.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wash thoroughly after handling.

Date of issue/Date	e of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version : 13	1/13
17003	Expressions® Inte Tint Base	erior Paint & Primer	Flat		SHW-85-NA-GHS-US	

# Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	<ul> <li>WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM</li> <li>OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.</li> <li>Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.</li> </ul>
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Calcium Carbonate	≥10 - <20	1317-65-3 🥄
Titanium Dioxide	≤10	13463-67-7
Cristobalite, respirable powder	<1	14464-46-1
Heavy Paraffinic Oil	≤1	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version	:13	2/13
17003	Expressions® Interior F Tint Base	Paint & Primer F	lat		SHW-85-	NA-GHS-US	

## Section 4. First aid measures

Section 4. First a				
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.			
Most important symptoms/e	effects, acute and delayed			
Potential acute health effe	<u>cts</u>			
Eye contact	: Causes serious eye irritation.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: Causes skin irritation.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/sym	<u>otoms</u>			
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>			
Specific treatments	: No specific treatment.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version : 13	3/13
17003	Expressions® Interior I Tint Base	Paint & Primer I	Flat		SHW-85-NA-GHS-US	

### Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures
 Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue
17003	Expressions® Interior F Tint Base	Paint & Primer F	lat

: 10/13/2020

# Section 7. Handling and storage

Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

**Control parameters** 

#### **Occupational exposure limits (OSHA United States)**

Ingredient name	CAS #	Exposure limits
Calcium Carbonate	1317-65-3	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total
Titanium Dioxide	13463-67-7	ACGIH TLV (United States, 3/2020). TWA: 10 mg/m <sup>3</sup> 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Cristobalite, respirable powder	14464-46-1	<ul> <li>OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m<sup>3</sup> / 2 x (%SiO2+2) 8 hours. Form: Respirable TWA: 30 mg/m<sup>3</sup> / 2 x (%SiO2+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2020). TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</li> </ul>
Heavy Paraffinic Oil	64742-65-0	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 3/2020). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist

# Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
Titanium dioxide	13463-67-7	CA British Columbia Provincial (Canada, 1/2020). TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m <sup>3</sup> 8 hours. Form: respirable fraction CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m <sup>3</sup> 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m <sup>3</sup> 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m <sup>3</sup> 15 minutes. TWA: 10 mg/m <sup>3</sup> 8 hours.
Cristobalite	14464-46-1	<ul> <li>CA British Columbia Provincial (Canada, 1/2020).</li> <li>TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA Quebec Provincial (Canada, 7/2019).</li> <li>TWAEV: 0.05 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction.</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> </ul>

#### **Occupational exposure limits (Mexico)**

	CAS #	Exposure limits
None.		

controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some
	cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version : 13	6/13
17003	Expressions® Interior Tint Base	r Paint & Primer	Flat		SHW-85-NA-GHS-US	;

# Section 8. Exposure controls/personal protection

-	· · · · ·
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point/boiling range	: 100°C (212°F)
Flash point	: Closed cup: 96°C (204.8°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: 2.3 kPa (17.5 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.32
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	

Date	e of issue/Date of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version : 13	7/13
170	17003 Expressions® Interior Paint & Primer Flat Tint Base				SHW-85-NA-GHS-US	

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Cristobalite, respirable powder	-	2B 1	- Nown to be a human carcinogen.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name				Category	Route of exposure	Target organ	S
Calcium Ca	rbonate			Category 3	-	Respiratory tra irritation	act
Date of issue/Da 17003		: 11/6/2020 erior Paint & Primer	<b>Date of previou</b> Flat	s issue : 10/~	13/2020	ion :13 V-85-NA-GHS-US	8/13 6

# Section 11. Toxicological information

Name	ity (repeated exposure)			
Name		Category	Route of exposure	Target organs
Cristobalite, respirable powo	der	Category 1	inhalation	respiratory tract
Aspiration hazard			·	·
Name			Result	
Heavy Paraffinic Oil			ASPIRATION HAZA	RD - Category 1
Information on the likely routes of exposure	: Not available.			
Potential acute health effec	<u>cts</u>			
Eye contact	: Causes serious eye irrit	ation.		
Inhalation	: No known significant ef	fects or critical haza	rds.	
Skin contact	: Causes skin irritation.			
ngestion	: No known significant ef	fects or critical haza	rds.	
Symptoms related to the pl	hysical, chemical and tox	icological characte	eristics	
Eye contact	: Adverse symptoms may pain or irritation watering redness	y include the followin	ıg:	
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may irritation redness	y include the followin	ıg:	
Ingestion	: No specific data.			
Delayed and immediate eff	ects and also chronic effe	ects from short and	l long term exposur	<u>e</u>
<u>Short term exposure</u>				
Potential immediate	: Not available.			
Potential delayed effects	: Not available.			
<u>Long term exposure</u> Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health eff	fects			
Not available.				
General	: No known significant ef	fects or critical haza	rds.	
	: May cause cancer. Ris			l of exposure.
Carcinogenicity	•	•	rds.	
Carcinogenicity Mutagenicity	: No known significant ef	fects or critical haza		
Carcinogenicity Mutagenicity Teratogenicity Developmental effects	•	fects or critical hazan fects or critical hazan	rds.	

#### Numerical measures of toxicity

Date of issue/Date of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version : 13	9/13
17003 Expression Tint Base	s® Interior Paint & Primer	Flat		SHW-85-NA-GHS-US	

# Section 11. Toxicological information

#### Acute toxicity estimates

Not available.

# Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water Fish - Fundulus heteroclitus		96 hours
Persistence and degradabil	i <u>ty</u>		
Not available.			
Bioaccumulative potential Not available.			
<u>Mobility in soil</u> Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.		
Other adverse effects	: No known significant effects or critical l	nazards.	
Section 13. Dispo	sal considerations		
Disposal methods	: The generation of waste should be avo of this product, solutions and any by-pri- requirements of environmental protection regional local authority requirements. If via a licensed waste disposal contractor the sewer unless fully compliant with the Waste packaging should be recycled, when recycling is not feasible. This may safe way. Care should be taken when cleaned or rinsed out. Empty containent Avoid dispersal of spilled material and the and sewers.	oducts should at all times comply on and waste disposal legislation Dispose of surplus and non-recyc r. Waste should not be disposed re requirements of all authorities Incineration or landfill should only aterial and its container must be d handling emptied containers that rs or liners may retain some prod	with the and any lable products of untreated to with jurisdiction be considered isposed of in a have not been uct residues.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Date of issue/Date of rea	vision : 11/6/20	D20 Date of previous	issue : 10/13/20	20 Vers	ion : 13 10/13
	essions® Interior Paint & Pr				V-85-NA-GHS-US

Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
pecial precaution		consider container s mode of transport (s suitably for that mod prior to shipment, ar responsibility of the p	izes. The presence ea, air, etc.), does i e of transport. All p id compliance with person offering the s goods must be tra	of a shipping descrip not indicate that the p ackaging must be re- the applicable regula product for transport ained on all of the risk	product is packaged viewed for suitability tions is the sole . People loading and as deriving from the

# Section 15. Regulatory information

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Inter	natior	<u>nal r</u>	equ	<u>ilations</u>

International lists	: Australia inventory (AICS): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (ENCS): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue	: 10/13/2020	Version :	13 11/13
17003 Expressions® Interior Paint & Primer Flat Tint Base				SHW-85-NA	A-GHS-US	

## Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification			
SKIN CORROSION/IRRIT SERIOUS EYE DAMAGE/ CARCINOGENICITY - Cat	Calculation method Calculation method Calculation method			
<u>History</u>				
Date of printing	: 11/6/2020			
Date of issue/Date of revision	: 11/6/2020			
Date of previous issue	: 10/13/2020			
Version	: 13			
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations			

#### **V** Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 10/13/2020

Date of issue/Date	of revision	: 11/6/2020	Date of previous issue
17003	Expressions® Interior P Tint Base	aint & Primer Fl	at

:10/13/2020