



Valspar® High Gloss Sealer, Wet Look

No. 82390

GENERAL DESCRIPTION

Valspar Wet Look High Gloss Sealer waterproofs and enhances the color and design of aggregate, masonry, brick, slate and pavers with a glossy, wet-look sheen. As durable as it is beautiful, it protects against the sun's powerful rays, damaging weather, water, gasoline and de-icing salts.

PRODUCT FEATURES

- Impart a rich, glossy finish
- Clear, waterproofing sealer for driveways, sidewalks, pavers and patios
- Protects from sun, water and household-chemical damage
- Resists gasoline, oil and de-icing salts
- For use over semi-transparent stain or bare concrete

RECOMMENDED USES

Interior and Exterior aggregate, concrete, brick, pavers, masonry, mortar and flagstone. Do not use on garage floors.

APPLICATION AND CLEANUP

Apply only when surface and air temperature are 50–90 °F (10–32 °C). Do not apply to wet or damp surfaces, or areas prone to ponding water. Dries to the touch in 1–2 hours. Recoat after 2 hours. Dries hard overnight. Apply with a roller, brush or low-pressure garden sprayer. If the first coat sinks in rapidly, apply a second coat after 2 hours. Allow to soak for 10–15 minutes — or until pores are completely sealed. Wipe off excess from the surface before the sealer dries. Clean up with warm, soapy water.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic resin
Viscosity: 10–15 Sec Ford Cup
Flashpoint: N/A
VOC (g/L): less than 100 g/L
VOC (lbs./gal.): 0.42
Volume Solids: 23%
Weight Solids: 25%
Weight Per Gallon: 8.53 lbs./gal.
Practical Coverage: Covers approximately 200–400 sq. ft. (18–37 m²) per gallon depending upon surface porosity. Do not thin.
Recommended Film Thickness:
5.3 mil Wet 1.2 mil Dry
Dry Time @ 77 °F and 50% Relative Humidity
To the Touch: 1–2 hours
Recoat: 2 hours
Dries Hard: 24 hours
Application Temperature: 50–90 °F (10–32 °C)

REGULATORY COMPLIANCE

Current as of: 3/10/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



Valspar® High Gloss Sealer, Wet Look

No. 82390

SURFACE PREPARATION

Note:

This product will seal out water and other stains, but will not correct moisture problems coming from within the surface. Test for moisture by taping aluminum foil or plastic wrap to the surface for 24–48 hours. If the surface is damp when the aluminum or plastic is removed, moisture migration is present. The source of the moisture must be corrected before using this product or it may turn white upon drying.

General:

Read the Lead Warning paragraph. All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Wash all surfaces, rinse well and allow to thoroughly dry overnight before applying.

Bare concrete:

Allow 60 days minimum for new concrete to cure before sealing

Previously sealed surfaces:

Clean with an all-purpose cleaner (TSP or substitute). Previously sealed surfaces must be porous and able to accept additional sealer.

Test surface porosity before sealing:

Avoid using this product on nonporous, sealed surfaces. To test, place a few drops of water on the surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

CAUTIONS

WARNING! VAPOR HARMFUL.

WARNING! CONTAINS ETHYLENE GLYCOL MONOBUTYL ETHER. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES, SKIN AND CLOTHING. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* IF SWALLOWED: Do not induce vomiting. Get medical attention immediately.*

* Call poison control center, hospital emergency room or physician immediately.

CS 4.3 EB

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631
877.825.7727
valsparpaint.com
Revised: 3/10/17
Version: 82390A