# **SAFETY DATA SHEET**

81001

# Section 1. Identification

Product name	: Valspar® Cabinet Door & Trim Satin Pastel Base
Product code	: 81001
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of th	e substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115

Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: May cause cancer. Suspected of damaging fertility or the unborn child.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Date of issue/Date	of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version : 4	1/13
81001	Valspar® Cabinet Door Pastel Base	& Trim Satin			SHW-85-NA-GHS-US	

## Section 2. Hazards identification

Supplemental label elements	<ul> <li>WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM</li> <li>OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.</li> <li>This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.</li> </ul>
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

#### CAS number/other identifiers

Ingredient name	% by weight	CAS number
	≥10 - ≤25	13463-67-7
Cristobalite, respirable powder	<1	14464-46-1
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	≤0.3	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.		
Ingestion	<ul> <li>Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.</li> </ul>		
Date of issue/Date of revision	: 11/2/2023 Date of previous issue : 10/2/2023 Version : 4 2/13		

Date of issue/Date	of revision	11/2/2023	Date of previous issue	: 10/2/2023	Version	: 4	2/13
81001	Valspar® Cabinet Door Pastel Base	& Trim Satin			SHW-85-N	IA-GHS-US	

## Section 4. First aid measures

Potential acute healt	<u>n епестs</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	s/symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to

before removing it, or wear gloves.

give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date	of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version : 4	3/13
81001	Valspar® Cabinet D Pastel Base	oor & Trim Satin			SHW-85-NA-GHS-US	

# Section 5. Fire-fighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
-	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination. See Section 10 for
	incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles
Cristobalite, respirable powder	14464-46-1	<ul> <li>OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m<sup>3</sup> / 2 x (%SiO2+2) 8 hours. Form: Respirable TWA: 30 mg/m<sup>3</sup> / 2 x (%SiO2+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m<sup>3</sup> 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2023). [Silica, crystalline] TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</li> </ul>
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	77-99-6	None.

#### Occupational exposure limits (Canada)

Ingredien	nt name		CAS #	Exposure limit	ts	
Cristobalit	te		14464-46-1	6/2022). [Silica and Cristobalit TWA: 0.025 m Respirable CA Quebec Pro TWAEV: 0.05 Respirable dust CA Alberta Pro 8 hrs OEL: 0.0 Respirable part CA Ontario Pro	ng/m <sup>3</sup> 8 hours. Form: ovincial (Canada, 6/20 mg/m <sup>3</sup> 8 hours. Form: t. ovincial (Canada, 6/20 025 mg/m <sup>3</sup> 8 hours. For iculate ovincial (Canada, 6/20 g/m <sup>3</sup> 8 hours. Form: Res	uartz 022). 18). m: 019).
)ate of issue/	Date of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version : 4	5/13
1001	Valspar® Cabine Pastel Base	et Door & Trim Satin			SHW-85-NA-GHS-	US

# Section 8. Exposure controls/personal protection

			CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: respirable fraction
Occupational exposure lim	i <u>its (Mexico)</u>		
		CAS #	Exposure limits
None.			
Biological exposure indice	<u>s (United States)</u>	I	
No exposure indices known.			
Biological exposure indice	<u>s (Canada)</u>		
No exposure indices known.			
Biological exposure indice	<u>s (Mexico)</u>		
No exposure indices known.			
Appropriate engineering controls	local exhaust ventila	ation or other eng	nes, gas, vapor or mist, use process enclosures, gineering controls to keep worker exposure to commended or statutory limits.
Environmental exposure controls			gulated chemical. See Section 15 of the US SDS
	they comply with the cases, fume scrubb	e requirements o ers, filters or eng	process equipment should be checked to ensure f environmental protection legislation. In some gineering modifications to the process equipment ns to acceptable levels.
Individual protection measu	ures		
Hygiene measures	eating, smoking and Appropriate techniq	l using the lavate ues should be us I clothing before	roughly after handling chemical products, before bry and at the end of the working period. sed to remove potentially contaminated clothing. reusing. Ensure that eyewash stations and safety n location.
Eye/face protection	assessment indicate gases or dusts. If c	es this is necess ontact is possibl	pproved standard should be used when a risk ary to avoid exposure to liquid splashes, mists, e, the following protection should be worn, unless egree of protection: safety glasses with side-
Skin protection			
Hand protection	worn at all times wh necessary. Conside during use that the g noted that the time t glove manufacturers	en handling che ering the parame gloves are still re to breakthrough s. In the case of	es complying with an approved standard should be mical products if a risk assessment indicates this is eters specified by the glove manufacturer, check etaining their protective properties. It should be for any glove material may be different for different mixtures, consisting of several substances, the be accurately estimated.
Body protection		isks involved an	e body should be selected based on the task being d should be approved by a specialist before
Other skin protection	: Appropriate footwea	ar and any addition eing performed a	onal skin protection measures should be selected and the risks involved and should be approved by a ct.

Date of iss	ue/Date of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version : 4	6/13
81001		t Door & Trim Satin			SHW-85-NA-GHS-	US
	Pastel Base					

### Section 8. Exposure controls/personal protection

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance						
Physical state	: Liq	quid.				
Color	: No	Not available.				
Odor	: No	Not available.				
Odor threshold	: No	ot available.				
рН	: 8.7	7				
Melting point/freezing point	: No	ot available.				
Boiling point, initial boiling point, and boiling range	: 10	0°C (212°F)				
Flash point	: Clo	osed cup: Not applicable.				
Evaporation rate	: 0.0	: 0.09 (butyl acetate = 1)				
Flammability	: No	Not available.				
Lower and upper explosion limit/flammability limit	: No	Not available.				
Vapor pressure	: 2.3	2.3 kPa (17.5 mm Hg)				
Relative vapor density	: 1[	1 [Air = 1]				
Relative density	: 1.3	31				
Solubility(ies)	:					
Media		Result				
cold water		Partially soluble				
Partition coefficient: n- octanol/water	: No	t applicable.				
Auto-ignition temperature	: Not available.					
Decomposition temperature	: No	: Not available.				
Viscosity	: Ki	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight	: No	ot applicable.				
Heat of combustion	: 0.6	644 kJ/g				
		• • • •				

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.

Date of issue/Date	of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version :	4 7/13
81001	Valspar® Cabinet Door Pastel Base	& Trim Satin			SHW-85-N/	A-GHS-US

### Section 10. Stability and reactivity

**Incompatible materials** 

: No specific data.

# Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	LD50 Oral	Rat	14000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Cristobalite, respirable powder	- +	2B 1	- Known to be a human carcinogen.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

#### Aspiration hazard

Not available.

Eye contact

#### Information on the likely : Not available.

routes of exposure

#### Potential acute health effects

: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version	:4	8/13
81001	Valspar® Cabinet Doo Pastel Base	r & Trim Satin			SHW-85-	NA-GHS-US	

# Section 11. Toxicological information

		ogical information
Inhalation	:	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	4	No known significant effects or critical hazards.
Symptoms related to the p	ohys	sical, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fect	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Potential chronic health ef	ffec	<u>ts</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	1	Suspected of damaging the unborn child.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	Suspected of damaging fertility.

Numerical measures of toxicity Acute toxicity estimates Not available.

Date of previous issue

:10/2/2023

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide 2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	10	Fish - <i>Fundulus heteroclitus</i> Daphnia - <i>Daphnia magna</i>	96 hours 48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	-	<1	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects	: No known significant effects or critical hazards.
-----------------------	---

## Section 13. Disposal considerations

Disposal methods

# : This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	UN3082	UN3082
UN proper shipping name	-	-	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, 3-Iodo-2-propynyl Butyl Carbamate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, 3-lodo-2-propynyl Butyl Carbamate). Marine pollutant
	evision : 11/2/20 spar® Cabinet Door & Trim S tel Base		issue : 10/2/202		on : 4 10/13 -85-NA-GHS-US


					(Zinc Pyrithione, 3-lodo-2-propynyl Butyl Carbamate)
Transport hazard class(es)	-	-	-	9	9
Packing group	-	-	-		
Environmental hazards	No.	No.	No.	Yes.	Yes.
Additional information	-			This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	This product is no regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <u>Emergency</u> <u>schedules</u> F-A, S F
pecial precautions ansport in bulk ac	cc m su to da ai	onsider container siz ode of transport (se litably for that mode shipment, and com the person offering	zes. The presence of a, air, etc.), does no of transport. All pa apliance with the ap the product for trans st be trained on all of	ovided for informational p of a shipping description f ot indicate that the produc ckaging must be reviewe plicable regulations is the nsport. People loading an of the risks deriving from situations.	or a particular ct is packaged d for suitability prior sole responsibility d unloading

## Section 15. Regulatory information

U.S. Federal regulations	: TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)					
	TSCA 5(a)2 final sigr	nificant new use rule	s: Sodium Nitrite; Chlorodiazocarboxylate			
	List name	Chemical name	Notes			
	United States - TSCA 5(a) 2 - Final significant new use rules	Sodium Nitrite	40 CFR 721.4740			
	United States - TSCA 5(a) 2 - Final significant new use rules	Chlorodiazocarboxylate	40 CFR 721.10414			
SARA 313 SARA 313 (40 CFR 372.45	) supplier notification can be	e found on the Environ	mental Data Sheet.			
California Prop. 65	, <b>.</b>					
	ontains chemicals known to	the State of California	a to cause cancer and birth defects or other			
International regulations						
Montreal Protocol						
Not listed.						
	n Persistent Organic Poll	<u>utants</u>				
Not listed.						
International lists	Japan inventory ( Japan inventory ( Korea inventory ( New Zealand Inve Philippines invent	ECSC): Not determine CSCL): Not determine ISHL): Not determined KECI): Not determined ISHL): Not determined KECI): Not determined Intory of Chemicals ( tory (PICCS): Not deter Substances Inventor	ed. ed. J. J. <b>NZIoC)</b> : Not determined.			

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Date of issue/Date	of revision	: 11/2/2023	Date of previous issue	: 10/2/2023	Version : 4	12/13
81001	Valspar® Cabinet Doo Pastel Base	r & Trim Satin			SHW-85-NA-GHS-US	

### Section 16. Other information

	Justification						
CARCINOGENICITY - Cat TOXIC TO REPRODUCTION	Calculation method Calculation method						
<u>History</u>							
Date of printing	: 11/2/2023						
Date of issue/Date of revision	: 11/2/2023						
Date of previous issue	: 10/2/2023						
Version	: 4						
Key to abbreviations       : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 197 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations							

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.