

TECHNICAL DATA SHEET

WD-40[®] Specialist[®] Industrial-Strength DEGREASER



PRODUCT DESCRIPTION

WD-40[®] SPECIALIST[®] INDUSTRIAL-STRENGTH DEGREASER - FAST-ACTING FORMULA is a powerful solvent-based degreaser that quickly cleans machinery, engines and equipment to look like new and run smoothly. Contains WD-40[®]PowerSolve Technology[™], a proprietary solvent that quickly breaks down grease yet unlike other harsh degreaser solvents is safe on most surfaces including metals, plastics, rubber, glass, aluminum and more.

APPLICATIONS

- ENGINES
- TIRE RIMS
- TRACTORS
- FORKLIFTS
- GEARS
- CHAINS
- INDUSTRIAL MACHINERY
- METAL TOOLS

FEATURES & BENEFITS

Unique Smart Straw
Sprays 2 Ways

Solvent-Based
formula quickly
dissolves grease,
oil, dirt, adhesives
and more

High Flashpoint



50-State VOC
Compliant

No Residue &
Low Fumes

NSF Category K1

PHYSICAL and CHEMICAL PROPERTIES

Boiling Point (initial):	221°C (430°F)	Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 5.6%
Solubility in Water:	Insoluble in water	pH:	Not Applicable
Vapor Pressure:	2.03 mmHg @20°C (Petroleum Solvent)	Vapor Density:	5.3 (Petroleum Solvent)
Flammability	Flammable aerosol	VOC:	9.7% (79g/L)
Coefficient of Water/Oil Distribution:	Not Established	Appearance/Odor:	Clear liquid/Mild petroleum
Flash Point:	94.5°C (202°F)		

PERFORMANCE RESULTS

EXTREME CLEANING SCORE

This test evaluates the cleaning ability of a fluid by using a mechanical device, the Gardner Scrubability Apparatus, that pulls a sponge across a tile that has been soiled with a choice of substances. The three common soils that were tested are: A2 - Kitchen Grease; A3 - Industrial Soil; and A6 - Heavy Household Soil.

WD-40 Specialist	75
Gunk Engine Degreaser	63

*RESULTS SHOW PERCENTAGE OF SOIL REMOVAL. HIGHER IS BETTER. .

DIRECTIONS

SHAKE CAN WELL. Flip straw up for precise STREAM with no overspray or down for wide SPRAY to cover larger areas. Apply by spraying directly on surface to be cleaned. Let set for a few seconds and wipe clean with dry cloth.

PACKAGING SPECIFICATIONS

Individual Unit					Case Pack						Pallet					
Appx Wt (oz)	W (in)	D (in)	Ht (in)	Cube	Case Pack	Appx Wt (lbs)	W (in)	D (in)	Ht (in)	Cube	Appx Wt (lbs)	Cases /Layer	Layers	Total QTY	Appx Ht (in)	Cube
1.24	2.625	2.625	9.75	0.038	6	7.75	5.75	8.18	10.31	0.281	1473.9	37	5	185	56.56	62.84

15oz. Industrial-Strength Degreaser 6 ct o/s Case # / GTIN #: 1 00 79567 30028 8 ITEM # / UPC #: 0 79567 30028 1

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

DISPOSAL

If this product becomes a waste, it would not be expected to meet the criteria of a RCRA hazardous waste. However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Do not puncture or incinerate containers, even empty. Dispose in accordance with federal, state, and local regulations.

SPECIAL USE WARNINGS

CONTENTS ARE FLAMMABLE: Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. **ELECTRICITY CAN BURN A HOLE IN THE CAN AND CAUSE CONTENTS TO BURST INTO FLAMES.** To avoid serious burn injury, do not let **THE CAN** touch battery terminals, electrical connections on motors or appliances or any other source of electricity. **CONTENTS UNDER PRESSURE:** Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat or store above 120°F. Avoid eye contact. Avoid prolonged or repeated contact with skin and clothing. Avoid breathing vapors or spray mists. Use in well ventilated area. Wash thoroughly with soap and water after use. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**
FIRST AID: CONTAINS PETROLEUM DISTILLATES AND CARBON DIOXIDE PROPELLANT
Ingestion (Swallowed): Do not induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately. **Eye Contact:** Flush thoroughly with water for 15 minutes. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. To prevent drying effects, avoid prolonged or repeated contact with skin. **Inhalation (Breathing):** If irritation develops, discontinue use and move to fresh air. Get medical attention if irritation or other symptoms persist.

REGULATORY INFORMATION

U.S. Federal Regulations: CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III: Hazard Category For Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure; **Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None; **Section 302 Extremely Hazardous Substances (TPQ):** None; **EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory; **Canadian WHMIS Classification:** Class B-5 (Flammable Aerosol), Class D-2-A (Very toxic material causing other chronic effects)



WD-40 COMPANY
 PO BOX 80607, San Diego, CA 92138 USA
 WD-40 Safety Hotline 1-888-324-7596
WD40Specialist.com

