



# Our ORIGINAL Formula



## Original Satin Finish

SATIN SHEEN



**Product #:** TB 6044

**More Info:** [waterlox.com/original](http://waterlox.com/original)

## Please Note:

This product is a finish only. You must first seal your wood with the Waterlox Original Sealer/Finish (TB 5284). Use this product as your final coat to provide a satin sheen.



### Product Details:

- Our traditional formulation is product number TB 6044.
- Produces a satin sheen appearance (20°-25° gloss level).
- Our lowest gloss level offered.
- Like all of our Tung oil finishes, 90% of the resin portion of the formula is from renewable, natural resources.
- Formulated as a traditional interior penetrating Tung oil finish.
- Forms a protective yet elastic finish against common household spills, moisture and foot traffic.
- Penetrates and waterproofs when used as a finishing system in conjunction with Waterlox Original Sealer/Finish.
- Easier to maintain than other interior clear finishes or surface finishes.\*
- We have two VOC compliant formulations available (TB 6045 - 450 VOC and TB 6035 - 350 VOC).

### Product Uses:

- Use as a finish coat to achieve a satin finish on all interior wood projects including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames, gun stocks and various woodworking projects.
- Non-toxic when dry/fully cured.
- Use as a finish coat over base coats of Waterlox Original Sealer/Finish.
- Coverage/thinning. One gallon covers 500 square feet per coat. One quart covers 125 square feet per coat. No thinning necessary.
- Dry time. Minimum of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.

\* Waterlox Original Satin Finishes are more difficult to repair and/or spot apply versus the Waterlox Original Sealer/Finish product. Our Tung oil finishes; however, are easier to repair than other surface finishes.