

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ULTRAMAX WOOD STAIN
ALL COLORS AND TINT BASES

HMIS CODES: H F R P
1 0 0

PRODUCT CODE: 190,191,192,193,194,195,196

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: **UNITED GILSONITE LABORATORIES**
ADDRESS: **1396 JEFFERSON AVENUE**
SCRANTON, PA 18509

EMERGENCY PHONE: **(800) 424-9300**

INFORMATION PHONE: **(570) 344-1202**
NAME OF PREPARER: **R. BARAKO**

DATE ISSUED: MAY 2008
SUPERSEDES: JANUARY 2008

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mmHg@TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
WATER	7732-18-5	NOT ESTAB	NOT ESTAB	NOT ESTAB	1.0 (68F)	75 - 80
ACRYLIC MODIFIED ALKYD RESIN	NOT ESTAB	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	8 - 10
PROPYLENE GLYCOL	57-55-6	NOT ESTAB	NOT ESTAB	NOT ESTAB	0.2 (68F)	<5
SYNTHETIC AMORPHOUS SILICON DIOXIDE	7631-86-9	20 MPPCT	10 MG/M ³	NOT ESTAB	N/A	<5

No toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of CFR 372 are present

SEE SECTION IX FOR LIST OF ADDITIONAL INGREDIENTS

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: DOES NOT EXCEED MAXIMUM VOC 250 G/L
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: COLORS, PRODUCT SPECIFIC. TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O = 1): 1.08
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME:
EXTINGUISHING MEDIA: NONE KNOWN
SPECIAL FIRE FIGHTING PROCEDURES: CONTAINERS MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

METHOD USED: N/A
LOWER: N/A **UPPER:** N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, HEADACHE, NAUSEA, MENTAL CONFUSION, SLURRED SPEECH DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC) NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: GIVE ONE OR TWO GLASSES OF WATER. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS DO NOT GIVE ANYTHING BY MOUTH. CONSULT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVISE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BRATHING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: RAGS, STEEL WOOL OR WASTE SOAKED WITH ZAR OIL MODIFIED WOOD STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATORS WITH SOLID PARTICULATE CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTIONS II & IX

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE CHEMICAL SPLASH GOGGLES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM. WASH COMTAMINATED CLOTHING BEFORE REUSE.

SECTION IX – ADDITIONAL INGREDIENTS

**OCCUPATIONAL
EXPOSURE LIMITS**

PRODUCT	INGREDIENT	CAS. NO.	PEL	TLV	OTHER	WEIGHT PERCENT
BRAZILIAN CHERRY 190	BURNT UMBER					
CYAN PEPPER						
ESPRESSO						
JAMAICAN RUM						
WHEAT						
EBONY						
TINT BASE / WOOD CONDITIONER						

(1) = TIME WEIGHTED AVERAGE

* SEE SECTION VI

SECTION X – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.