

PRODUCT DATA SHEET

Publication Date: 6-8-22

ZAR® Deck & Siding Solid Color Coating

PRODUCT DESCRIPTION

ZAR® Deck & Siding Solid Color Coating combines the opacity of paint with the penetrative properties of stain. This innovative formula includes self-crosslinking Core-Shell Technology for higher performance standards with increased adhesion, weatherability, and color retention. Also fortified with Aliphatic Urethane for increased durability.

- Self cross-linking, core shell latex for superior adhesion
- Broad spectrum preservative for outstanding mold & mildew protection
- Fortified with Aliphatic Urethane for increased durability

BASIC USES

Ideal for most exterior surfaces including:

- Wood decking
- Most composite decking
- Textured hardboard
- Fiber cement
- T-111 siding
- Concrete
- Stucco
- Adobe
- Brick
- Galvanized metal
- Aluminum and vinyl siding
- Plastic gutters and downspouts

TECHNICAL DATA

COMPOSITION: Latex base

SHEEN: N/A

% WEIGHT SOLIDS: 46.2 – 54.4(Depending on color)

DENSITY (LBS./US GAL.): Depending on color SG 1.18-1.36)



COVERAGE

Smooth surfaces: 300-400 square feet (27.871 - 37.16 m²) per gallon
Rough Surfaces: 100-200 (9.29 - 18.58 m²) square feet per gallon



COATS

Recommended



DRY TIME

30 minutes



CLEAN-UP

Soap and Water

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

VISCOSITY: 97 +/-3 Ku @25°C

COLORS:

- 5 ready mixed
- 3 tint bases

DRY TIME:

- 30 minutes to recoat, 30 minutes to touch
- Allow 24 hours for full cure

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

COVERAGE:

Smooth surfaces: 300-400 square feet (27.871 - 37.16 m²) per gallon
Rough Surfaces: 100-200 (9.29 - 18.58 m²) square feet per gallon

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.

FLASH POINT: 104°F (40°C)

SHELF LIFE: 5 years unopened container

FREEZE/THAW: Protect from freezing

CONTAINER SIZES: 1 gallon and 5-gallon containers

VOC

Does not exceed 100 g/L

TINTING

Personalize and create a unique color using the MatchRite tinting system. Tint dependent on tint base used - up to 12 oz.

LIMITATIONS

Do not apply over clear finishes. Do not pretreat or use a water repellent preservative. Test the wood for factory treatment by sprinkling a few drops of water on the surface. If water is readily absorbed into the wood, proceed. If not, DO NOT apply ZAR Deck and Siding Stain. Wait five months and then retest.

SURFACE PREPARATION

Surface must be clean, dry and in good condition. Remove all mildew, dirt, loose wood fibers, paint flakes, oil and grease. Repair or replace any loose, cracked or warped boards. All mildew (dark, fuzzy or powdery deposits) must be removed with a wood cleaner or the following solution: 1/3 up heavy-duty laundry detergent to 1 quart household bleach to 3 quarts of warm water. Apply with a scrubbing brush. Rinse thoroughly and allow to dry before staining. Wear protective eye goggles and waterproof gloves when handling solution.

Previously painted or stained wood: Clean previously painted surface thoroughly. Remove all loose or flaking paint by scraping. Sand glossy paint surface to improve adhesion.

APPLICATION

Apply only when air and surface temperatures are between 40°F and 95°F. DO NOT THIN. STIR THOROUGHLY before and during application. NOTE: Multiple containers of the same color should be mixed together for uniformity. Do not apply if rain is expected within 24 hours. Apply using a brush, roller, foam pad applicator or by spray. If spraying, the coating should be dry brushed or back rolled for color uniformity. **Apply 2 coats.** Avoid applying in direct sunlight. May be sprayed, but application with a synthetic brush is recommended. Be sure to maintain a wet edge when applying. **CLEAN UP:** Clean application

WARNING If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SPECIFICATION

CSI MASTERFORMAT®:

09 93 13 EXTERIOR DECK, FENCE, AND SIDING FINISHES

FIRST AID

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call poison control center, hospital emergency room, or physician immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, call poison control center, hospital emergency room, or physician immediately. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately.

 **WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.**

For additional health and safety information, please refer to the Safety Data Sheet (SDS).

LIMITED WARRANTY

UGL, makers of ZAR Deck & Siding Stain, warrants, subject to the limitations set forth herein, that this product, under normal use and proper storage, will be free from defects in material or workmanship and merchantable for a period of five (5) years on Decks and fifteen (15) years on Siding from the original date of purchase. This limited warranty extends to the original consumer purchaser of the product only and is non-transferable. If this product is found to be defective by UGL within the warranty period, you will receive a replacement of the product or, at UGL's option, a full refund of the purchase price upon presentation of proof of purchase (original sales receipt). This limited warranty excludes failure to apply the product to a properly prepared bare surface in accordance with UGL's instructions provided with this product. UGL MAKES NO FURTHER EXPRESS WARRANTIES. THIS LIMITED WARRANTY EXCLUDES (1) LABOR AND ALL OTHER COSTS ASSOCIATED WITH THE APPLICATION OR REMOVAL OF THE PRODUCT OR ANY PLACEMENT PRODUCT, AND (2) ANY INDIRECT, SPECIAL, EXEMPLARY, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the limitation or exclusion of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights and you may also have other legal rights which vary from state to state. To make a warranty claim please contact (with proof of purchase) the store where you purchased the product or contact UGL directly at 1-800-848-7253 (Consumer Hotline) or by mail at UGL Consumer Inquiry Department, P.O. Box 70, Scranton PA 18501-0070.


ZAR® is a registered trademarks of United Gilsonite Laboratories (UGL).

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

ZAR® Deck & Siding Solid Color Coating

	CONTAINER	NUMBER/CASE	COLOR	ORDER NUMBER
ZAR® D& S Solid Color Coating	1 gallon	2/case	Purely White/ Light Tint Base	82013
ZAR® D& S Solid Color Coating	1 gallon	2/case	High Tea	82113
ZAR® D& S Solid Color Coating	1 gallon	2/case	Oxford Brown	82213
ZAR® D& S Solid Color Coating	1 gallon	2/case	Sable Canyon	82313
ZAR® D& S Solid Color Coating	1 gallon	2/case	Crypto Gray	82413
ZAR® D& S Solid Color Coating	1 gallon	2/case	Tint Medium	82513
ZAR® D& S Solid Color Coating	1 gallon	2/case	Tint Dark	82613
ZAR® D& S Solid Color Coating	5 gallon	each	Purely White/ Light Tint Base	82015
ZAR® D& S Solid Color Coating	5 gallon	each	High Tea	82115
ZAR® D& S Solid Color Coating	5 gallon	each	Oxford Brown	82215
ZAR® D& S Solid Color Coating	5 gallon	each	Sable Canyon	82315
ZAR® D& S Solid Color Coating	5 gallon	each	Crypto Gray	82415
ZAR® D& S Solid Color Coating	5 gallon	each	Tint Medium	82515
ZAR® D& S Solid Color Coating	5 gallon	each	Tint Dark	82615

Note: Color swatches are representative only.



820
Purely White/ Light
Tint Base




821
High Tea



822
Oxford Brown



823
Sable Canyon



824
Crypto Gray



1-800-845-5227 • Fax 1-570-969-7634 • www.ZAR.com
 Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509
 Mail to: P.O. Box 70, Scranton, PA 18501-0070
 Plant Locations: Jacksonville, IL • Jackson, MS