



TECHNICAL DATA

JMX-04

JOMAX® MOLD & MILDEW STAIN REMOVER

DESCRIPTION AND USES

JOMAX® Mold & Mildew Stain Remover removes tough mold & mildew stains on drywall and wood prior to painting. Ideal for use on fiberglass, tile, grout, vinyl, plastic and more. Use weekly around bath and shower stalls to prevent mold and mildew stains & soap scum buildup.

PRODUCTS

| SKU (32 oz. Spray) | Description |
|--------------------|-----------------------------|
| 60118 | Mold & Mildew Stain Remover |

PRODUCT APPLICATION

DIRECTIONS FOR USE

Remove all loose dirt, oil, grease, and other contaminants. Rotate the nozzle to spray position for large areas. Rotate the nozzle to stream for a concentrated jet spray on hard to reach areas. Apply directly to soiled areas. Wait 5 to 10 minutes for stains to disappear and then rinse thoroughly with water. For difficult stains, some scrubbing may be necessary. Wipe dry, using a clean cellulose sponge, cloth or paper towel. For sensitive skin, wear gloves.

PRODUCT APPLICATION

NOTE: This product may not be compatible with all surfaces and all conditions surrounding the application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. Use with adequate ventilation at all times. During use, a NIOSH approved respirator is advised. ***Do not mix this product with other chemicals and do not use on varnished surfaces, granite, marble, silver, brass or leather.**

CAUTION! Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

DISPOSAL

The empty container can be recycled. If recycling is not available, discard in trash.

PHYSICAL PROPERTIES

| Physical Properties | | MOLD & MILDEW STAIN REMOVER |
|---------------------|------------|-----------------------------------------|
| Composition | | Sodium Hypochlorite, Surfactants, Water |
| Weight | Per Gallon | 8.38 lbs. |
| | Per Liter | 1.0 kg |
| pH | | 9-10 |
| Practical Coverage | | 1,000 sq.ft./quart |
| Shelf Life | | 5 years |
| Flash Point | | 145°F (63°C) |
| Safety Information | | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-619
Rev: 010417