



ZINSSER® COVER STAIN® WITH TURBO SPRAY SYSTEM™

DESCRIPTION AND USES

Zinsser® Cover Stain® with Turbo Spray System™ combines the power of Cover Stain all-purpose primer with the speed and convenience of the Turbo Spray System to provide the perfect aerosol solution for priming medium to large sized projects fast.

Cover Stain with Turbo Spray System is great for:

- Stains** – Blocks nicotine, graffiti, fire, smoke, water and dark colors.
- Sealing** – Seals interior/exterior bare wood, flat paint and spackling.
- Bonding** – Sticks to non-galvanized metals, glossy paint, ceramic tile, glass, etc.

The Turbo Spray System with spray up to 10" wide allows for faster project completion making it the ideal primer aerosol for large projects. Use on any interior or exterior wood, concrete, drywall or non-galvanized metal. Adheres to hard-to-paint surfaces such as railings, shutters, outdoor furniture and sticks to glossy paint, glass and ceramic tile. Perfect for sealing spackle, drywall repairs, and hiding dark colors.

PRODUCT

SKU	DESCRIPTION (26 Oz. Aerosol)
352066	Cover Stain White

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC.** **EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN.** **PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously until ball inside can rattles. Turn upside down and continue shaking for one minute – shake occasionally during use. Hold can upright 8-14" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. **Do not use near open flame.**

NOTE: The closer the can is held to the surface, the faster you should move the can while painting to avoid drips and sags.

DRY AND RECOAT TIMES

Based on 70°F (21°C) 50% relative humidity. Allow more time at cooler temperatures. Dries in 1 hour. Topcoat in 1 hour with latex or oil-base paints. For best results, allow primer to cure overnight when applying strong solvent-base topcoats.

CLEAN UP

Wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.



ZINSSER® COVER STAIN® WITH TURBO SPRAY SYSTEM™

PHYSICAL PROPERTIES

COVER STAIN WITH TURBO SPRAY SYSTEM		
Resin Type	Alkyd/Solvent-Based	
Pigment Type	Inorganic	
Solvents	VM&P Naptha, xylene, acetone, 1-nitropropane, nitroethane	
MIR	0.61 max	
Fill Weight	26 oz.	
Recommended Dry Film Thickness (DFT) per Coat	2.0 mils (50µ)	
Practical Coverage at Recommended DFT (assume 15% material loss)	16-20 sq.ft./can	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Handle	30 minutes
	Recoat	60 minutes
	Full Cure	24 hours
Shelf Life	5 years	
Dry Heat Resistance	<230°F	
Flash Point	-141°F (-96°C)	
Shelf Life	5 years	
Safety Information	For additional information, see SDS	

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 888-855-1774
www.rustoleum.com

Form: ARJ-1896
Rev.: 111119