

Catalog Number: EXN08ASC3
Product ID: 7TCA297180R0300
UPC Number: 78621019665
EAN Number: 05011949233751
Status: Active

Single Compression Cable Gland, 1-1/2 Inch NPT Thread, For Use with All Cable Types, Flameproof Ex d and Increased Safety Ex e, Deluge Proof, IP66-68 Rating, Cable Range 22 to 35mm, Nickel Plated Brass

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Kopex
Type	Single Compression Cable Gland
Application	For Use with All Cable to Provide Secure Cable Connections Through Knockouts and Threaded Entries
Standard	Approved to EN60079-0, 60079-1, 60079-7, 60079-31
Size	1-1/2 Inch NPT
Conductor Range	22 to 35 Millimeters
Material	Brass
Finish	Nickel Plated
Color	Metallic
Insulation	IP66-68 Rating
Temperature Rating	-40 to 100 Degrees C
Environmental Conditions	Flameproof Ex d

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	1 1/2 inch
Thread length	28mm
Hexagon angular dimension	77mm
Suitable for cable diameter	22.0-35.0mm
Material	Metal
Material quality	Brass
Surface protection	Nickel-plated
Halogen free	N
Glass-fibre reinforced	N
Degree of protection (IP)	IP68
Shock resistant	N
Colour	Natural colour
Bend radius protection/trumpet flare	N
With locknut	N
Model	Straight
Flat cable coupling	N
Strain relief	N
Operating temperature	-40-+100°C
Explosion-tested version	Y
For Ex-zone gas	None
For Ex-Zone dust	None
EMC-version	N

Packaging

Inner Quantity	2
Inner Dimensions (inches)	7.09x3.54x3.54

Outer Quantity	18
Outer Dimensions (inches)	11.81x11.81x7.87
Weight Uom	0.1 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com