



Actual

**Catalog Number:** EXN10MMC1  
**Product ID:** 7TCA297180R0080  
**UPC Number:** 78621019491  
**EAN Number:** 05011949230521  
**Status:** Active

Double Compression Cable Gland, M75 Thread, Flameproof Ex d and Increased Safety Ex e, Suitable for use with SWA, SWB, and AWA Conduit, IP66 Rating, Inner Cable Range 45 to 60mm, Outer Cable Range 54 to 70mm, Nickel Plated Brass

### North American Specifications (UNSPSC)

|                          |  |
|--------------------------|--|
| UNSPSC                   | 39121431 Cable gland connector   |
| IGCC                     | 4601 Cable gland connector   |
| Brand Name               | Kopex  |
| Type                     | Double Compression Gland   |
| Application              | For Use with SWA (Steel Wired Armoured), AWA (Aluminum Wired Armour), and SWB (Steel Wired Braid) Conduit to Provide Secure Cable Connections Through Knockouts and Threaded Entries |
| Standard                 | UL Listed, Approved to EN60079-0, 60079-1, 60079-7, 60079-31   |
| Size                     | M75  |
| Conductor Range          | Inner 45 to 60mm, Outer 54 to 70mm   |
| Material                 | Brass  |
| Finish                   | Nickel Plated  |
| Color                    | Metallic   |
| Insulation               | IP66 Rating  |
| Temperature Rating       | -40 to 100 Degrees C   |
| Environmental Conditions | Flameproof Ex d and Increased Safety Ex e, Suitable for Zones 1, 2, 21, 22   |

### European Specifications (ETIM)

|                                      |                            |
|--------------------------------------|----------------------------|
| ETIM                                 | EC000441 Cable screw gland |
| Thread type                          | Metric                     |
| Nominal thread size metric/PG        | 75                         |
| Pitch thread                         | 1.5mm                      |
| Thread length                        | 20mm                       |
| Hexagon angular dimension            | 110.5mm                    |
| Suitable for cable diameter          | 45.0-70.0mm                |
| Material                             | Metal                      |
| Material quality                     | Brass                      |
| Surface protection                   | Nickel-plated              |
| Halogen free                         | N                          |
| Glass-fibre reinforced               | N                          |
| Degree of protection (IP)            | IP68                       |
| Shock resistant                      | N                          |
| Colour                               | Natural colour             |
| Bend radius protection/trumpet flare | N                          |
| With locknut                         | N                          |
| Model                                | Straight                   |
| Flat cable coupling                  | N                          |
| Strain relief                        | N                          |
| Operating temperature                | -40-+100°C                 |
| Explosion-tested version             | Y                          |
| For Ex-zone gas                      | 1, 2                       |
| For Ex-Zone dust                     | 21, 22                     |
| EMC-version                          | N                          |

**Packaging**

|                           |                  |
|---------------------------|------------------|
| Inner Quantity            | 1                |
| Inner Dimensions (inches) | 7.09x3.54x3.54   |
| Outer Quantity            | 6                |
| Outer Dimensions (inches) | 11.81x11.81x7.87 |
| Weight Uom                | 4.32 lbs. Each   |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)