



Actual

Catalog Number: AT21/M20/CS90/BLB
Product ID: 7TCA296170R0263
EAN Number: 05020963046995
Status: Active

Adaptalok ATS, 90 Degree Conduit Fitting, Swivel External Male Thread, Nominal Conduit Size 21mm, M20 Thread, Polyamide (Nylon) 66, Nickel Plated Brass Thread/TPE, Black with Blue Elastomer

North American Specifications (UNSPSC)

| | |
|-------------|--|
| UNSPSC | 39121311 Electrical fittings |
| IGCC | 4441 Electrical fittings |
| Brand Name | Adaptaflex |
| Type | Conduit Fitting with Metric Threads |
| Application | For Insertion into Threaded Entries or Knockout to Connect Conduit |
| Size | NC 21mm |
| Material | Polyamide/Nylon 6.6 |
| Color | Black/Blue Elastomer |
| Connection | 90 Degree |
| Cable Entry | M20 Thread |

European Specifications (ETIM)

| | |
|---|---|
| ETIM | EC001176 Screw connection for corrugated plastic hose |
| Nominal diameter | 21mm |
| Degree of protection (IP) | IP68 |
| Model | 90°-elbow |
| Revolving thread | Y |
| Construction type | External thread |
| Type of connection | Snap connection |
| Thread type | Metric |
| Thread connection size | M20 x 1.5 |
| Thread length | 11.2mm |
| Material | Polyamide |
| Colour | Black |
| Approved in combination with protective conduit UR | N |
| Approved in combination with protective conduit DIN EN 61386-23 | Y |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 1x1x1 |
| Weight Uom | 0.11 lbs. Each |

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com