

Catalog Number: ESM32-15B-LN
Product ID: 7TCA296250R0068
EAN Number: 05016947001104
Status: Active

Euro Index Cable Gland, M32 Thread, 17.0-25.0mm Cable Range, 37.0mm Gland Depth, 45.5mm Gland Diameter, 41mm Across Flats Dimension, 50 Piece Pack, Polyamide 6.6 with Nitrile Rubber Seal, Black with Locknut

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Adaptaflex
Type	Euro Index Cable Gland with Locknut
Special Features	Integral claw design prevents cable twisting during installation
Application	Provide Strain Relief and Connection for Conduit Systems
Size	M32
Conductor Range	17.0 to 25.0mm
Material	Polyamide/Nylon 6.6 with Nitrile Rubber Seal
Color	Black
Insulation	IP68
Temperature Rating	-20 Degrees C to +90 Degree C

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	Metric
Nominal thread size metric/PG	32
Thread length	12mm
Wrench width	41mm
Hexagon angular dimension	45.5mm
Suitable for cable diameter	17.0-25.0mm
Material	Plastic
Material quality	Polyamide (PA)
Surface protection	Untreated
Halogen free	Y
Glass-fibre reinforced	N
Degree of protection (IP)	IP68
Shock resistant	N
Colour	Black
RAL-number	9005
Bend radius protection/trumpet flare	N
With locknut	Y
Model	Straight
Flat cable coupling	N
Strain relief	N
Operating temperature	-20-+90°C
Explosion-tested version	N
For Ex-zone gas	None
For Ex-Zone dust	None
EMC-version	N

Packaging

Outer Quantity	50
Outer Dimensions (inches)	20x3x18
Weight Uom	0.03 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com