Lead Free Washing Machine Valves





Washing Machine Valves

Heavy-duty Lead Free Bronze

Features & Benefits

- Heavy duty lead free bronze construction
- No-leak O-ring bonnet & stem
- Long-lasting EPDM seals
- Available in various inlet connections
- 3/4" male hose thread outlet
- Maximum pressure: 125 PSI
- Maximum temperature: 180°F

- 8-9 GPM flow rate
- 3-year limited warranty
- NSF/ANSI 372 certified lead free by IAPMO
- Suitable for potable drinking water applications
- Nickel Plated finish



Base Models





221CCLF

1/2" compression inlet x 3/4" male hose thread outlet

1/2" FIP Boiler Drain



247LF

1/2" female iron pipe inlet x 3/4" male hose thread outlet

1/2" FIP x MIP, With Bypass & Plug



248LF

1/2" FIP inlet x 1/2" MIP outlet, with reversible bypass 3/4" hose thread & plug

1/2" FIP, Top Handle



249LF

1/2" female iron pipe inlet x 3/4" male hose thread outlet

1/2" FIP Bypass



250LF

1/2" female iron pipe inlet x 3/4" hose thread outlet & 1/2" MIP bypass outlet

Repair & Replacement Parts

Stem Repair Parts Kit



PK1000

Seat washer (2) & screw (1), nylon bonnet washer (4) & handle screw (7)

Replacement Stem Replacement Tee



PK1260

Burnished tee handle (6) & handle

Complete stem & bonnet replace-

PK1110

Assembly

ment (nickel plated) (1-5)

Compression Nut & Ferrule



PK1170

Replacement compression nut & ferrule- nickel plated (#8-9)

Replacement Hose Connection & Plug



PK1200

Hose, plug and washers for 248LF series valves (# 10-11)











