

VFK SERIES

FAN FORCED WALL HEATERS

- HIGH CAPACITY UP TO 4800 WATTS
- THREE PIECE DESIGN
- SLIM SURFACE OR RECESSED MOUNTING
- EASY TO INSTALL AND SERVICE

- NORTHERN WHITE LOUVERED COVER
- TWO-POLE THERMOSTAT
- BUILT-IN THERMAL CUTOUT, FAN DELAY



APPLICATIONS

Berko's high-capacity, heavy duty fan forced wall heaters are designed for use almost anywhere in residential, commercial or industrial areas requiring electric fan forced heaters in 1500 to 4800 watt capacities. They perform exceptionally well in such applications as motels, entryways, playrooms, basements, workshops, garages, stores and similar large areas.

MOUNTING LIMITATIONS

- 1. For wall mounting Do not install back box closer than 8 inches from floor or adjacent wall.
- Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where air flow may be obstructed.

Thermostat range 40° to 90°F Air movement 100 CFM



SELECTION CHART

14-5/8" \(\frac{1}{1-1/4"}\)	1-5/8* - - - - - - - - - - - - -	
		18-1/4"
15-3/4"	-	3-7/8"

CATALOG NO.	VOLTS	WATTS	PH	BTU/HR.	AMPS	
VFK151	120	1500	1	5120	12.5	
VFK204	240	2000	1	6826	8.3	
VFK304	240	3000	1	10239	12.5	
VFK404	240/208	4000/3000	1	13652/10239	16.7/14.4	
VFK484	240/208	4800/3600	1	16382/12287	20.9/17.3	
VFK4083	208	4000	3	13652	11.1	
VFK487	277	4800	1	16382	17.3	
VFK488	208	4800	1	16382	23.1	
VFK4883	208	4800	3	16382	13.3	

ACCESSORIES

CATALOG NO.	DESCRIPTION
VFKSM	Surface Mounting Frame.
VFKS-1	1" Semi-Recessed Frame.
VFKS-2	2" Semi-Recessed Frame.
VFK-SFK	14 Gauge Security Front Cover.